AD 740 990

# ENCAPSULATION A DOC BIBLIOGRAPHY

DDC-TAS-72-19-1

**MAY 1972** 

Approved for public release; distribution unlimited.

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
Springfield, Va. 22151



**UNCLASSIFIED** 

Deirense Documentation Ceinter detense supply agency

UNCLASSIFIED						
Security Classification						
	MENT CONTROL DAT	*				
(Security classification of title, body of abstract ORIGINATING ACTIVITY (Corporate author)	ct and indexing annulation i	بر انجوب به بهروان بها بازند و المام المام و	SECURITY GLASSIFICATIONS			
DEFENSE DOCUMENTATION CENTER			UNCLASSIFIED			
Cameron Station		Zb. GHOUP	26. GHOUP			
Alexandria, Virgiria 22314						
REPORT TITLE						
ENCAPSULATION						
DESCRIPTIVE NOTES (Type of report and inclusive, c Bibliography (October 195	(atea) 15 = Santambay	1671 Y	·			
AUTHOR(S) (First name, middle initial, last name)	o - Septembey					
			-			
REPORT DATE	70. TOTA	L NO. OF PAGES	76. NO. OF REFS			
May 1972	<u> </u>	1-1-4	, 77.			
COCTRACT OR GRANT NO.	Se. ORIG	NATON'S REPORT N	IMBERISI (**)			
	ļ		A 7			
, PRÔJECT NO.	וט	C-TAS-72-1	9-1			
•	9b. OTHE	R REPORT NO(S) (An	y other numbers that may be easigned			
•	this n	this report)				
<b>1.</b>	Į AI	740 990				
1. SUPPLEMENTARY NOTES	12. SPON	SORING MILITARY AC	TIVETY			
			•			
	` (					
S. ABSTRACT						
	•					
Encapsulation used as	s a protectiv	covering	for electronic			
circuits, insulation from						
and thin film coatings of	capacitors.	is the subj	ect of this			
bibliography. References						
deterioration effects are			·			
	, , ,					
Corporate Author-Mon.	itoring Agenc	, Subject,	Title, and:			
Personal Author Indexes a	re included.					
	•	· .				

DD . FORM .. 1473

UNCLASSIFIED
Security Classification

Security Classification		LINKA		LINK B		LINK C	
ALT WALL AND THE PROPERTY OF T	ROLE	£ÇWY.	ROLE.	WT	ROLE	ΨT	
		,		,			
#Dibliographics	, <b>j</b>		ľ.				
*Bibliographies *Encapsulation Embedding Substances		1	1		2	, ,	
Embedding Substances		:	ì	}	) ,	ĺ	
Iransistors	,	١.		ľ			
Manufacturing Methods			1	ľ			
Films	1 .						
Aerosols			ί.				
Lacquer Films	, j	1		1		c	
Coatings				l	:		
Electronic Equipment Integrated Circuits			. 1	`	,		
Mica		1		١			
Microminiaturization(Electronics)		ï					
Naval Equipment		1	.,		ľ l		
Naval Equipment Packaged Circuits	<u> </u>			<b>'</b>			
Packaging		l					
Dielectrics	ļ	_	<u>'</u>				
			, `	ľ			
	ļ ·	ļ		·	r		
	1	1		,	l. 1		
						,	
	, 7	ł		·	ť		
	ľ						
	1			,	<u> </u>		
		,	,		1 1		
						,	
	l				ŀ l		
						1	
	<b>.</b> `		ř l				
		ŀ					
	ľ						
					ŀl		
	1		Ì	<b>,</b>	] ]		
					] ]		
					)		
	,	<b>]</b> ;			, ,		
	Ä						
					1 1		
			,				
	1				ŀ [		

UNCLASSIFIED
Security Ciassification

AD- /47 490

## ENCAPSULATION A DDC BIBLIOGRAPHY

DDC-TAS-72-19-1

October 1955 - September 1971

MAY 1972

Approved for public release; distribution unlimited.

DEFENSE DOCUMENTATION CENTER

DEFENSE SUPPLY AGENCY

CAMERON STATION

ALEXANDRIA, VIRGINIA 22314

UNCLASSIFIED

#### F-OREWORD

This bibliography contains the pertinent (weighted) references in the DDC collection on *Encapsulation*. The time coverage is January 1953 to January 1972. In addition to the weighted references, it also contains selective citations related to the subject.

Corporate Author-Monitoring Agency, Subject, Title, and Personal Author Indexes are included.

BY ORDER OF THE DIRECTOR, DEFENSE SUPPLY AGENCY

**OFFICIAL** 

MARERT P STECHAR

Administrator

Defense Documentation Center

## C O N T E N T S

<u> </u>	age
FOREWORD	iii
AD BIBLIOGRAPHIC REFERENCES	1
<u> </u>	
CORPORATE AUTHOR-MONITORING AGENCY	01
SUBJECT	D-1
ŤĬŤLĖ	T-1
PERSONAL AUTHOR	P- ]

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. ZZZHT

APHY ELECTRONICS GABS FORT MONMOUTH N J.

ENCAPSULATING RESINS AND POTTING COMPOUNDS

( U:5-

REPT. NO. ER E 1101

UNGLASSIFIED REPORT

DESCRIPTORS: \*EMBEDDING SUBSTANCES, \*PLASTICS, ENCAPSULATION

t M s

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. 2222HT

AD-251 485 GÉMÉRAL ELECTRIC CO ÚTICA N Y

RESEARCH AND DEVELOPMENT OF THERMOCOUPLE ENERGY (U)

DESCRIPTIVE NOTE: MONTHLY PROGRESS REPT. NO. 4, 29 DEC 60-28 JAN 61 AUG 60 9P CONTRACT: DA-18-108-405-CHL-941, DA-18-108-CHL-6561

UNCLASSIFIED REPORT

DESCRIPTORA: \* ENCAPSULATION, \*THERMOCOUPLES, DESIGN, LEAD COMPOUNDS, PRODUCTION, TELLURIDES, THEORY (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-255 010 - Stanford Reséarch inst mento park calif

ENCAPSULATED AEROSOLS

(U)

IV ROBBINS, ROBERT C.;

UNCLASSIFIED: REPORT

DESCRIPTORS: \*AEROSOLS, \*CHEMICAL WARFARE AGENTS, \*COATINGS, \*ENCAPSULATION, AMMONIUM COMPOUNDS, BENZENEBORONIC ACID, CHLORIDES, COAGULATION, CONDENSATION, DIOXIDES, ELECTROSTATICS, ETHYLENES, FILMS, LIQUIDS, NITROGEN COMPOUNDS, PHOSPHATES, PHOSPHITES, PHOSPHORIC ACIDS, PHILALATES, POLYMERIZATION, ROLYMERS, SOLIDS, VAPORS

(U)

WARLOUS METHODS OF AEROSOL ENCAPSULATION WERE STUDIED: (1) LIQUID PHASE MICROENCAPSULATION! (2) CONDENSATION: AND (3) COAGULATION. AEROSOL ENCAPSULATION BY CONDENSATION, USING THE CORE PARTICLES OR DROPLETS AS CONDENSATION NUCLEI. PROVED TO BE A GENERALLY SUCCESSFUL TECHNIQUE. COAGULATION WITH INERTIAL FORCES, USING SIMPLE LOW- . POWERED DEVICES, SHOWED LITTLE PROMISE AS A PRACTICAL AEROSOL ENCAPSULATION METHOD. COAGULATION WITH ELECTROSTATIC CHARGING OF THE PARTICLES WAS ONLY PARTIALLY SUCCESSFUL IN SOLID ON LIQUID AND LIQUID ON LIQUID SYSTEMS, BUT WORKED QUITE WELL IN ENCAPSULATING SOLID CORES WITH LIQUID FILMS. LIQUID PHASE MICROENCAPSULATION WAS QUITE SUCCESSFUL, WHERE APPLICABLE. A NUMBER OF LIQUID CORES WERE SUCCESSFULLY POLYERSED. (AUTHOR) (U)

DOC REPORT BIBLEOGRAPHY SEARCH CONTROL NO. ZZZNT

AD-299 962 MAVAL ORDNANCE TEST STATTION CHINA LAKE CALIF

EFFECT OF PROCESS VARIABLES ON THE DIMENSIONS AND QUALITY OF EXTRUSION-COATED PROPELLANT GRAINS (U).

DEC 60 IV METCALF, H.F. SUTHERLAND, RODNEY; REPT. NO. TP 2597
MONITOR: NAVWEPS 7604

UNCLASSIFIED REPORT

DESCRIPTORS: OCOATINGS, OFNCAPSULATION, OEXTRUSION, OPLASTIC COATINGS, OPROPELLANT GRAINS, CELLULOSE, ETHYL CELLULOSE, MACHINE TOOLS, MANUFACTURING METHODS, PROCESSING, QUALITY CONTROL, SOLID ROCKET PROPELLANTS (1)

THE SECOND PHASE OF AN EXPERIMENT TO EVALUATE AN EXTRUSION-COATING PROCESS FOR INHIBITING ROCKETPROPELLANY GRAINS WITH ETHYLCELLULOSE IS DESCRIBED. THE OBJECTIVES OF THIS PHASE OF THE EXPERIMENT ARE TO APPLY A SET OF CHOSEN OPERATING CONDITIONS IN THE 2 1/2-INCH EXTRUDER AND TO CONSIDER THE EFFECT OF EIGHT ADDITIONAL PROCESS FACTORS ON THE QUALITY AND DIMENSIONS OF THE INHIBITED PROPELLANT GRAINS. DATA RESULTING FROM THESE APPLICATIONS ARE PRESENTED IN TABULAR AND GRAPHICAL FORM, AND AN INTERPRETATION OF THE DATA IS INCLUDED IN THE TEXT.

#### UNCLASSIBLED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

ADEZET 829 Western Electric to inc Winston-Salem N C

INDUSTRIAL PREPAREDNESS STUDY. LACQUER FILM

(U)

MAY 51 YV LLOYD H.E.; CONTRACT: DASS 0595081268

UNCLASSIFIED REPORT

DESCRIPTORS: \*CAPACITORS, ALUMINUM COATINGS, CELLULOSE ACETATES, COATINGS, DIELECTRIC FILMS, ELECTRIC INSULATION, ENCAPSULATION, FILMS, MANUFACTURING METHODS, METAL COATINGS, PAPER, PLASTIC COATINGS, PRODUCTION, QUALITY CONTROL, RESISTANCE (ELECTRICAL), TESTS, THIN FILMS, (STORAGE DEVICES), VARNISHES (U) IDENTIFIERS: THIN FLAS, THIN FILMS ELECTRONICS

EFFORT HAS BEEN STRECTED PRIMARILY TOWARD.

IMPROVEMENTS THE QUALITY OF THE LACQUER FILM

CAPACITORS DIFFICULTIES EXPERIENCED WITH

DETERIORATION OF INSULATION RESISTANCE AND EFFECTIVE

SERIES RESISTANCE UPON THE APPLICATION OF HEAT HAVE

BEEN RESOLVED. ALSO. EXCESSIVE CAPACITANCE GROWTH

HAS BEEN BROUGHT UNDER CONTROL. DATA WERE PRESENTED

TO SHOW THE PRESENT LEVEL OF QUALITY. ALSO.

PREVIOUSLY COLLECTED DATA IS USED TO MAKE COMPARISONS

WIT THE CURRENT EXPERIENCE. PREPRODUCTION SAMPLES

FOR THE 1.0 AND 0.1 MICROFARAD SIZES ARE UNDERGOING

ELECTRICAL TEST. SAMPLES FOR THE 5.6 MICROFARAD

SIZE ARE IN AN ADVANCED STAGE OF PRODUCTION.

(AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT.

AD-258 395 SYNTHETIC MICA CO WEST CALDWELL N.J.

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC.
MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC
COMPONENTS
(U)

NOV 6D 1V BARR, F.A. IMCCARTHY, J.P. F. CONTRACT: NOBS78714

UNCLASSIFIED REPORT

DESCRIPTORS: DEMBEDDING SUBSTANCES, DENCAPSULATION,

MICA, ALUMINUM COMPOUNDS, BINDERS, COATINGS,

DIELECTRICS, ELECTRICAL PROPERTIES, ELECTRONIC

EQUIPMENT, GLASS, HIGH-TEMPERATURE RESEARCH, MATERIALS,

PHOSPHATES, PHYSICAL PROPERTIES, POROSITY

(U)

INCREASING THE CONCENTRATION OF AQUEOUS ALUMINUM PHOSPHATE DECREASED THE POROSITY OF PHOSPHATEBONDED SYNTHETIC MICA COMPOUND. POROSITY CAN BE DECREASED BY GLASS COATINGS BUT THE THERMAL EXPANSION OF THE GLASS MUST MATCH THAT OF THE SAMPLE. A VOLUME SHRINKAGE OF APPROXIMATELY 7% WAS CALCULATED FOR A STANDARD PHOSPHATE-BONDED SYNTHETIC MICA COMPOUND. INITIAL RESULTS OF ELECTRICAL PROPERTIES AT ELEVATED TEMPERATURES INDICATE THAT THE PHOSPHATE-BONDED SYNTHETIC MICA SYSTEMS ARE SUITABLE FOR 500 C USE. COMMERCIAL ELECTRONIC COMPONENTS (MAGNETIC AMPLIFIERS, CAPACITORS, AND SMALL MOTORS) WERE SUCCESSFULLY POTTED AND ENCAPSULATED WITH THE BONDED SYNTHETIC MICA COMPOUND. (AUTHOR)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-260 926

STANFORD RESEARCH INST MENLO PARK CALIF

ENCAPSULATED AEROSOLS

(0)

IV ROBBINS, ROBERT C.;

UNCLASSIFIED REPORT

DESCRIPTORS: \*AFROSOLS, \*ENCAPSULATION, ACETAES, ACRYLIC RESINS, BUTYL RADICALS, CHEMICAL WARFARE AGENTS, COATINGS, CONDENSATION, CONTAINERS, ETHYLENES, FILMS, LIQUIDS, NITROCELLULOSE, PHOSPHITES, POLYMERIZATION, POLYMERS, RUBBER, VAPORS, VINYL RADICAL (U)

CONDENSATION POLYMERIZATION OF A NUMBER OF VAPOR PHASE MONOMERS, AS A MEANS OF ENCAPSULATING AEROSOL DROPLETS. WAS STUDIED. THE BEST OF THESE, VINYL ACETATE, POLYMERIZED RAPIDLY AND PRODUCED SOME POLYMER FILM ENCAPSULATION OF THE AEROSOL DROPLETS. A TWO-STAGE MICROCAPSULE GENERATOR WAS DESIGNED, FABRICATED, AND OPERATED. DIBUTYL PHOSPHITE DROPLETS OF ABOUT 5-MICRON DIAMETER WERE ENCAPSULATED WITH A LIQUID GLYCERINE FILM. BY USING SOLUTIONS OF ENCAPSULATING MATERIAL, THE GENERATOR ALSO PRODUCED MICROCAPSULES OF DIBUTYL PHOSPHITE IN POLYETHYLENE, NITROCELLULOSE, AND NATURAL RUBBER. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. JZZZHT

AD-261 938
BELL TELEPHONE LABS INC WHIPPANY N J

ENGINEERING SERVICES ON TRANSISTORS

(U)

MAY 61 1V ATALLA, M.M. IDODSON, G.A.; CONTRACT: DA36 0395C85352

UNCLASSIFIED REPORT

DESCRIPTORS: \*DIODES, \*TRANSISTOR AMPLIFIERS, \*TRANSISTORS, AGING (PHYSIOLOGY), DESIGN, ELECTRICAL PROPERTIES, ENCAPSULATION, FAILURE (MECHANICS), GERMANIUM, IMPUPITIES, MEASUREMENT, MICROWAVE EQUIPMENT, RELIABILITY, SILICON, STORAGE, STRESSES, SWITCHING CIRCUITS, TEMPERATURE, TEST METHODS, TESTS (U)

STUDIES AND INVESTIGATIONS WERE CONTINUED ON TRANSISTORS AND TRANSISTOR-LIKE DEVICES WITH A VIEW TOWARD DEMONSTRATING AND INCREASING THE PRACTICABILITY OF THEIR USE IN OPERATING EQUIPMENT. STATUS REPORTS ARE PRESENTED ON: (1) ACCELERATED STEP-STRESS AGING OF DIODES, (2) A DOOD-MC MICROWAVE GERMANIUM TRANSISTOR, (3) A 1-WATT, 1000 MC GERMANIUM TRANSISTOR, (4) INTEGRATED CIRCUIT DEVELOPMENT, (5) TRANSISTOR REQUIREMENTS FOR DCTL, AND (6) AN ANALYSIS OF STORAGE TIME BEHAVIOR OF DIFFUSED EPITAXIAL SILICON TRANSISTORS. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-265 314 STANFORD RÉSEARCH INST MENLO PARK CALIÉ

ENCAPSULATED AFROSOLS

(U)

IV ROBBINS ROBERT C.;

UNCLASSIFIED REPORT

DESCRIPTORS: \*AEROSOLS, \*ENCAPSULATION, AEROSOL GENERATORS, BUTYL RADICALS, CHEMICAL WARFARE AGENTS, COATINGS, DESIGN, DROPS, EFFECTIVENESS, ETHYLENES, LIQUIDS, PHOSPHITES, POLYMERS, RUBBER, WAXES

A TWO-STAGE MICROCAPSULE GENERATOR HAS BEEN UTILIZED TO PRODUCE A VARIETY OF LIQUID COME MICROCAPSULES. A NUMBER OF OPERATIONAL AND DESIGN CHANGES HAVE BEEN MADE TO IMPROVE THE PERFORMANCE OF THE GENERATOR AND TO INCREASE ITS VERSATILITY. THE GENERATOR HAS BEEN USED TO PROVIDE MICROCAPSULES OF DIBUTYL PHOSPHITE IN RUBBER. DIBUTYL PHOSPHITE IN PARAFFIN. AND DIBUTYL PHOSPHITE IN POLYETHYLENE. STUDIES WERE MADE OF THE EFFECT OF FILM COATING ON THE EVAPORATION RATE OF DIBUTYL PHOSPHITE MICRODROPLETS. AN INVESTIGATION WAS MADE OF THE EFFECT OF SOLUTION CONCENTRATION ON COAT THICKNESS IN SPRAYDRIED MICROCAPSULES. NOZZLE PESIGN WAS FOUND TO BE A CRITICAL PARAMETER. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-269 461 GENERAL ELECTRIC CO SYRACUSE N Y

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS (U)

DEC 60 IV KLEIN, PHILIPP H.; CONTRACT: NOBS78403

UNCLASSIFIED REPORT

DESCRIPTORS: \*ELECTRIC POWER PRODUCTION, \*GENERATORS, \*THERMAL CONDUCTIVITY, \*THERMOELECTRICITY, ANTIMONY ALLOYS, BISMUTH ALLOYS, CALCIUM COMPOUNDS, CHROMIUM COMPOUNDS, ENCAPSULATION, HEAT TRANSFER, INTERMETALLIC COMPOUNDS, LEAD COMPOUNDS, MAGNESIUM COMPOUNDS, MATERIALS, SILICATES, TANTALUM, TELLURIDES, THERMAL INSULATION

DESCRIPTORS: .THERMOELECTRICITY, .GENERATORS, OTHERMAL CONDUCTIVITY, ENCAPSULATION, LEAD COMPOUNDSC COMPOUNDS, BISMUTH ALLOYS. CONSIDERATION OF THERMAL SYSTEM NO. 1 WAS CONTINUED. THE SOURCE OF HEAT FOR THIS SYSTEM IS SATURATED STEAM AT 533 K (500 F), AND THE HEAT SINK IS SEA WATER AT 291 K (65 F) . RESULTS FOR FORCED-CONVECTION COOLING HAVE BEEN COMPARED WITH THOSE FOR FREE-CONVECTION COOLING. IN ADDITION, THE POSSIBLE IMPROVEMENTS IN PERFORMANCE THAT MAY RESULT FROM USE OF BETTER THERMOELECTRIC MATERIALS THAN ARE CURRENTLY AVAILABLE HAVE BEEN COMPUTED. THESE RESULTS WERE OBTAINED WITH THE AID OF A COMFUTER PROGRAM DESIGNATED NOBS-2. PROGRESS WAS ALSO MADE IN THE PREPARATION OF COMPUTER PROGRAM NOBS-3, WHICH PROVIDES A MORE ACCURATE REPRESENTATION OF THE LOSSES IN ELECTRICAL CONDUCTORS, ELECTRICAL CONTACTS, AND THERMAL SHUNTS THAN IS POSSIBLE WITH THE NOBS-2 PROGRAM. IN ADDITION. GENERAL CHARACTERISTICS HAVE BEEN EVOLVED FOR THE NEXT THERMAL SYSTEM TO BE ANALYZED. (AUTHOR) (U)

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-265 499
SYNTHETIC MICA CO-WEST CALDWELL N J

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC
MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC
COMPONENTS (U)

MAY 61 1V BARR, F.A., MCCARTHY, J.P.; CONTRACT: NOBS78714

UNCLASSIFIED REPORT

DESCRIPTORS: ODIELECTRICS, OELECTRONIC EQUIPMENT,
OF BEDDING SURSTANCES, DENCAPSULATION, MICA, ADHESIVES,
A NATES, ALUMINUM COMPOUNDS, BINDERS, BORON
COMPUUNDS, COATINGS, DIELECTRIC PROPERTIES, GLASS,
GYPSUM, HIGH-TEMPERATURE RESEARCH, MEASUREMENT,
MECHANICAL PROPERTIES, PARTICLES, PHOSPHATES, PHYSICAL
PROPERTIES, POROSITY, THERMAL EXPANSION:
THERMODYNAMICS

PHOSPHATE SYNTHETIC MICA WAS INVESTIGATED AS A DIELECTRIC MATERIAL FOR ENCAPSULATING AND EMBEDDING ELECTRONIC COMPONENTS FOR 500 C USE. PHYSICAL PROPERTIES OF THE SYSTEM WERE DETERMINED AND FOUND TO BE SUITABLE FOR HIGH TEMPERATURE USE. VARIOUS METHODS OF REDUCING POROSITY WERE INVESTIGATED INCLUDING DRY PRESSING, GLASS COATING, ADDITIVES AND VARIOUS PHOSPHATE BONDS. THE USE OF A DEVITRIFIED GLASS SEALING CEMENT AS A COATING FOR THE PHOSPHATE SYNTHETIC MICA RESULTED IN A COMPOSITE MATERIAL CURED BELOW 500 C. HAVING GOOD PHYSICAL PROPERTIES WITH WATER ABSORPTION LESS THAN 18. COMMERICAL CAPACITORS, TRANSFORMERS, AND MOTORS WERE ENCAPSULATED AND TESTED. PROTOTYPE HIGH TEMPERATURE RESISTORS WERE CONSTRUCTED AND ENCAPSULATED FOR 500 C APPLICATIONS USING CERAMO-PLASTIC INJECTION MOLDING TECHNIQUES IN COMBINATION WITH THE PHOSPHATE-MICA DIELECTRIC MATERIAL. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-265 857 GENERAL ELECTRIC CO SYRNOUSE N Y

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS (U)

FEB 61 1V LUFT-LOS CONTRACT - NOBS78403

UNCLASSIFIED REPORT

DESCRIPTORS: •ELECTRIC POWER PRODUCTION, •POWER SUPPLIES, •THERMOELECTRICITY, ANTIMONY ALLOYS, ARSENIDES, BISMUTH ALLOYS, CALCIUM COMPOUNDS, CERAMIC MATERIALS, CHEMICAL PROPERTIES, CHROMIUM COMPOUNDS, CRYSTAL STRUCTURE, DESIGN, ELECTRICAL PROPERTIES, ENCAPSULATION, GENERATORS, HALL EFFECT, HEAT, HEAT TRANSFER, INTERMETABLIC COMPOUNDS, LEAD COMPOUNDS, MAGNESIUM COMPOUNDS, MEASUREMENT, MECHANICAL PROPERTIES, OXIDES, SELENIDES, SOURCES, TANTALUM, TELLURIDES, TESTS

THE WORK ON A SELECTED SYSTEM, DESIGNATED THERMAL SYSTEM NO. 1, WAS COMPLETED USING A COMPUTER PROGRAM. THERMAL SYSTEM NO. 1 IS BASED ON SATURATED STEAM AT \$73 K, AS THE HEAT SOURCE AND 291 K WATER AS THE HEAT SINK. MGD-TIO2 CERAMIC WAS MADE INTO CAP ULE BODIES AND USED FOR SUCCESSFUL ENCAPSULATION OF LEAD TELLURIDE. SEEBECK COEFFICIENT OF MG3SB2 WAS MEASURED IN THE 300 TO 1250 K TEMPERATURE RANGE, THE VALUES RANGING FROM 100 TO 159 MICROVOLTS PER DEGREES K. ELECTRICAL MEASUREMENTS WERE PERFORMED ON CRSBO.9SEO.1. INCLUDING SEEBECK COEFFICIENT AND ELECTRICAL RESISTANCE. A NUMBER OF II-IV COMPOUNDS WAS PREPARED AND THEIR THERMOELECTRIC PROPERTIES MEASURED. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-265 866 LOCKHEED MISSILES AND SPACE CO SUNNYVALE CALIF

ENCAPSULATING, POTTING, AND EMBEDDING MATERIALS FOR ELECTRONIC COMPONENTS AND MODULES. AN ANNOTATED BIBLIOGRAPHY (U)

AUG 61 1V OWENS, GEORGE E. 1 REPT. NO. SB 61 50 CONTRACT: AF04 647 787

UNCLASSIFLED REPORT

DESCRIPTORS: •BIBLIOGRAPHIES, •EMBEDDING SUBSTANCES, •ENCAPSULATION, •INSULATING MATERIALS, ELECTRIC INSULATION, ELECTRONIC EQUIPMENT (U)

THIS BIBLIOGRAPHY RESULTS FROM A SEARCH FOR INFORMATION ON MATERIALS USED FOR ENCAPSULATING. POTTING. AND EMBEDDING ELECTRONIC COMPONENTS. THERE ARE 97 REFERENCES, ARRANGED BY TITLE, WITH PUBLICATION DATES BETWEEN JANUARY 1998 AND AUGUST 1961. FOLLOWING THE REFERENCES ARE INDEXES OF AUTHORS AND SPONSORS, JOURNAL SOURCES, AND REPORT NUMBERS. THE FOLLOWING SOURCES WERE CONSULTED DURING THE SEARCH: LMSC TECHNICAL INFORMATION CENTER CARD CATALOGS, APPLIED SCIENCE AND TECHNOLOGY INDFX, 1958-1961, ASTIA TECHNICAL ABSTRACT BULLETIN, 1958-1961, ELECTRICAL ENGINEERING ABSTRACTS, 1958-1961, ENGINEERING INDEX, 1958-1961, U.S. GOVERNMENT RESEARCH REPORTS, 1960-1961, AND PERTINENT JOURNALS, 1961. (AUTHOR)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. ZZZHT

AD-265 894
NATIONAL CASH REGISTER CO DAYTON OHIO

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID-ROCKET FUEL

(U.).

JUN 61 1V HSIĘH PÁUL Y .; CONTRACT: NONR284800

UNCLASSIFIED REPORT

DESCRIPTORS: \*AMIDES, \*DROPS, \*ENCAPSULATION, \*FILMS, \*HYDRAZINES, \*LIQUID ROCKET PROPELLANTS, \*METHYL HYDRAZINES, COATINGS, COPOLYMERIZATION, ETHYLENES, GELS, LIQUIDS, MEMBRANES, ORGANIC COMPOUNDS, PHYSICAL PROPERTIES, POLYMERIZATION, POLYMERS, PRODUCTION, ROCKET FUELS, ROCKET OXIDIZERS

THE PHENOMENA INVOLVED IN ENCAPSULATION FROM NONAQUEOUS MEDIA IS DISCUSSED. STUDIES INCLUDED: (1) ESTABLISHMENT OF THE ESSENTIAL CONDITIONS FOR THE ACCUMULATION OF MACROMOLECULES AROUNDA DISPERSED LIQUID DROPLET TO BE ENCAPSULATED (INTERNAL PHASE), (2) ENCAPSULATION OF LIQUIDS BY INTERFACIAL POLYMERIZATION APPROACH, AND (3) TESTING OF THE COMPATIBILITY OF ETHYLENE DIAMINE, 1,1-DIMETHYL HYDRAZINE, AND HYDRAZINE WITH VARIOUS SOLVENTS. AMINES, ESPECIALLY ETHYLENE DIAMINE, WERE SELECTED AS MODEL COMPOUNDS. (U)

DDG REPORT STALLOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-265 895 NATIONAL CASH REGISTER CO DAYTON OHLO

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUE.

(U)

JAN 64 1V HSTEH, PAUL You's CONTRACT: NONRENTHOO

UNGLASSIFIED REPORT

DESCRIPTORS: DENCAPSULATION, DETHYL CELLULOSE, DETIMES, OGASES, DAISTROCELLULOSE, DOLYMERS, DEMIPERHEABILITY, DAPORS, AMMONIA, ARGON, CARBON DIOXIDE, COATINGS, DIFFUSION, DIPOLE ANTENNAS, HELIUM, LIQUID ROCKET PROPELLANTS, MEMBRANES, NITROGEN, OXYGEN, PLASTIC GOATINGS, ROCKET FUELS, SOLUBILITY, SULFUR COMPOUNDS, WATER VAPOR

PERMEABILITY OF ETHYLCELLULOSE AND NITROCELLULOSE FILMS TO 13 DIFFERENT GASES AND VAPORS WAS DETERMINED. THE SOLUBILITY OF THESE GASES AND VAPORS IN ETHYLCELLULOSE AND NITROCELLULOSE WAS ALSO HEASURED Y GRAVIMETRIC AND VOLUMETRIC METHODS OF EQUILIBRIUM SORPTION. FROM THESE DATA FOR PERMEABILITY AND SOLUBILITY, DIFFUSION CONSTANTS OF THE GASES AND VAPORS IN THE POLYMERIC FILMS WERE CALGULATED BY MEANS OF THE RELATION, P EQUALS DS. IT WAS FOUND THAT THE DIFFUSION CONSTANT DECREASED LINEARLY WITH AN INCREASE OF MOLECULAR WEIGHT! HOWEVER. THE SHAPE FACTOR OF THE MOLECULES PLAYED AN IMPORTANT ROLE IN DIFFUSION. THE SOLUBILITY CONSTANTS DECREASED LINEARLY WITH AN INCREASE OF THE LENMARD-JONES FORCE CONSTANTS WHEN SOLUBILITY WAS EXPRESSED ON , 94P. INCL. IL WEIGHT BASIS RATHER THAN A VOLUME BASIS. IT IS POSSIBLE TO ESTIMATE PARMEABILITIES OF OTHER GASES AND VAPORS IN THESE FILMS FROM THEIR MOLECULAR WEIGHTS AND LENNARD+ JONES FORCE CONSTANTS. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. YZZZHT

- AD-266 P61 Synthetic Mica Co West Caldwell N J:

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRONIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS (U)

FEB 61 IV BARR, F.A. IMCCARTHY, J. A. S. CONTRACT: NOBS75714

UNCLASSIFIED REPORT

DESCRIPTORS: •EMBEDDING SUBSTANCES, •ENCAPSULATION,
•MICA, ALUMINUM COMPOUNDS, BINDERS, BORATES, CASTING,
DIELECTRIC PROPERTIES, DIELECTRICS, ELECTRICAL
PROPERTIES, ELECTRONIC EQUIPMENT, GLASS, LEAD COMPOUNDS,
MOLDING MATERIALS, PHOSPHATES, PHYSICAL PROPERTIES,
POROSITY, PRESSURE, PROCESSING, SILICONES, SYNTHETIC
RUBBER

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-274 642
DEPUTY COMMANDER AEROSPACE SYSTEMS INGLEWOOD CALIF

CRYSTAL GROWTH AND CRYSTALLOGRAPHY. A LITERATURE SURVEY

(U)

JAN 62 IV CHERON, THEODORE; REPT. NO. TDR62 5 CONTRACT: AFO4 647 930

MONITOR: DEAS TOR62 5

UNCLASSIFIED REPORT

DESCRIPTORS: •BIBLIOGRAPHIES, •CORUNDUM, •CRYSTALS, •GARNET, •RUBY, •SPINELS, ALUMINUM COMPOUNDS, CRYSTAL STRUCTURE, FERRITES, GROWTH, LASERS, METALLIC COMPOUNDS, OXIDES, PREPARATION, REFRACTORY MATERIALS, SAPPHIRES, SPECTROGRAPHIC ANALYSIS

THIS BIBLIOGRAPHY, CONSISTING OF 163 ENTRIES, COVERS THE PERIOD FROM 1990 TO 1961. IT REVIEWS THE LITERATURE ON THE PREPARATION OF CRYSTALS FOR LASERS, COVERING MAGNETIC AND NON-MAGNETIC GARNETS, RUBIES, CRYSTALLOGRAPHY, AND HIGH/ELTING METAL OXIDES. (AUTHOR)

DDC REPORT BIRLIOGRAPHY SEARCH CONTROL NO, /ZZZHT

AD-283 325 STANFORD RESEARCH INST MENLO PARK CALIF

ENCAPSULATED AEROSOLS

(U)

APR 62 IV ROBBINS, ROBERT C. ;

UNCLASSIFIED REPORT

DESCRIPTORS: •AEROSOLS, \*COATINGS, •ENCAPSULATION, AMMONIUM COMPOUNDS, BENZOIC ACIDS, CHEMICAL WARFARE AGENTS, CHLORIDES, COAGULATION, CONDENSATION, DIOXIDES, ELECTROSTATICS, ETHYLENES, FILMS, LIQUIDS, NITROGEN COMPOUNDS, PHOSPHATES, PHOSPHITES, PHOSPHORIC ACIDS, PHTHALATES, POLYMERIZATION, POLYMERS, SOLIDS, VAPORS (U)

METHODS OF AEROSOL ENCAPSULATION INCLUDED: PREENCAPSULATION, COLLECTION, THEN REDISPERSION: ENCAPSULATION BY CONDENSATION FROM A SUPERSATURATED VAPOR, OR BY CONDENSATION INVOLVING CATALYTIC POLYMERIZATION; AND VARIOUS COAGULATION METHODS. THE PHYSICAL AND CHEMICAL PROPERTIES OF THE CORE AND COAT MATERIALS DETERMINE THE RANGE OF APPLICABILITY OF EACH METHOD. A USEFUL MICROENCAPSULATION METHOD, BASED ON COAGULATION BY INERTIAL FORCE WAS DEVELOPED. THE GENERATION APPARATUS, CONSISTING OF TWO AEROSOL GENERATORS IN SERIES. WAS UTILIZED TO PRODUCE MANY KINDS OF MICROCAPSULES. A FLUID ENERGY MILL WAS FOUND USEFUL FOR THE PRODUCTION OF SOME MICROCAPSULES. THE PERMEABILITY OF MICROCAPSULE FILMS AND THE EFFECT OF EXPOSURE TIME AND HUMIDITY WERE STUDIED USING DIBUTYL PHOSPHITE CORES. PHYSICAL PROPERTIES OF MICROCAPSULE CORE AND COAT MATERIALS BELIEVED TO BE IMPORTANT IN ENCAPSULATION WERE MEASURED. (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHY

AD-284 0.5 SOUTHWEST RESEARCH INST SAN ANTONIO TEX

ENCAPSULATION OF FOODS

(U)

IV SCHUETZE, CLARKE E. IMCMAHON, WILLIAM

E.;

REPT. NO. TOR62 53

CONTRACT: AF33 616 7717

MONITOR: 6570 AMRL TDR62 53

UNCLASSIFIED REPORT

DESCRIPTORS: \*CONTAINERS. \*ENCAPSULATION, \*FOOD.
COATINGS, PRESERVATION, PROCESSING, SEACE FLIGHT (U)

BARRIER MATERIALS MESTING FOOD AND DRUG ADMINISTRATION STANDARDS WERE STUDIED FOR USE IN THE ENCAPSULATION OF FOODS. AND FOR THE PREPARATION OF SAMPLE CAPSULES OF FOOD ITEMS FOR EVALUATION. THE ENCAPSULATING MATERIAL MUST BE CAULE CONTENTS UNDER AMBIENT CONDITIONS AND ALSO IN HIGH TEMPERATURE AND HIGH VACUUM ENVIRONMENTS. THE FOOD IN THE CAPSULES MUST PEMAIN UNCONTAMINATED AND HIGHLY STABLE FOR SIX MONTHS WITHOUT REFRIGERATION. FOOD OF LOW MOISTURE CONTENT WERE ENCAPSULATED IN TWO STEPS, USING A SOFT-SHELLED CAPSULE WITH AN OVERWRAP. FUDGE, POUND CAKE, AND BROWNIES WERE FIRST PLACED IN PREFORMED CONTAINERS; CARAMELS AND PECANS WERE FIRST SPRAY CABLE OF MAINTAINING ITS ESSENTIAL PROPERTIES AND THOSE OF THE CAPSULE CONTENTS UNDER AMBIENT CONDITIONS AND ALSO IN HIGH TEMPERATURE AND HIGH VACUUM ENVIRONMENTS, THE FOOD IN THE CAPSULES MUST REMAIN UNCONTAMINATED AND HIGHLY STABLE FOR SIX MONTHS WITHOUT REFRIGERATION. FOODS OF LOW MOISTURE CONTENT WERE ENCAPSULATED IN TWO STEPS, USING A SOFT-SHELLED CAPSULE WITH AN OVERWRAP. FUDGE, POUND CAKE, AND BROWNIES WERE FIRST PLACED IN PREFORMED CONTAINERS; CARAMELS AND PECANS WERE FIRST SPRAY COATED. IN EACH CASE THE BITE-SIZED PORTIONS WERE HEAT-SEALED INTO PLASTIC BAGS. FOODS OF MODERATE MOISTURE CONTENT, EXEMPLIFIED BY MEAT, AND FOODS OF HIGH MOISTURE CONTENT. SUCH AS VEGETABLES AND FRUITS, WERE ENCAPSULATED IN LAMINATED CONTAINERS WITH AN OVERWRAP. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. ZZZHT

AD-286 907 PHILCO CORP LANSDALE PA

PEM FOR TRANSISTOR MANUFACTURING PROCESS IMPROVEMENT

(U)

JUL 62 IV SANDERS, J.;
REPT. NO. R 232 1
CONTRACT: DA36 0395C86720

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS), (\*MANUFACTURING METHODS), RELIABILITY, STRESSES, STORAGE, OPERATION, ENCAPSULATION, ELECTRODES, TEMPERATURE, SEALS(STOPPERS), DEGASIFICATION, CHEMICAL MILLING, HIGH-TEMPERATURE RESEARCH, PRODUCTION

(M)

A PRODUCTION ENGINEERING MEASURE WAS STUDIED FOR IMPROVEMENT OF PRODUCTION TECHNIQUES TO INCREASE THE RELIABILITY FOR THE JET ETCH TRANSISTOR TYPE 2N501A, WITH A MAXIMUM OPERATING FAILURE RATE OF 0.018 PER 1000 HOURS AT A 908 CONFIDENCE LEVEL AT 25 C AS AN OBJECTIVE. EFFORTS WERE MADE TO IMPROVE THE FOLLOWING SEVEN MANUFACTURING PROCESSES: (1) PLATING EDGE DEFINITION, (2) HIGHER TEMPERATURE ALLOYS, (3) LEAD ATTACHMENTS (INCLUDES COLLECTOR ATTACHMENTS), (4) CONTROLLED FORMATION OF SURFACE OXIDES FOR SURFACE STABILIZATION, (5) GETTERING TECHNIQUES FOR ENCAPSULATING AND SEALING, (6) THERMAL DISSIPATION OF PACKAGE, AND (7: LEAK DETERMINATION. ESTABLISHMENT OF A PILOT LINE TO INCORPORATE THESE PROCESS IMPROVEMENTS IS REPORTED. PRELIMINARY OPERATING STRESS DATA O TRANSISTORS FABRIC TED ON THE PILOT LINE INDICATES AN IMPROVEMENT IN POWER HANDLING CAPABILITY AS A RESULT OF THE PROCESS IMPROVEMENTS COMPLETED. PROBLEMS ASSOCIATED WITH OPERATING STRESS TESTING AND WITH OBTAINING CORRELATION BETWEEN OPERATING STRESS TESTING AND STORAGE STRESS TESTING ARE DISCUSSED. (AUTHOR)

(U)

DDC REPORT BIBLICGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-289 291
WESTINGHOUSE ELECTRIC CORP WASHINGTON D C

HIGH CURRENT AND HIGH VOLTAGE SILICON CONTROLLED RECTIFIERS (U)

OCT 62 1V CONTRACT: NCBSR87646

UNCLASSIFIED REPORT

DESCRIPTORS: \*POWER, \*RECTIFIERS, ALUMINUM, ANTIMONY, BORON, COOLING, CRYSTALLIZATION, CRYSTALS, DIFFUSION, ELECTRIC CURRENTS, ELECTRIC POTENTIAL, ENCAPSULATION, GOLD ALLOYS, MOLYBDENUM, SILICON, SWITCHING CIRCUITS, TRANSIENTS

DEVELOPMENT OF A HIGH CURRENT, HIGH VOLTAGE SILICON CONTROLLED RECTIFIER.

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-294 110
TOW SEMICONDUCTORS INC LAWNDALE CALIF

PRODUCTION ENGINEERING MEASURE RELIABILITY THRU PROCESS IMPROVEMENT

(U)

SEP 62 IV BARNES, S. H. CHIEN, F.;

UNCLASSIFIED REPORT

DESCRIPTORS: \*MANUFACTURING METHODS, \*TRANSISTORS, DIFFUSION, ELECTRICAL PROPERTIES, ENCAPSULATION, EVAPORATION, FAILURE (MECHANICS), LIFE EXPECTANCY, PROCESSING, PRODUCTION, QUALITY CONTROL, RELIABILITY (U)

EFFORT IS PRESENTED ON THE PRODUCTION ENGINEERING MEASURE TO INCREASE TRANSISTOR RELIABILITY. PROCESS IMPROVEMENTS WITHIN THE MAJOR TASKS OF MATERIAL EVALUATION, DIFFUSION AND PHOTORESIST, CONTACT METALLIZING, LEAD ATTACHMENT, AND ENCAPSULATION WERE ACCOMPLISHED. EMPHASIS WAS PLACED ON THE METHOD OF CONTACT METALLIZING AND LEAD ATTACHMENT. SAMPLE QUANTITIES OF DEVICES UTILIZING AN EVAPORATED ALUMINUM LAYER FOR BASE AND EMITTER CONTACTS WERE PLACED ON LIFE TEST. EQUIPMENT WAS RECEIVED TO REGIN ALUMINUM WIRE BONDING. FEASIBILITY TESTS TO DETERMINE STRESS LEVELS OF THE STEP-STRESS AGING WERE STARTED. RELIABILITY EVALUATION OF PRODUCTION DEVICES CONTINUED TO FURTHER SUBSTANTIATE THE FAILURE RATE BASIS FROM WHICH THE EFFECTS OF THE PROCESS IMPROVEMENT TASKS WILL BE MEASURED. (AUTHOR) (U)

DDC REPORT BIHLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-295 538
MCDONNELL AIRCRAFT CORP ST LOUIS MO

ELECTRICAL POTTING COMPOUNDS - SURFACE AND VOLUME RESISTIVITY AT ELEVATED TEMPERATURES FOR PROTRACTED TIMES (PHASE 11: ELECTRICAL TESTS) (U)

JAN 63 80P REPT. NO. 9354 CONTRACT: AF33 657 7749

UNCLASSIFIED REPORT

DESCRIPTORS: • ELECTRONIC EQUIPMENT, • EMBEDDING
SUBSTANCES, • ENCAPSULATION, CONTAINERS, ELECTRIC
CONNECTORS, ELECTRICAL PROPERTIES, PACKAGED CIRCUITS,
PLASTICS, RESISTANCE (ELECTRICAL), TEMPERATURE, TESTS(U)

POTTING COMPOUNDS FOR ELECTRONIC CIRCUITS; SURFACE AND VOLUME RESISTIVITY AT ELEVATED TEMPERATURE FOR PROTRACTED PERIODS OF TIME.

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-296 356 LOCKHEED MISSILES AND SPACE CO SUNNYVALE CALIF

INSPECTING AND TESTING OF EMBEDDING MATERIAL'S AND COMPONENTS OF ELECTRICAL MODULES BEFORE, DURING AND AFTER ASSEMBLY: A PARTIALLY ANNOTATED BIBLIOGRAPHY

(U)

NOV 62 1V PIERCE, CHARLIE M.;
REPT. NO. 5862 433 80 62 28

UNCLASSIFIED REPORT

DESCRIPTORS: •EMBEDDING SUBSTANCES, •ENCAPSULATION,
AGING (MATERIALS), BIBLIOGRAPHIES, CONTAMINATION,
DEGRADATION, EFFECTIVENESS, ELECTRON MICROSCOPY,
ELECTRONIC EQUIPMENT, EPOXY PLASTICS, ISOCYANATE
PLASTICS, MEASURING DEVICES (ELECTRICAL + ELECTRONIC),
MICROORGANISMS, MINE STERILIZERS, NON-DESTRUCTIVE
TESTING, PLASTICS, POLAROGRAPHIC ANALYSIS, PRINTED
CIRCUITS, RADIOGRAPHY, RESISTANCE (ELECTRICAL), SEALING
COMPOUNDS, SPACECRAFT, STRAIN GAGES, STRESSES, TEST
METHODS

AD-296 3569N4 +++BIBLIOGRAPHY ON INSPECTION AND TESTING OF EMBEDDING MATERIALS AND COMPONENTS OF ELECTRONICS MODULES BEFORE, DURING, AND AFTER ASSEMBLY. (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-412 282

LOCKHEED MISSILES AND SPACE CO SUNNYVALE CALIF

VACUUM DE-GASSING OF ENCAPSULANTS.

(U)

JUN 61 17P DEFELICE, A+;
REPT- NO. MRI267 D1

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ENCAPSULATION, MANUFACTURING METHODS), (\*MODULES ('LECTRONIC), DEGASIFI CATION), VACUUM APPAR, TUS, EPOXY PLASTICS, POLYETHYLENE PLASTICS, TEMPERATURE, TESTS, BUBBLES, CRAZING, HARDNESS, CASTING, IDENTIFIERS: 1961, VACUUM IMPREGNATOR.

(U)

(U)

PROCESSES AND TECHNIQUES FOR THE OPERATION OF THE VACUUM IMPREGNATOR FOR DE-GASSING THE RESINS USED FOR ENCAPSULATING ELECTRONIC MODULES IS REPORTED. A TOTAL OF 225 DISTINCT TESTS WERE RUN USING 9 DIFFERENT RESIN FORMULATIONS. RESIN TYPES IN CLUDED EPOXIES AND POLYURETHANES. TWO FACTORS. PRE-MIX TEMPERATURE OF INGREDIENTS AND APPLI CATION OF VACUUM WERE VARIED. THE RESULTING SAMPLES WERE EVALUATED FOR BUBBLES, CRACKS, CRAZING AND HARDNESS. APPLICATION OF VACUUM TO BATCHES PRIOR TO CASTING AND CURING PROVED EFFECTIVE FOR DE-GASSING ENCAPSULATING MATERIALS FOR MOST OF THE FORMULATIONS TESTED. TAKEN OVER ALL THE RESULTS VARIED WIDELY, RANGING FROM PERFECT TO UNACCEPTABLE. (AUTHOR)

(U)

DDC REPORT BIRLICGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-427 412
PICATINNY ARSENAL DOVER N J AMMUNITION ENGINEERING
DIRECTORATE

ENCAPSULATING PROPELLANTS BY MEANS OF ULTRASONIC WELDING, (U)

DEC 63 16P ZGLENICKI, CHARLES ISILBERMAN, LOUIS;
REPT. NO. AED-TM-1308

UNCLASSIFIED REPORT

#### SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*ULTRASONIC RADIATION, WELDING),
(\*PROPELLANT TANKS, WELDING), (\*WELDING, PROPELLANT
TANKS), ENCAPSULATION, ALUMINUM, TESTS, INDUSTRIAL
EQUIPMENT, STORAGE
(U)
IDENTIFIERS: ULTRASONIC WELDING, 1963

AN AL CONTAINER HOLDING M5 PROPELLANT HAS CAUSED FUNCTIONAL PROBLEMS BECAUSE OF INADEQUATE SEALING. THE ULTRASONIC WELDING APPROACH PROVIDED THE MOST EFFECTIVE AND DURABLE SEAL. ONE HUNDRED AND THIRTY-THREE CONTAINERS SEALED BY ULTRASONIC WELDING WITHSTOOD 28 DAYS TEMPERATURE CYCLING WITHOUT ANY DETECTABLE LEAKAGE. THIRTY-FIVE CONTAINERS FILLED WITH M5 PROPELLANT WERE TEMPERATURE-CYCLED AND EXPOSED TO A SOLVENT-SATURATED ATMOSPHERE FOR 11 DAYS. CLOSED BOMB TESTS OF THE PROPELLANT AFTERWARD INDICATED AN EFFECTIVE SEAL WAS ACHIEVED. METICULOUS ATTENTION TO SURFACE CLEANLINESS IS NOT REQUISITE TO ACHIEVE SOUND WELDS. FOIL THIN COVERS WHICH PRESENT A MINIMUM RESISTANCE TO PROPAGATION OF EXPLOSIVE EFFECTS CAN BE WELDED. PROPELLANT TRAPPED IN THE WELD ZONE DID NOT IGNITE. SIGNIFICANT COST SAVINGS CAN BE REALIZED IN HIGH VOLUME PRODUCTION OVER METHODS USING SPECIAL SEALANTS. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-430 751 NAVAL RESEARCH LAB WASHINGTON D C

ENCAPSULATION TECHNIQUES FOR NRL IRRADIATION EFFECTS STUDIES. (U)

DEC 63 23P STEELE, L. E. ; HAWTHORNE, J. R.

REPT. NO. NRL-MR-1481 PROJ: SROO7 01 01 TASK: 0858

UNCLASSIFIED REPORT

DESCRIPTORS: (\*STEEL, RADIATION DAMAGE), (\*CONTAINERS, DESIGN), ENCAPSULATION, NUCLEAR REACTORS, REACTOR MATERIALS, TEST REACTORS, MECHANICAL PROPERTIES, THERMAL RADIATION, POWER REACTORS, STAINLESS STEEL, ALUMINUM, TEST FACILITIES
IDENTIFIERS: 1963, NUCLEAR RADIATION

VARIOUS SYSTEMS AND TECHNIQUES FOR ENCAPSULATION OF IRRADIATION EXPERIMENTS HAVE BEEN DEVISED IN THE COURSE OF SEVERAL YEARS OF RESEARCH USING SEVERAL AEC TEST REACTOR FACILITIES. A CAPSULE DESIGN PHILOSOPHY HAS EVOLVED WHICH IS BASED UPON THE USE OF TWO TYPES OF CAPSULES. SEALED UNITS AND EXTERNALLY CONTROLLED UNITS FOR THE IRRADIATION OF LARGE NUMBERS OF METALLURGICAL SPECIMENS UNDER A RANGE OF THERMAL AND NUCLEAR CONDITIONS. THE BASIC PHILOSOPHY OF CAPSULE DESIGN IS DESCRIBED ALONG WITH SPECIFIC TECHNIQUES UTILIZED FOR VARIOUS TEST REACTOR CAPSULES AND FOR LONG-TERM POWER REACTOR SURVEILLANCE CAPSULES. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-432 229
NAVAL BOILER AND TURBINE LAB PHILADELPHIA PA

EVALUATION OF HIGH TEMPERATURE INSTRUMENTATION FOR DYNAMIC ANALYSIS. ENCAPSULATED STRAIN GAGE INSTALLATION FOR USE IN STEAM ENVIRONMENT. (U)

FEB 64 49P TOLOTTA, S. :

PROJ: A384

TASK: SF013 06 20 , SUBTASK 3950

UNCLASSIFIED REPORT

#### SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*STRAIN GAGES, STEAM), (\*BOILERS, INSTRUMENTATION), SEALS (STOPPERS), INSTALLATION), WELDS, ENCAPSULATION, FRACTURE (MECHANICS) THERMAL STRESSES, HIGH TEMPERATURE RESEARCH (U) 1DENTIFIERS: 1964

AN INSPECTION OF THE INTERIOR OF A STEAM DRUM ABOARD THE USS DECATUR REVEALED A CRACK EXTENDING AROUND THE UPPER HALF OF THE MANWAY. THE STRESSES CAUSING THE FAILURE WERE THOUGHT TO BE HIGHLY CONCENTRATED: THEREFORE, IT WAS NECESSARY TO USE A STRAIN GAGE WITH A SHORT GAGE LENGTH (1/8 IN) THAT COULD OPERATE IN A SATURATED STEAM ATMOSPHERE AT 1200 PSIG. BECAUSE THERE WERE NO KNOWN CEMENTS OR PROTECTIVE COATINGS WHICH WERE CAPABLE OF OPERATION IN THE PROPOSED ENVIRONMENT, IT WAS NECESSARY TO DEVELOP A SPECIAL GAGE INSTALLATION. THE UNIT DEVELOPED CONSISTED OF A STRAIN GAGE CEMENTED ATOP A STAINLESS STEEL SHIM WHICH HAD BEEN TACK WELDED TO THE TEST SPECIMEN AND THEN SEALED BY SILVER SOLDERING. THIS TYPE INSTALLATION WAS CAPABLE OF MEETING THE REQUIREMENTS. DETAILED INSTRUCTIONS FOR CONSTRUCTION, INSTALLATION AND CALIBRATION ARE DESCRIBED IN APPENDIXED INSTRUMENT STANDARDS. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD=433 654 PHILCO CORP LANSDALE PA

PEM FOR TRANSISTOR MANUFACTURING PROCESS IMPROVEMENT.

(U)

DESCRIPTIVE NOTE: FINAL PROGRESS REPT., 30 APR 62-31 DEC 63,
DEC 63 210P SANDERS, J. G.;
CONTRACT: DA36 D395C8672D
PROJ: R232

UNCLASSIFIED REPORT

#### SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),
(\*SPECIFICATIONS, PROCESSING), GERMANIUM, ELECTRODES,
NICKEL, TIN ALLOYS, ZINC ALLOYS, GALLIUM ALLOYS, HEAT
RESISTANT METALS AND ALLOYS, DEGASIFICATION,
ENCAPSULATION, EMISSIVI(Y, COATINGS, MASS SPECTROSCOPY,
TEST METHODS, LIFE EXPECTANCY, QUALITY CONTROL
(U)
IDENTIFIERS: JET ETCH TYPE TRANSISTOR, 1963, THERMAL
RESISTANCE

THE WORK FOR RELIABILITY IMPROVEMENT OF THE JET ETCH TYPE TRANSISTOR THROUGH PROCESS IMPROVEMENTS IS COMPLETE. THE REPORT INCLUDES THE OVER-ALL PROCESSING SPECIFICATION FOR THE IMPROVED TRANSISTOR. AND THE APPLICABLE INSPECTION AND QUALITY CONTROL PLAN. DATA ARE GIVEN ON THE FINAL TEST LOT OF THE IMPROVED DEVICE AND INDICATE THE LOT ACCEPTANCE TEST WAS PASSED. THE METHOD DEVISED FOR ACCELERATED TESTING AND EXTRAPOLATION OF RELIABILITY LEVELS UNDER USE CONDITIONS WAS EFFECTIVELY DEMONSTRATED. ACCUMULATED DATA ON TRANSISTORS PRODUCED USING THE IMPROVED PROCESSES SHOW THAT AN ACCELERATION CURVE HAVING A SLOPE EQUIVALENT TO AN ACTIVATION ENERGY OF 19.6 KCAL/ MOLE IS REALISTIC FOR THE IMPROVED DEVICE. THERMAL RESISTANCE MEASUREMENT STUDIES SHOWED THAT THE D-C BETA METHOD OF TEST WITH VOLTAGE COMPENSATION GIVES RESULTS THAT ARE REPRODUCIBLE AND CLOSELY APPROACH THE VALUES OF EFFECTIVE THERMAL RESISTANCE DETERMINED FROM OPERATING AND STORAGE LIFE TESTS. THE MAXIMUM OPERATING RATING OF THE II ROVED TRANSISTOR IS REPORTED AS 150 MW AT 25 C AT A LAMBDA = 0.78. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-435 114 RADIO-CORP OF AMERICA SOMERVILLE N J

PRODUCTION ENGINEERING MEASURE ON 2N1708 SILICON PLANAR EPITAXIAL TRANSISTOR. VOLUME 1. (U)

DESCRIPTIVE NOTE: FINAL REPT. 1 MAY 62-30 NOV 63.

NOV 63 160P GRANGER, G. F. POSSEMATO, L.

R. 1
CONTRACT: DA36 0395C86729

·

### UNCLASSIFIED REPORT

#### SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*TRANSISTORS, EPITAXIAL GROWTH),
RELTABILITY, SILICON, ELECTRONIC SWITCHES, ELECTRICAL
PROPERTIES, PROCESSING, MANUFACTURING METHODS, CRYSTAL
SUBSTRUCTURES, PHOTOENGRAVING, SEMICONDUCTOR DEVICES,
DIFFUSION, METALLURGY, GOLD ALLOYD; WIRE, GOLD,
ALUMINUM, PELLETS, ENVIRONMENTAL TESTS, FIXED CONTACTS,
METAL SEALS, NICKEL, ENCAPSULATED, STORAGE, TESTS,
STRESSES, ACCELERATION, FAILURE (MECHANICS),
DISSIPATION, OPERATION, LIFE EXPECTANCY, AGING
(MATERIALS), SWITCHING CIRCUITS
(U)

A PRODUCTION RUN WAS MADE TO DEMONSTRATE THE RELIABILITY ACHIEVED AS A RESULT OF PROCESS IMPROVEMENTS INCORPORATED INTO THE PROCESSING. A SUMMARY OF THE WORK PERFORMED IN EACH OF THE MAJOR PROCESSING AREAS TO EFFECT THE IMPROVEMENT IS DESCRIBED IN THIS REPORT. A PROGRAM OF LIFE TESTING. ANALYSIS OF EXISTING LIFE TEST DATA AND FAILURE ANALYSIS WAS PERFORMED CONCURRENTLY WITH THE WORK IN THE PROCESSING AREA. THIS PROGRAM INCLUDED ACCELERATED TESTING ON BOTH STORAGE AND OPERATING LIFE TESTS WHICH LEAD TO THE ESTABLISHMENT OF ACCELERATION CURVES. THE ANALYSIS OF RESULTS ON EXTENDED LIFE TESTS, THE ANALYSIS OF FAILURES, AND A STUDY OF THE EFFECT OF AGING. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-443 097
SYLVANIA ERECTRONIC SYSTEMS-WEST MOUNTAIN VIEW CALIF
ELECTRONIC DEFENSE LABS

NONCOMMUNICATIONS EXPENDABLE JAMMER INVESTIGATIONS.

VOLUME 3. MECHANICAL DEVELOPMENT, (U)

APR 64 55P FIRTH, MILTON ; REICHHOLD, RALPH; REPT. NO. EDL G220 , VOL. 3 CONTRACT: DA36 039AMC00088E

UNCLASSIFIED REPORT

#### SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*RADIO JAMMING, LANDING IMPACT), (\*LANDING IMPACT, PACKAGING), RADAR JAMMING, AIR DROP OPERATIONS, SEMICONDUCTOR DEVICES, MODULES (ELECTRONIC), SHOCK (MECHANICS), ENCAPSULATION, DROP TESTING, MATHEMATICAL ANALYSIS, SUBMINIATURE ELECTRONIC EQUIPMENT, MICROMINIATURIZATION (ELECTRONICS), SHOCK RESISTANCE, MOUNTING BRACKETS

[U]

RESULTS ARE REPORTED OF A STUDY TO DETERMINE OPTIMUM PACKAGING TECHNIQUES FOR THE ELECTRONIC EQUIPMENT AND THE SHOCK LEVELS THAT THE DIFFERENT PACKAGES AND CFRYAIN ELECTRONIC COMPONENTS COULD WITHSTAND, AS WELL AS LANDING TECHNIQUES AND SHOCK ATTENUATION DEVICES. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

ADH489 906 9/1 SPEER CARBON CO NIAGARA FALLS N Y

RESISTORS FOR MICROPOWER CIRCUITS.

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 4. 1 APR-30 JUN 66.

OCT 66 13P PARKS, CHARLES F.;
REPT. NO. SCC-24, R-140
CONTRACT: DA-28-043-AMC-01524(E)
PROJ: DA-1P6-22001-A-057
TASK: 1P6-22001-A-057-06
MONITOR: ECOM D1524-4

UNCLASSIFIED REPORT

DESCRIPTORS: (\*RESISTORS, DESIGN), SURFACE
PROPERTIES, OPTIMIZATION, ENCAPSULATION, ELECTRIC
CONNECTORS, ELECTRIC WIRE, PROCESSING,
PREPARATION, SUBSTRATES, ELECTRICAL PROPERTIES,
TEMPERATURE, RESISTANCE(ELECTRICAL),
NOISE(RADIO), FILMS
(U)
IDENTIFIERS: MICROPOWER RESISTORS

MICROPOWER RESISTORS OF 4.7 MEGOHM RESISTANCE VALUE HAVE BEEN PREPARED IN FINISHED FORM FOR TESTING ACCORDING TO SPECIFICATIONS. PRELIMINARY INVESTIGATIONS INCIDENT TO THEIR PREPARATION HAVE BEEN COMPLETED. THE STRENGTH OF SUBSTRATES HAS BEEN STUDIED, AND PROCESSING PARAMETERS IN THE PRESSING OPERATION HAVE BEEN EVALUATED. FABRICATION OF SUBSTRATES UNDER CONDITIONS INDICATED IN THIS INVESTIGATION HAS BEEN ACCOMPLISHED, AND SUBSTRATES OF SATISFACTORY STRENGTH HAVE BEEN PRODUCED. A NUMBER OF OTHER RESISTOR PROCESSING VARIABLES HAVE ALSO BEEN EXAMINED. THE SURFACE PREPARATION OF SUBSTRATES AND THE USE OF VARIOUS TERMINATING MATERIALS HAVE BEEN INVESTIGATED FOR EFFECTS ON RESISTANCE AND NOISE. IMPROVEMENT IN PROPERTIES OF RESISTORS HAS BEEN OBTAINED. DIFFERENT RESISTIVE PASTES HAVE BEEN COMPARED TO PERMIT SELECTION OF ONE PRODUCING AN OPTIMUM COMBINATION OF FIRED PROPERTIES. FIRED RESISTIVE FILMS ON THE NEW SUBSTRATE SYSTEM HAVE BEEN HELIXED SUCCESSFULLY USING THE IMPROVED HELIXING MACHINE, AND A NEWLY INSTALLED BRIDGE CIRCUIT HAS PERMITTED REPRODUCIBLE HELIXING TO VALUE. ENCAPSULATION OF HELIXED UNITS HAS BEEN INVESTIGATED AND EFFECTS ON RESISTANCE VALUE AND TEMPERATURE COEFFICIENT OF RESISTANCE HAVE BEEN FOUND TO BE ESSENTIALLY NEGLIGIBLE. (AUTHOR) (U)

UNCLASSIFIED

/ZZZHT

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-601 772 NATIONAL CASH REGISTER CO DAYTON OHIO

A STUDY OF THE ENCAPSULATION OF HIGH ENERGY SUBSTANCES.

(U)

DESCRIPTIVE NOTE: FINAL REPT. 1 APR 59-31 DEC 63.

APR 64 69P PETROPOULOS, CONSTANTINE C.;

CONTRACT: NONR2848 DO

UNCLASSIFIED REPORT

# SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*LIQUID ROCKET PROPELLANTS,
ENCAPSULATION), (\*ENCAPSULATION, LIQUID ROCKET
PROPELLANTS), (\*PLASTICS, COMPATIBILITY), FILMS,
PERMEABILITY, HYDRAZINE, POLYAMIDE PLASTICS, ARCYLIC
RESINS, POLYMERIZATION COPOLYMERIZATION
(U)
IDENTIFIERS: GLYCIDYL METHACRYLATE, HYDROXYETHYL
METHACRYLATES, METHALLYL METHACRYLATE; VINYLOXYETHYL
METHACRYLATES

INITIAL WORK WAS DIRECTED TOWARDS THE UNDERSTANDING OF BASIC FACTORS RESPONSIBLE FOR SMALL MOLECULES PERMEATING POLYMERIC FILMS. PROGRESS WAS MADE IN THIS AREA. IN ADDITION, RESEARCH WAS CONDUCTED IN THE AREA OF ENCAPSULATION. THIS RESEARCH INCLUDED THE STUDY OF BASIC MECHANISMS ASSOCIATED WITH ENCAPSULATION, COMPATIBILITY OF POLYMERS WITH POTENTIAL LIQUID FUELS (E. G. HYDRAZINE), SYNTHESIS OF NEW POLYMERS, AND THE ENCAPSULATION OF LIQUID FUELS OR MODEL COMPOUNDS.

DDC REPORT RIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD7602 270 MOTOROLA INC SCOTTSDALE ARIZ

MINIATURE THIN FILM INDUCTORS (MODIFICATION NO. 2). (U)

DESCRIPTIVE NOTE: FINAL DEVELOPMENT REPT. FOR 27 MAY 63-27 MAY 64.

JUN 64 78P GLEASON, F. R. ;

REPT. NO. 4003

CONTRACT: NOBSR85397

PROJ: SROBBO3 TASK: 9636

UNCLASSIFIED REPORT

## SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*MINIATURE ELECTRONIC EQUIPMENT, (COILS), (\*COILS, METAL FILMS), FILMS, GOLD, ENCAPSULATION, FERRITES, NICKEL ALLOYS, ZINC ALLOYS, COBALT ALLOYS, INDUCTANCE, SPRAYS, CHLORIDES, VAPOR PLATING, EVAPORATION, ELECTRODEPOSITION (U) TDENTIFIERS: THIN FILMS

THE REPORT DESCRIBES A PROGRAM DIRECTED TOWARD THE DEVELOPMENT OF TECHNIQUES FOR FABRICATING MINIATURE THIN-FILM INDUCTORS. THE BASIC DEVICE CONSISTS OF A FLAT SPIRAL CONDUCTING PATH DEPOSITED ON A BULK FERRITE SUBSTRATE AND ENCAPSULATED WITH A FERRITE FILM DEPOSIT. THE GOAL OF THE PROGRAM WAS TO FABRICATE THESE INDUCTANCES IN A RANGE FROM 38 TO 1000 MICROHENRIES WITH A Q-VALUE OF 100 MEASURED AT 1 MC. THE TECHNIQUE FOR DEPOSITING THE FERRITE FILM BY THE SPRAY HYDROLYSIS OF A CHLORIDE SOLUTION IS DESCRIBED. THE SPIRAL COILS WERE MADE FROM GOLD AND DEPOSITED BY A COMBINATION OF VACUUM EVAPORATION AND ELECTRODEPOSITION TECHNIQUES. THE MAXIMUM AIR CORE COIL INDUCTANCE OBTAINED IN AN AREA 0.3 INCH SQUARE WAS 1.8 MICROHENRIES. THE LARGEST INDUCTANCE VALUE OBTAINED FOR A SINGLE ENCAPSULATED COIL WAS 54 MICROHENRIES WITH A Q-VALUE OF 6 AT 1 MC . (AUTHOR) (U)

DDC REPORT BIRLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-602 939
TEXAS INSTRUMENTS INC DALLAS

PRODUCTION ENGINEERING MEASURES TO INCREASE TRANSISTOR RELIABILITY FOR THE 20656. (U)

DESCRIPTIVE NOTE: FINAL PROGRESS REPT. FOR ; JUL 62-31 MAR 64.

MAR 64 248P REPT. NO. 03 64 43

CONTRACT: DA36-0395C86730

## UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: A PORTION OF THIS DOCUMENT IS ILLEGIBLE OR NONREPRODUCIBLE.

DESCRIPTORS: (\*TRANSISTORS, RELIABILITY (ELECTRONICS)),
(\*QUALITY CONTROL, TRANSISTORS), ENGINEERING, PRODUCTION
CONTROL, SILICON, COATINGS, DIFFUSION, BANDING, WELDING,
ENCAPSULATION, TEST METHODS, GOLD ALLOYS, STRESSES,
TESTS, MILITARY REQUIREMENT
(U)
IDFNTIFIERS: THICK FILMS, PLANAR

THE PROCESS IMPROVEMENT WORK ON THE 2N656 DEVICE WAS COMPLETED DURING THE FIRST TWELVE MONTHS OF THE CONTRACT. THE RESULTANT TRANSISION IS A RUGGED PLANAR DEVICE UTILIZING GOLD ALLOY WAFER MOUNTING. ULTRASONIC LEAD BONDING WITH NO INLINE ETCH OR WAFER COATING AND IS CAPABLE OF 15 WATTS DISSIPATION AT 1000 CASE TEMPERATURE. IMPROVED FACILITIES. PROCESSES AND PROCESS CONTROLS IN THE DIFFUSION. PHOTO RESIST, CONTRACT EVAPORATION AND ASSEMBLY AREAS HAVE ALL CONTRIBUTED TO THE SIGNIFICANTLY IMPROVED PRODUCT QUALITY AND UNIFORMITY. THE MAJOR PORTION OF RELIABILITY IMPROVEMENT HAS RESULTED FROM THE PLANARIZATION OF THE DEVICE AND THE RE-DESIGN OF THE PACKAGE WHICH REPLACED THE SINGLE 0.017 IN. DIAMETER WIRE SLUG SUPPORT WITH TWO APPROXIMATELY 0.015 IN. THICK BY 0.090 IN. WIDE TABS. STRESS TESTS CONDUCTED ON 1,100 PRODUCTION PLANAR DEVICES CONFIRM THAT THE IMPROVED TRANSISTOR EXCEEDS THE CONTRACT OBJECTIVE OF 0.01% PER THOUSAND OPERATING HOURS AT A 90% CONFIDENCE LEVEL. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-604 196
CLEVITE TRANSISTOR PRODUCTS WALTHAM MASS

PRODUCTION ENGINEERING MEASURE FOR THE IMPROVEMENT OF GERMANIUM ALLOY POWER TRANSISTORS.

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 7, 31 OCT 63-31 JAN 64,

JAN 64 24P KELLEY, LUCILLE T. ; LOCONTE, JEREMIAH A.;

CONTRACT: DA36 0395C86724

UNCLASSIFIED REPORT

## SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*TRANSISTORS, GERMANIUM), (\*MANUFACTURING METHODS, TRANSISTORS), DESIGN, QUALITY CONTROL, RELIABILITY (ELECTRONICS), FAILURE (MECHANICS), STRESSES, LIFF FXPECTANCY, ALLOYS, SOLDERING, CHEMICAL MILLING, ENCAPULATION, DESSICANTS, ENVIRONMENTAL TESTS, SEMICONDUCTOR DEVICES

ENGINEERING DESIGN CHANGES HAVE BEEN COMPLETED AND EVALUATED. THE NEW PROCESS AND PRODUCTION TECHNIQUES HAVE BEEN EVALUATED AND IMPLEMENTED INTO THE PRODUCTION LINE FLOW. ALL UNITS IN THE FINAL PRODUCTION RUN WERE ASSEMBLED ACCORDING TO CONDITIONS SPECIFIED IN THE FINAL CONTRACT AGREEMENT. QUALITY CONTROL PROCEDURES HAVE BEEN REVIEWED. THE Q.

C. MANUAL WILL BE INCLUDED IN THE FINAL REPORT.

FINAL RELIABILITY PROOF TESTING IS IN PROCESS. AN IMPROVED FAILURE RATE IS INDICATED, BUT AT THIS DATE THE DATA IS INSUFFICIENT TO DRAW FINAL CONCLUSIONS.

(AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-605 159
JOHNS HOPKINS UNIV BALTIMORE MD

ANALOG COMPUTER RESEARCH INTO THE ENERGY-EXCHANGE BETWEEN GASES AND SOLIDS. (U)

•

DESCRIPTIVE NOTE: SCIENTIFIC REPT.:

MAY 64 316P ROGERS, MILTON;

CONTRACT: AF49 638 496

MONITOR: AF0SR, 1001

UNCLASSIFIED REPORT

### SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*TRANSPORT PROPERTIES, THERMODYNAMICS),
(\*ENLPGY, TRANSPORT PROPERTIES), GASES, SOLIDS,
PARTICLES, FLUID MECHANICS, TEMPERATURE, SURFACES,
CHEMISORPTION, ADSORPTION, MATHEMATICAL ANALYSIS, ANALOG
COMPUTERS
(U)
IDENTIFIERS: ENFRGY EXCHANGE

A COMPARISON IS MADE BETWEEN VARIOUS MODELS OF THE INTERACTION & A DESCRIPTION IS GIVEN OF THE CIRCUITRY AND TECHNIQUES USED TO INVESTIGATE THE PROBLEM OF ENERGY EXCHANGE BETWEEN GASES AND SOLIDS. BOUNDS ON THE APPLICABILITY AND INTERPRETATION OF DATA OBTAINED SOLELY FROM COMPUTATIONAL EXPERIMENTS. WHETHER PERFORMED WITH AN ANALOG OR A DIGITAL COMPUTER. ARE DELINEATED IN SOME DETAIL. DATA ARE PRESENTED WHICH WAS OBTAINED IN A SERIES OF ANALOG COMPUTER EXPERIMENTS IN GAS SURFACE INTERACTIONS USING SEVERAL VARIATIONS OF A VERY SIMPLE MODEL OF THE INTERACTION POTENTIAL, THE LATTICE, AND THE PHYSICAL STATE OF THE SOLID, PARTICULARLY TEMPERATURE . FOR THE MAJORITY OF THE RESEARCH, A NON-LINEAR COUPLING (POTENTIAL) WAS USED BETWEEN GAS PARTICLES AND SURFACE ATOM. SEVERAL MAJOR APPROXIMATIONS WERE MADE IN THE FORMULATION OF THE MODELS INVESTIGATED. (U)

37

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-605 984
TRW SPACE TECHNOLOGY LABS LOS ANGELES CALIF

LOW PRESSURE ELECTRICAL DISCHARGE STUDIES.

(U)

DEC 59 72P KREBS.W. H. ;REED.A. C. ; REPT. NO. STL/TR-59-0000-09931 CONTRACT: AF04 647 309

UNCLASSIFIED REPORT

## SUPPLEMENTARY NOTE:

PESCRIPTORS: (\*ELECTRIC DISCHARGES, HIGH ALTITUDE),
(\*GUIDED MISSILE COMPONENTS, MALFUNCTIONS), AIR, WATER
VAPOR, SPARKS, SECONDARY EMISSION, ELECTRICAL EQUIPMENT,
LOW-PRESSURE RESEARCH, ELECTRODES, ELECTRICAL
PROPERTIES, GEOMETRIC FORMS, ENCAPSULATION, CASTING,
REVIEWS, BIBLIOGRAPHIES
(U)
IDENTIFIERS: BRFAKDOWN (ELECTRICAL)

THE REPORT CONCERNS ELECTRICAL BREAKDOWN OF AIR AT LOW PRESSURES OR HIGH ALTITUDES (70,000 TO 250,000 FEET) DUE TO SECONDARY EMISSION. INFORMATION PERTINENT TO THE PROBLEM OF LOW FREQUENCY (O TO 1000 CPS) SPARKING WAS COMPILED THROUGH A LITERATURE SURVEY. A BIBLIOGRAPHY CONCERNING ELECTRICAL BREAKDOWN AT BOTH LOW AND HIGH FREQUENCIES WAS COMPILED. A TEST PROGRAM YIELDED THE FOLLOWING RESULTS: NO STATISTICALLY SIGNIFICANT DEVIATION FROM PASCHEN'S LAW WAS DETECTED. THE ADDITION OF WATER VAPOR TO THE AIR CONSTITUTING THE TEST ENVIRONMENT CAUSED A SIGNIFICANT LOWERING OF THE MINIMUM SPARKING VOLTAGE. RECOMMENDATIONS ARE MADE RELATIVE TO TEST PROGRAMS FOR MISSILE ELECTRICAL COMPONENTS EMPLOYING VOLTAGES HIGHER THAN 200 VOLTS. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-611 752 MITRE CORP BEDFORD MASS

LEAD ATTACHMENT AND ENCAPSULATION TECHNIQUES FOR THIN FILM MICROCIRCUITS, (U)

FEB 65 16P EVERETT PATRICK N. ;
REPT. NO. W-6353
CONTRACT: AF19 628 2390
PROJ: 708 0
MONITOR: ESD . TDR-64-630

UNCLASSIFIED REPORT

## SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*PACKAGED CIRCUITS, MANUFACTURING METHODS), (\*ENCAPSULATION, PACKAGED CIRCUITS), (\*MICROMINIATURIZATION (ELECTRONICS), ELECTRIC CONNECTORS), ELECTRIC WIRE, ATTACHMENT, METAL FILMS, BONDING, SOLDERING, EPOXY PLASTICS, MODULES (ELECTRONICS), RESISTORS, SEMICONDUCTOR DEVICES, PRINTED CIRCUITS (U) IDENTIFIERS: THIN FILMS

THE TECHNIQUES DESCRIBED WERE DEVELOPED FOR ENCAPSULATING EXPERIMENTAL THIN FILM CIRCUITS DEPOSITED ON 0.5-INCH SQUARE GLASS SUBSTRATES. THE ENCAPSULATION IS EPOXY, WITH FINAL PACKAGE DIMENSIONS OF 0.6-INCH SQUARE X .125-INCH THICK. UP TO 32 RIBBON LEADS EMERGE, ON .050 CENTERS, ARRANGED ON THE PERIPHERY OF THE PACKAGE. A FACTOR COMPLICATING THE ENCAPSULATION WAS THE REQUIREMENT THAT THE LEADS EMERGE ON THE FOUR EDGES OF THE UNIT. A MOLDING PROCESS USING SILICONE RUBBER MOLDS, AND A HYPODERMIC FILLING ARRANGEMENT WAS EVOLVED. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-620 933

NATIONAL CASH REGISTER CO DAYTON OHIO CAPSULAR RESEARCH
AND PRODUCT DEVELOPMENT DEPT

ENCAPSULATION OF VIRUSES.

(U)

DESCRIPTIVE NOTE: REPT. FOR MAR-OCT 64,

AUG 65 40P ANDERSON.JERROLD L. ;BUTZ.

S. DAVID ;

CONTRACT: AF29 601 6344

PROJ: AF-8803

MON:TOR: AFWL TR-64-167

UNCLASSIFIED REPORT

# SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*VIRUSES, ENCAPSULATION),

(\*ENCAPSULATION, BACTERIOPHAGES), (\*BACTERIOPHAGES,
ENCAPSULATION), VIABILITY, TOXICITY, ETHYL
CELLULOSE, SPACE BIOLOGY, RADIATION EFFECTS,
RADIOLOGICAL DOSAGE, DOSIMETERS, PHOTOGRAPHIC
EMULSIONS
(U)
IDENTIFIERS: LYOPHILIZATION

RESEARCH EFFORTS WERE DIRECTED TOWARD DEVELOPMENT OF A METHOD OF ENCAPSULATING VIRUSES IN SPHERES CONTAINING A PREDICTABLE PHAGE TITER TO BE USED IN BIOLOGICAL DOSIMETRY EXPERIMENTS. INITIAL STUDIES DEMONSTRATED THE ABILITY OF THE BACTERIOPHAGE TO UNDERGO LYOPHILIZATION AND ENCAPSULATION YIELDING A PRODUCT OF ADEQUATE VIABILITY. THE BUTAREZ TOLUENE ETHYLCELLULOSE ENCAPSULATION SYSTEM PROVED SATISFACTORY FOR PRODUCING SPHEROIDAL VIRUSETHYLCELLULOSE CAPSULES OF TWENTY-FIVE TO FIFTY MICRONS DIAMETER. THE MEAN DIAMETER BEING FORTY-TWO MICRONS. VIABILITY DETERMINATIONS YIELDED A PHAGE TITER OF 1.7 X 10 TO THE 11TH POWER PHAGES PER GRAM OF CAPSULES; HENCE, A CAPSULE OF AVERAGE DIAMETER POSSESSED A THEORETICAL TITER OF 8 X 1000 PHAGES. SIMULATED END-USE TESTS PROVED PHOTOGRAPHIC DEVELOPER CHEMICALS. SUCH AS COULD BE USED FOR THE PROCESSING OF VIRUS-BEARING NUCLEAR EMULSIONS, TO BE NONTOXIC TO THE ENCAPSULATED PHAGES. A MODIFICATION IN THE SCOPE OF THE PROGRAM DIRECTED THE CONCLUDING WORK TO THE PREPARATION OF CAPSULES LESS THAN FIFTEEN MICRONS IN DIAMETER. SAMPLES OF VIRUSETHYLCELLULOSE CAPSULES WERE SUBMITTED TO THE AIR FORCE. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-625 956 SYLVANIA ELECTRIC PRODUCTS INC WOBURN MASS SEMICONDUCTOR DIV

RELIABILITY ANALYSIS OF X-BAND TUNNEL DIODES. (U)

DESCRIPTIVE NOTE: FINAL TECHNICAL REPT. DEC 65 74P DAVIS, CHARLES !LUECK, ARTHUR i

CONTRACT: AF30(602)-3487 PROJ: AF-4519 TASK: 451901 MONITOR: RADC . TR-65-291

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-615 498.

DESCRIPTORS: ( TUNNEL DIODES, RELIABILITY (ELECTRONICS)), X-BAND, MANUFACTURING METHODS, PROCESSING, SEMICONDUCTOR DEVICES, ENCAPSULATION, GERMANIUM ALLOYS, TIN ALLOYS, ARSENIC, GALLIUM

(U)

THE REPORT PRESENTS AN ACCOUNT OF A MICROWAVE TUNNEL DIODE IMPROVEMENT PROGRAM, AND THE RESULTS OBTAINED FROM RELIABILITY TESTS PERFORMED ON DEVICES FABRICATED BY THE IMPROVED PROCESSES. A NEW SOLID STRUCTURE TUNNEL DIODE WAS DEVELOPED DURING THIS CONTRACT WHICH EXHIBITS SUPERIOR RELIABILITY CHARACTERISTICS TO ANY PREVIOUSLY TESTED TUNNEL DIODE. THE PROCESS AND FABRICATION DETAILS FOR THIS DEVICE ALONG WITH RELIABILITY DATA ARE INCLUDED IN THE REPORT. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-628 537 11/9 9/1
HARRY DIAMOND LABS WASHINGTON D C

LOW-LOSS STYRENE-TYPE FOAM-IN-PLACE ENCAPSULATING RESINS, (U)

OCT 65 24P ENGELHARDT, F. J. O. ;
REPT. NO. TR-1308,
PROJ: DA-19523801A300 HDL-96300

UNCLASSIFIED REPORT

## SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*ENCAPSULATION, STYRENE PLASTICS),
(\*STYRENE PLASTICS, ENCAPSULATION), (\*EXPANDED
PLASTICS, ENCAPSULATION), STYRENES, PROPELLANTS,
POLYMERIZATION, POWDERS, DIELECTRIC PROPERTIES,
RADIOFREQUENCY, COMPRESSIVE PROPERTIES, DENSITY
(U)
IDENTIFIERS: POTTING COMPOUNDS

LOW-DIELECTRIC-LOSS STYRENE-TYPE FOAM-IN-PLACE ENCAPSULATING RESINS ARE NOT AVAILABLE COMMERCIALLY. SUCH A RESIN HAS NOW BEEN DEVELOPED. A PROPELLANT WAS ADDED TO THE CATALYZED STYRENE-POLYSTYRENE MIXTURE; AS THE TEMPERATURE OF THE POLYMERIZING RESIN ROSE. THE PROPELLANT EXPANDED THE RESIN INTO A CELLULAR STRUCTURE. HOMOGENEOUS FOAMS WERE OBTAINED IN THE PRESENCE OF FINELY POWDERED POLYMERS. WHICH ACTED AS BUBBLE NUCLEATORS. THE RESULTANT RIGID FOAMS HAD DIELECTRIC CONSTANTS RANGING FROM 1.2 TO 1.8, AND LOSS TANGENTS FROM 0.0002 TO 0.001 OVER THE FREQUENCY RANGE 102 AND 108 CPS. SOME OF THESE MATERIALS HAD REMARKABLY FLAT LOSS-FREQUENCY CURVES, LOSSES RANGING ONLY BETWEEN 0.0004 AND 0.0005 OVER THE SAME FREQUENCY RANGE. DENSITIES WERE VARIED BETWEEN 0.194 AND 0.850 G/CU CM, OR BETWEEN 12 AND 57 LB/CU FT. THESE DATA INDICATE THE USEFULNESS OF THE NEW CELLULAR MATERIALS AS RF ENCAPSULATING RESINS. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-628 618 9/1 13/8 PHILCO CORP LANSDALE PA

RESEARCH AND DEVELOPMENT LOW COST INTEGRATED CIRCUIT TECHNIQUES. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 1, 15

JUN-14 SEP 65,

SEP 65 72P WAGNER, S. ; WALKER, M.;

REPT. NO. PHILCO R-506,

CONTRACT: DA-28-043-AMC-01424(E), PROJ: DA-1P622001056 TASK: 1P62200105602

UNCLASSIFIED REPORT

## SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*INTEGRATED CIRCUITS, MANUFACTURING METHODS), (\*ENCAPSULATION, INTEGRATED CIRCUITS), (\*ELECTRIC CONNECTORS, INTEGRATED CIRCUITS), ELECTRIC WIRE, BONDING, SEMICONDUCTOR DEVICES, GLASS, COATINGS, DEPOSITION, EVAPORATION, VAPOR PLATING, PROCESSING, ASSEMBLING, PACKAGING, HERMETIC SEALS, PRINTED CIRCUITS (U)

THE USE OF AN ADMERENT IMPERVIOUS COATING FOR ENCAPSULATING SILICON INTEGRATED CIRCUITS, COMBINED WITH A BATCH MOUNTING AND INTERCONNECTION TECHNIQUE. WILL RESULT IN (1) DECREASED COST AS A RESULT OF PACKAGE ELIMINATION; (2) INCREASED PACKING DENSITY; (3) IMPROVED RELIABILITY DUE TO REDUCTION IN THE NUMBER OF CONTACTS AND ELIMINATION OF AU-AL THERMOCOMPRESSION BONDS. THIS REPORT DESCRIBES A TECHNIQUE FOR SELECTIVE DEPOSITION OF 1 TO 2 MICRON THICK GLASS ON SILICON INTEGRATED CIRCUITS AND ATTACHING THESE CIRCUITS TO A PRINTED CIRCUIT BOARD BY MEANS OF 'FLIP CHIP' MOUNTING. GLASS HAS BEEN DEPOSITED BY MEANS OF EVAPORATION AND PYROLYTIC VAPOR PLATING. EVAPORATION APPEARS TO HAVE SOME ADVANTAGES. EVALUATION OF TWO HIGH TEMPERATURE METALIZATION SYSTEMS (TI-AG-TI AND CR-AG-CRI HAS INDICATED SATISFACTORY PROPERTIES. A TEST MODEL EMPLOYING THESE TECHNIQUES HAS BEEN DESIGNED FOR ENVIRONMENTAL TESTING AND TECHNIQUE EVALUATION. (AUTHOR)

(4)

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-628 837 9/5 13/4
DOUGLAS AIRCRAFT CO INC SANTA MONICA CALIF MISSILE AND SPACE SYSTEMS DIV

STRESS ANALYSIS OF ENCAPSULATION MATERIALS FOR WELDED MODULES, (U)

FEB 66 61P SMITH, M. H. ; REPT. NO. SM-48410;

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE:

DESCRIPTORS: (.MODULES(ELECTRÔNIC).
ENCAPSULATION), (.ENCAPSULATION, MATERIALS),
(.PACKAGING. TEST EQUIPMENT(ELECTRONICS)),
WELDS, STRAIN GAGES, EPOXY PLASTICS.
TRANSDUCERS, STRESSES. MATHEMATICAL ANALYSIS.
EMBEDDING SUBSTANCES

(U)

A STRAIN-GAUGE LOAD TRANSDUCER, SIMULATING AN AXIAL-LEADED DISCRETE COMPONENT, WAS DEVELOPED AND FABRICATED BY DAC TO MEASURE THE MAGNITUDE AND DIRECTION OF AXIAL STRESSES EXERTED BY AN ENCAPSULATING MATERIAL. THE EPOXY ENCAPSULATION MATERIALS EXHIBITED RESIDUAL COMPRESSIVE STRESSES DUE TO THE INITIAL CURE OF RESIN. THERMAL CYCLING SUBSTANTIALLY INCREASED THESE COMPRESSIVE STRESSES AT THE LOWEST TEMPERATURES. TENSILE STRESSES WERE RECORDED DURING THE ELEVATED TEMPERATURE PHASE OF THE TEST. COMPRESSIVE STRESSES WERE PRODUCED AS THE CYCLE WAS COMPLETED FURMING A CLOSED HYSTERESIS LOOP. CHARACTERISTIC OF THESE MATERIALS. ON THE STRESS VS. TEMPERATURE CURVE. WITHIN A TYPICAL CORDWOOD WELDED MODULE WITH COMPONENT DENSITY LEVELS OF 10-30 PERCENT. THE STRESS LEVELS WERE REDUCED BY INCREASING LEVELS OF COMPONENT LOADING. THE LOW-DENSITY, MICROBALLOON-FILLED STYCAST 1093/11 EPOXY MATERIAL EXHIBITED SIGNIFICANTLY LOWER, MORE UNIFORM TENSILE AND COMPRESSIVE STRESSES THAN THE MEDIUM-DENSITY, MINERAL-FILLED HYSOL 4215/3561 (9709466, TYPE I) EPOXY MATERIAL WITHIN THIS SAME TEST CONFIGURATION. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-630 566 11/9 9/3 13/10
NAVY MARINE ENGINEERING LAB ANNAPOLIS MD

EFFECT OF WATER ABSORPTION ON DIMENSIONAL STABILITY
OF ELECTRIC MOTOR ENCAPSULATING MATERIALS. (U)

DESCRIPTIVE NOTE: RESEARCH AND DEVELOPMENT PHASE REPT.,
MAR 66 15P TOBIN, JOHN F.;
REPT. NO. MEL-421/65,
PROJ: S-F013 12 15,

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE:

DESCRIPTORS: (\*EPOXY PLASTICS, ENCAPSULATION),

(\*ENCAPSULATION, EPOXY PLASTICS), (\*ELECTRIC

MOTORS, ENCAPSULATION),

PERFORMANCE(ENGINEERING), WATER,

ABSORPTION(PHYSICAL), WINDING, DEEP SUBMERGENCE,

STATISTICAL ANALYSIS, UNDERWATER EQUIPMENT,

DEGRADATION, STABILITY

(U)

EXPERIMENTS WITH EPOXY MATERIALS TO DETERMINE THEIR DIMENSIONAL CHANGE AS CAUSED BY WATER ABSORPTION (WHEN USED AS ENCAPSULATING MATERIALS FOR SUBMERSIBLE ELECTPIC MOTOR WINDINGS) WERE CONDUCTED WITH SUFFICIENT SAMPLE POPULATION TO ALLOW STATISTICAL ANALYSIS. THE STUDIES SHOWED THAT THE WATER ABSORPTION RATES OF THE THREE EPOXIES WERE IDENTICAL AND THAT DEEP SUBMERGENCE PRESSURES DID NOT ACCELERATE THE ABSORPTION RATE OR THE DIMENSIONAL GROWTH OF THE EPOXIES. DIMENSIONAL CHANGES DUE TO WATER ABSORPTION WERE FOUND TO BE VERY SMALL IN ALL CASES. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

13/8 AD-631 491 9/1 PHILCO CORP LANSDALE PA

LOW COST INTEGRATED CIRCUIT TECHNIQUES.

(U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 2. 15 SEP-14 DEC 65, WAGNER STURGER ; WALKER MAURO APR 66 68P

CONTRACT: DA=28-043-AMC-01424(E) PROJ: 1P622001A056.

MONITOR: ECOM . 01424-2

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-628 618.

DESCRIPTORS: ( • INTEGRATED\_CIRCUITS , MANUFACTURING METHODS), ( DENCAPSULATION, INTEGRATED CIRCUITS), GLASS, EVAPORTATION, DEPOSITION, CAPACITORS, PRINTED CIRCUITS, VAPOR PLATING, SILICON COMPOUNDS, DIOXIDES, MASKING, OXIDES, METALS, SILICON, VOLTAGE, CAPACITANCE, ALUMINUM, ETCHING (U) IDENTIFIERS: SILICON DIOXIDE (U)

BOTH THE EVAPORATED AND PYROLYTIC GLASS DEPOSITION TECHNIQUES HAVE BEEN IMPROVED, RESULTING IN ENCAPSULATING DEPOSITS OF HIGHER QUALITY. THE PINHOLE PROBLEM ASSOCIATED WITH THE EVAPORATED GLASS HAS BEEN NEARLY ELIMINATED. ALSO, IMPROVED ADHERENCE HAS BEEN OBTAINED WITH THE PYROLYTICALLY DEPOSITED GLASS. GLASS DELINEATION WAS IMPROVED BY USING AN IMPROVED FIXTURE FOR EVAPORATION THROUGH A METAL MASK. SOME IMPROVEMENT WAS ALSO MADE IN THE DELINEATION OF PYROLYTICALLY DEPOSITED GLASS. IN THE WORK ON GLASS EVALUATION TECHNIQUES, A METHOD INVOLVING PRESSURIZED STEAM HAS PROVEN TO BE EFFECTIVE IN THE RELATIVE EVALUATION OF THE PASSIVATING PROPERTIES OF GLASS. ALSO, MOBILE CHARGE CONCENTRATION STUDIES WERE PERFORMED ON BOTH EVAPORATED AND PYROLYTICALLY DEPOSITED GLASS. PROBLEMS ENCOUNTERED IN METALIZATION INCLUDE INCREASED OHMIC CONTACT RESISTANCE AND POOR DELINEATION. SOME TEST MODELS HAVE BEEN PRODUCED. ALTHOUGH DEVICE AND METAL DELINEATION PROBLEMS HAVE DELAYED THE COMPLETION OF THE VEHICLES. THE VEHICLES HAVE BEEN SUBJECTED TO PRELIMINARY ELECTRICAL AND ENVIRONMENTAL EVALUATION. A PLAN FOR THE TESTING AND SPECIFICATION OF THE PRELIMINARY EXPLORATORY DEVELOPMENT MODELS WAS PREPARED. (AUTHOR) 46

(U)

**JZZZHT** 

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /2ZZHT

AD=635 183 9/1 13/8 PHILCO CORP LANSDALE PA

LOW COST INTEGRATED CIRCUIT TECHNIQUES.

(U)

DESCRIPTIVE NOTE: PROGRESS REPT. NO. 3, 15 DEC 65-14 MAR 66 (TECHNICAL).

JUL 66 44P WAGNER, STURGER ; WALKER,

MAURO ;

CONTRACT: DA-28-043-AMC-01424(E);

PROJ: DA-1P6-22001-A056,

TASK: 02,

MONITOR: ECOM 01424-3

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-631 491.

DESCRIPTORS: (\*INTEGRATED CIRCUITS, MANUFACTURING HETHODS), (\*ENCAPSULATION, INTEGRATED CIRCUITS), COSTS, VAPOR PLATING, GLASS, PERFORMANCE (ENGINEERING)

(U)

EVALUATION STUDIES OF EVAPORATED AND VAPOR PLATED GLASS HAVE LED TO THE RECOMMENDATION THAT ONLY THE VAPOR PLATED GLASS PROCESS BE USED IN CONTINUING THE REMAINDER OF THE PROGRAM. VAPOR PLATED GLASS HAS SHOWN SUPERIOR PROPERTIES AS A DIELECTRIC AND IN MOBILE CHARGE CONTENT. AN IMPORTANT CONSIDERATION IS THE COMPATIBILITY OF VAPOR PLATED GLASS WITH EXISTING METALIZATION SYSTEMS. A NUMBER OF CONSTRUCTION METHODS HAVE BEEN EVOLVED AND PROVEN FEASIBLE, ALTHOUGH SEVERAL PROBLEMS REMAIN. HOWEVER, THE PROBLEMS ARE BASICALLY THOSE OF PROCESSING AND THUS CAPABLE OF RESOLUTION DURING FABRICATION OF THE JEST VEHICLES. CONTINUED IMPROVEMENTS IN BATCH ASSEMBLY TECHNIQUES HAVE LED TO MORE REPRODUCIBLE AND BETTER DEFINED SOLDER JOINTS. FURTHER ELECTRICAL EVALUATIONS HAVE BEEN MADE OF DEVICES TO DETERMINE THE EFFECTS OF GLASSING. THESE EVALUATIONS HAVE ALSO EVIDENCED THE SUPERIORITY OF VAPOR PLATED GLASS. AN ERROR IN ONE OF THE MASKS PROVED TO BE RESPONSIBLE FOR A SATURATION VOLTAGE PROBLEM. A SPECIFICATION QUESTION HAS ARISEN BECAUSE OF THE RATHER WIDE RANGE OF LEAKAGE CURRENTS RESULTING FROM GOLD DOPING. THIS LEAKAGE CURRENT VARIATION MADE THE TEST VEHICLES WHICH WERE CONSTRUCTED UNSATISFACTORY FOR ENVIRONMENTAL TESTING. A REVISED APPROACH TO THE FINAL EXPLORATORY DEVELOPMENT MODELS IS RECOMMENDED TO PERMIT EMPHASIS ON THE CONSTRUCTION TECHNIQUES WHICH UTILIZE VAPOR PLATED GLASS. (AUTHOR) (U)

UNCLASSIFIED

/ZZZHT

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-646 915 11/9 9/3
JOHNS HOPKINS UNIV SILVER SPRING MD APPLIED PHYSICS
LAB

THE IMPROVEMENT OF ENCAPSULATING FOAMS AND QUALITY ASSURANCE OF POTTING PLASTIC.

DESCRIPTIVE NOTE: TECHNICAL MEMO.,

AUG 66 39P WINCKLER,G. A. F. ; EVANS,R. C.

REPT. NO. TG-817 CONTRACT: NOW-62-0604 MONITOR: IDEP 501.32.19.45-56-01

UNCLASSIFIED REPORT

DESCRIPTORS: (\*EXPANDED PLASTICS, \*ENCAPSULATION),
(\*EMBEDDING SUBSTANCES, TEST METHODS); CIRCUITS,
DAMAGE, PRESSURE, VISCOSITY, HARDENING,
CATALYSTS, QUALITY CONTROL, DIELECTRIC PROPERTIES;
RESISTANCE(ELECTRICAL), DENSITY, INSTRUCTION
MANUALS
(U)

PLASTIC FOAMS USED FOR ENCAPSULATING ELECTRONIC CIRCUITS MAY, DURING THEIR FORMATION, EXERT SUFFICIENT PRESSURES TO DAMAGE COMPONENTS AND CONNECTIVE WIRING. THIS PROBABLY CAUSED BY THE INCREASING VISCOSITY OF THE PLASTIC WHILE GAS IS STILL BEING GENERATED. THE DANGER MAY RE ALLEVIATED BY ALTERING THE FORMULATION CHEMICALLY SO THAT GAS GENERATION IS COMPLETED BEFORE THE PLASTIC BEGINS TO HARDEN. THE CONSEQUENCES WHICH WOULD RESULT FROM THE USE OF A MISLABELLED OR SUBSTANDARD CAN OF POTTING PLASTIC IN FLIGHT HARDWARE ARE SO SERIOUS THAT EACH CAN MUST BE INDIVIDUALLY TESTED TO ELIMINATE THAT POSSIBILITY. THIS MAY READILY BE ACCOMPLISHED BY CASTING A TEST DISK AND THEN MEASURING ITS DIELECTRIC CONSTANT, VOLUME RESISTIVITY. SURFACE RESISTIVITY AND DENSITY. THE ELECTRICAL TESTING CAN BE PERFORMED IN LESS THAN TEN MINUTES AND IS, THEREFORE, FEASIBLE AS A STANDARD QUALITY ASSURANCE PROCEDURE. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-648 420 13/8 11/9 9/3
PLASTICS TECHNICAL EVALUATION CENTER DOVER N J

ENCAPSULATION OF ELECTRONIC PARTS IN PLASTICS: A REVIEW, (U)

FEB 67 67P MOLZON, ARNOLD E.;
REPT. NO. PLASTEC-29

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ELECTRONIC EQUIPMENT, ENCAPSULATION), (\*ENCAPSULATION, PLASTICS), COATINGS, FOAMS, EMBEDDING SUBSTANCES, POLYMERS, CASTING, MATERIAL FORMING, MOLDING, THERMAL PROPERTIES

THE ADVANCES AND TRENDS IN THE PLASTICS ENCAPSULATION OF ELECTRONIC PARTS AND CIRCUITS ARE REVIEWED. IN LESS THAN 20 YEARS THIS INDUSTRY HAS DEVELOPED INTO A HIGH PRODUCTION OPERATION. INCLUDED IN THIS REPORT ARE: TYPES OF PLASTICS USED. MATERIAL REQUIREMENTS AND MATERIAL CONSUMPTION. KNOWN MATERIAL SUPPLIERS AND EQUIPMENT SUPPLIERS ARE LISTED AND THEIR PRODUCTS IDENTIFIED. ALSO TABULATED APE 47 PERTINENT SPECIFICATIONS, 111 CONTRACTS (WITH REPORTS), AND 53 GOVERNMENT LABORATORY REPORTS. THESE REFLECT THE MATERIALS RESEARCH AND DEVELOPMENT IN THE DEPARTMENT OF DEFENSE. IN NASA, AND IN INDUSTRY. THE AVAILABILITY OF INFORMATION IS ALSO DISCUSSED. THE REPORT CONTAINS A BIBLIOGRAPHY OF 207 ITEMS ON ENCAPSULATION. (U)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

14/4 AD-660 349 9/1 ARMY ELECTRONICS COMMAND FORT MONMOUTH N J

PRELIMINARY INVESTIGATION OF PLASTIC ENCAPSULATED TRANSISTORS.

(U)

DESCRIPTIVE NOTE: TECHNICAL REPT., SEP 67 NAKIM, E. B. ; CANEPA, R. ; 17P REPT. NO. ECOM-2879 PROJ: DA-1H6-22001-A-056 TASK: 1H6-22001-A-056-01-14

UNCLASSIFIED REPORT

DESCRIPTORS: (OTRANSISTORS, ENCAPSULATION), PERFORMANCE (ENGINEERING) PLASTICS. RELIABILITY (ELECTRONICS), ENVIRONMENTAL TESTS, EPOXY PLASTICS, SILICONE PLASTICS

(U)

AN EVALUATION OF EPOXY AND SILICONE TRANSISTOR PACKAGES WAS CARRIED OUT ON SEVEN DEVICE TYPES. ALL PACKAGES APPEARED FAVORABLE UNDER STANDARD MIL TESTS BELOW 130C. HOWEVER, A NEW REALISTIC ENVIRONMENTAL TEST HAS BEEN DEVISED WHICH APPEARS TO DETECT POTENTIALLY UNRELIABLE DEVICES IN LESS THAN 500 HOURS. THE RESULTS FROM THIS TEST INDICATE THAT SILICONE PACKAGES ARE GENERALLY MORE DESIRABLE THAN EPOXY. HOWEVER. THIS CAN VARY BETWEEN MANUFACTURERS AND SOME EPOXY UNITS HAVE BEEN FOUND TO BE AS STABLE AS SILICONE, DEPENDING ON THE MANUFACTURER. RESULTS OF TESTS ARE DISCUSSED AS WELL AS VARIOUS PROBLEM AREAS. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-669 850 9/1
ITT SEMICONDUCTOR PRODUCTS LABS PALO ALTO CALIF

FOUR-LAYER DIODE DEVELOPMENT PROGRAM.

(U)

DESCRIPTIVE NOTE: FINAL REPT.,

APR 68 74P SCARLETT, ROBERY M.;

CONTRACT: AF 30(602)-4045

PROJ: AF+5573

MONITOR: RADC TR-68-136

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ELECTRONIC SWITCHES,
DIODES(SEMICONDUCTOR),
(\*DIODES(SEMICONDUCTOR), MANUFACTURING
METHODS), MODULATORS,
RELIABILITY(ELECTRONICS), VOLTAGE,
FAILURE(ELECTRONICS), THERMAL STABILITY,
LEAKAGE(ELECTRICAL), SILICON, BORON,
DIFFUSION, SURFACE PROPERTIES, ENCAPSULATION (U)

THIS EFFORT IS THE CULMINATION OF SEVERAL YEARS
WORK TO IMPROVE AND DEMONSTRATE THE FOUR-LAYER DIODE
IN HIGH POWER SWITCH SERVICE. THE FABRICATION OF
THE DEVICE. ITS CHARACTERISTICS AND AN EVALUATION OF
PERFORMANCE OF THE DEVICE IN A HIGH VOLTAGE HIGH
CURRENT ENVIRONMENT IS DISCUSSED. SEVERAL DEVICE
PROBLEMS BECAME EVIDENT DURING THIS EFFORT AND ARE
CHARACTERIZED IN THE TEXT. THE FAILURE RATES,
THERMAL DISSIPATION PROBLEMS, VOLTAGE DISTRIBUTION.
REPETITION RATE LIMITATIONS AND GENERAL DEVICE
BEHAVIOR ARE THOROUGHLY DISCUSSED. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-671 797 9/5
NAVAL AMMUNITION DEPOT CRANE IND

MICRO-NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPMENTS.

(U)

JUL 68 222P
REPT. NO. NAD-CR-MICRO-NOTES-24
MONITOR: IDEP 515.00.00.00-X9-10

## UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SPONSORED BY NAVAL AIR SYSTEMS COMMAND, WASHINGTON, D.C. AND NAVAL ELECTRONICS SYSTEM COMMAND, WASHINGTON, D.C. SEE ALSO AD-667 719.

DESCRIPTORS: (\*NAVAL EQUIPMENT,

\*MICROMINIATURIZATION(ELECTRONICS)),
(\*INTEGRATED CIRCUITS, TESTS), RADIO RECEIVERS,
FREQUENCY SHIFT CONVERTERS, RADIATION DAMAGE,
GATES(CIRCUITS), LOGIC CIRCUITS, SWITCHING
CIRCUITS, RELAXATION OSCILLATORS, AMPLIFIERS,
PERFORMANCE(ENGINEERING), SEMICONDUCTOR DEVICES,
ENCAPSULATION

(U)

CONTENTS INCLUDE: MICROELECTRONICS FSK
RECEIVER; EVALUATION OF DIGITAL UNITS; EVALUATION
OF ANALOG UNITS; PLASTIC ENCAPSULATED SEMICONDUCTOR
DEVICES AND MICROCIRCUITS; INTRODUCTION TO
RADIATION EFFECTS IN INTEGRATED CIRCUITS.

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-689 224 9/5
ROME AIR DEVELOPMENT CENTER GRIFFISS AFB N Y

FAILURE MECHANISMS IN PLASTIC ENCAPSULATED MICROCIRCUITS.

(U)

DESCRIPTIVE NOTE: TECHNICAL REPT.,

MAY 69 34P TAMBURRINO, ALFRED L.;

KAPFER, VINCENT C.;

REPT. NO. RADC-TR-69-111

PROJ: AF-5519

TASK: 551906

HONITOR: IDEP 515.00.00.00-F9-01

UNCLASSIFIED REPORT

DESCRIPTORS: (\*INTEGRATED CIRCUITS,
RELIABILITY(ELECTRONICS)), TEST METHODS,
ENCAPSULATION, EPOXY PLASTICS, PHENOLIC PLASTICS,
SILICONE PLASTICS, THERMAL STRESSES, SALT SPRAY
TESTS, LIQUID IMMERSION TESTS, STRESSES,
CORROSION, ALUMINUM ALLOYS,
FAILURE(MECHANICS)

(U)

THIS PAPER DEALS WITH THE QUESTION OF MILITARY ACCEPTANCE OF MICROCIRCUITS ENCAPSULATED IN PLASTIC MATERIALS. A DISCUSSION OF MILITARY APPLICATIONS AND REQUIREMENTS AND THEIR RELATION TO DEVICE QUALIFICATION TESTING AND SCREENING IS GIVEN. IT IS POINTED OUT THAT QUALIFICATION TESTS ARE BASED UPON ABSOLUTE MINIMUM STANDARDS NOR VALIDLY DERIVED ACCELERATION FACTORS, BUT ON EXPERIENCE WITH SIMILAR DEVICES, AND KNOWLEDGE OF THE EXPECTED CAPABILITIES OF GOOD DEVICES. EPOXY, PHENOLIC, AND SILICONE ENCAPSULATED MICROCIRCUITS HAVE BEEN SUBJECTED TO A VARIETY OF HIGH STRESS TESTS AND FOUR BASIC TYPES OF FAILURES OBSERVED: EXTERNAL SURFACE CONDUCTION, INTERNAL (SILICON CHIP) SURFACE EFFECTS, ALUMINUM METALLIZATION CORROSION, AND BOND BREAKAGE DUE TO THERMAL MISMATCH. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTPOL NO. /ZZZHT

AD-690 445 9/8
NAVAL AMMUNITION DEPOT CRANE IND

MICRO-NOTES. INFORMATION ON MICROELECTPONICS FOR NAVY EQUIPMENTS.

(U)

JUL 69 131P REPT. NO. NAD-CR-MICRO-NOTES-28

## UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE; SPONSORED BY NAVAL AIR SYSTEMS COMMAND, WASHINGTON, D. C., AND NAVAL ELECTRONICS SYSTEM COMMAND, WASHINGTON, D. C.

DESCRIPTORS: (\*NAVAL EQUIPMENT,

\*MICROMINIATURIZATION(ELECTRONICS)),

(\*INTEGRATED CIRCUITS, NAVAL RESEARCH),

SEMICONDUCTOR DEVICES, ENCAPSULATION, LOGIC

CIRCUITS, TABLES, ENVIRONMENTAL TESTS, ION

BOMBARDMENT, DOPING, GATES(CIRCUITS),

RELIABILITY(ELECTRONICS)

(U)

IDENTIFIERS: LSIC(LARGE SCALE INTEGRATED

CIRCUITS), LARGE SCALE INTEGRATED CIRCUITS

THE REPORT DISCUSSES THE RESULTS OF A JOINT EFFORT TO DISSEMINATE INFORMATION ON EVALUATION, APPLICATION, AVAILABILITY, RESEARCH AND DEVELOPMENT, AND STANDARDIZATION ACTIVITY PERTAINING TO STATE-OF-THE-ART MICROELECTRONIC CIRCUITS, DEVICES, AND MATERIALS, WITH A VIEW TOWARD AVOIDING DUPLICATION OF EFFORT AND MAKING MAXIMUM USE OF TECHNICAL RESOURCES. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-703 292 GENERAL MOTORS CORP KOKOMO IND DELCO RADIO DIV

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.

(U)

DESCRIPTIVE NOTE: TECHNICAL REPT. 9 JAN-9 NOV 69; FEB 70 84P BEVINGTON. JOHN R. ; LITTLE,

DAVID R. I

CONTRACT: F30602-69-C-0154

PROJ: AF-5519 TASK: 551906

MONITOR: RADC. IDEP TR-69-451.515.00.00.00-F9-

07

## UNCLASSIFIED REPORT

DESCRIPTORS: ( INTEGRATED CIRCUITS, RELIABILITY (ELECTRONICS)), ( \*ENCAPSULATION, INTEGRATED CIRCUITS), PLASTICS, MOISTUREPROOFING. THERMAL STRESSES, FAILURE (MECHANICS)

(U)

INSUFFICIENT DATA EXISTS WITH RESPECT TO THE LONG TERM STABILITY OF PLASTIC-ENCAPSULATED MICROCIRCUITS. OF SPECIAL INTEREST IS THE DEGREE OF SUSCEPTIBILITY OF THESE PLASTIC PACKAGES TO SUCH ENVIRONMENTAL STRESSES AS MOISTURE RESISTANCE (WITH AND WITHOUT BIAS) AND THERMAL SHOCK. THE OBJECTIVE OF THIS STUDY IS TO DETERMINE THE SUITABILITY OF REPRESENTATIVE, PRODUCTION, PLASTIC-ENCAPSULATED INTEGRATED CIRCUITS FOR MILITARY APPLICATIONS. AND TO DEVELOP METHODS AND TECHNIQUES FOR ASSESSING AND ASSURING THE RELIABILITY OF SUCH CIRCUITS. A SERIES OF SCREENS AND TESTS ARE BEING PERFORMED ON SELECTED CIRCUITS, AND DETAILED FAILURE ANALYSES ARE BEING PERFORMED TO DETERMINE THE FAILURE MODES AND MECHANISMS CHARACTERISTIC OF THE VARIOUS TYPES OF PLASTIC ENCAPSULATIONS. THE RESULTS TO DATE HAVE INDICATED CONTRASTS IN PERFORMANCE BETWEEN PACKAGE TYPES AND BETWEEN SCREENED AND UNSCREENED GROUPS. AS WELL AS SIGNIFICANT LOT TO-LOT VARIATIONS. SEVERAL TENTATIVE CONCLUSIONS HAVE BEEN DRAWN RASED ON TEST RESULTS TO DATE; HOWEVER, FINAL CONCLUSIONS MUST AWAIT COMPLETION OF THIS STUDY. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-704 925 9/8
DEFENSE DOCUMENTATION CENTER ALEXANDRIA VA

PACKAGED CIRCUITS. VOLUME 1.

(U)

DESCRIPTIVE NOTE: REPORT BIBLIOGRAPHY MAR 59-FEB 69.
APR 70 159P
REPT. NO. DDC-TAS-70-39-1

## UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO VOLUME 2, AD-868 525 AND VOLUME 3, AD-508 800.

DESCRIPTORS: (\*PACKAGED CIRCUITS,

\*BIBLIOGRAPHIES), PACKAGING, ELECTRONIC

EQUIPMENT, INTEGRATED CIRCUITS,

MICROMINIATURIZATION(ELECTRONICS),

RELIABILITY(ELECTRONICS),

MODULES(ELECTRONICS), PRINTED CIRCUITS,

MOLECULAR ELECTRONICS, ELECTRIC CONNECTORS,

MANUFACTURING METHODS, WELDING, SEMICONDUCTOR

DEVICES, ENCAPSULATION, COMPUTERS, DATA STORAGE

SYSTEMS, DATA PROCESSING SYSTEMS, COMPUTER LOGIC

(U)

IDENTIFIERS: THIN FILMS

SELECTIVE REFERENCES INCLUDE: COMPATIBLE TECHNIQUES FOR INTEGRATED CIRCUITRY; RESULTS OF STUDIES TO DETERMINE OPTIMUM PACKAGING TECHNIQUES FOR THE ELECTRONIC EQUIPMENT AND THE SHOCK LEVELS THAT THE DIFFERENT PACKAGES AND CERTAIN ELECTRONIC COMPONENTS COULD WITHSTAND; A SYSTEM FOR COMPUTER-AIDED SELECTION AND ASSIGNMENT OF ELECTRONIC MODULES; AN ELECTRONIC PACKAGING PROGRAM WAS INITIATED TO DEVELOP AND EVALUATE INTEGRATED CIRCUIT PACKAGING TECHNIQUES APPLICABLE TO UNMANNED SCIENTIFIC SPACECRAFT DATA SYSTEM; AND ALL ASPECTS OF MICROCIRCUIT PACKAGING ARE STUDIED AND EACH OF THE THREE BASIC APPROACHES TO THE PACKAGING OF MICROCIRCUITS ARE INVESTIGATED AND EVALUATED. NAMELY. TYPE OF CONTAINERS, GLASS AND METAL FLAT PACKAGES, AND ENCAPSULATED TYPE PACKAGES. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-715 108 9/5
NAVAL AMMUNITION DEPOT CRANE IND

MICRO-NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPMENTS.

(U)

OCT 70 80P REPT. NO. NAD-CR-MICRO NOTES-30

## UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO REPORT DATED 1 FEB 70, AD-702 751.

DESCRIPTORS: (\*MICROMINIATURIZATION(ELECTRONICS),
NAVAL EQUIPMENT), INTEGRATED CIRCUITS, COUNTING
METHODS, CORRELATORS, STANDARDIZATION,
ENCAPSULATION, PLASTICS

(U)

CONTENTS: A CONTINUING REPORT ON EFFORTS TO DETERMINE THE THEORY AND METHODS REQUIRED TO FABRICATE MICROCIRCUIT ULTRA HIGH SPEED PRESCALERS; A SUMMARY OF THE WORK DONE ON DEVELOPMENT OF AN LSI CORRELATOR; MINUTES OF THE SECOND MEETING OF THE DOD/NASA COMMITTEE ON RESEARCH AND DEVELOPMENT OF PLASTIC DEVICES AND MATERIALS (WGR AND D); A COMPLETE SUMMARY OF WORK-TO-DATE DONE ON EVALUATION OF PLASTIC ENCAPSULATED INTEGRATED CIRCUITS.

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-715 984 9/5 POME AIR DEVELOPMENT CENTER GRIFFISS AFB N Y

STRESS INDUCED INTERMITTENT FAILURES IN ENCAPSULATED MICROCIRCUITS.

(U)

DESCRIPTIVE NOTE: TECHNICAL REPT.,
OCT 70 60P HABERER, JOHN R.;
REPT. NO. RADC-TR-70-213
PROJ: DE-69-3

UNCLASSIFIED REPORT

DESCRIPTORS: (\*INTEGRATED CIRCUITS, FAILURE(ELECTRONICS)), RELIABILITY(ELECTRONICS), ENCAPSULATION, CIRCUIT INTERCONNECTIONS

(U)

THE PROBLEM OF TEMPERATURE INTERMITTENT OPERATION IN ENCAPSULATED INTEGRATED CIRCUIT IS DISCUSSED AND A TECHNIQUE IS PRESENTED WHICH HAS BEEN EFFECTIVE IN DETECTING POTENTIAL FAILURES RESULTING FROM METALLIZATION, BOND OR LEAD WIRE TEMPERATURE INTERMITTENTS. THESE ARE THE MAIN CAUSES OF INTERMITTENT OPERATION IN ENCAPSULATED MICROCIRCUITS AT PRESENT, AND THIS TECHNIQUE SHOULD LEAD TO IMPROVEMENT IN ENCAPSULATED DEVICE RELIABILITY IF IMPLEMENTED AS A SCREENING OR QUALIFICATION TEST. THE INSTRUMENTATION USED AT RADC FOR THIS TECHNIQUE, CALLED THE MONITORED THERMAL CYCLE TEST (MTC), IS PRESENTED AND A PROPOSED STANDARD TEST METHOD, BASED ON THIS TEST IS INCLUDED AS AN APPENDIX. SEVERAL REPRESENTATIVE DEVICE FAILURE ANALYSIS SUMMARIES ARE INCLUDED TO ILLUSTRATE THE CAUSE OF TYPICAL ENCAPSULATED INTEGRATED CIRCUIT INTERMITTENTS RESULTING FROM FAILURE OF THE LEAD WIRE-BOND-INTERCONNECT SYSTEM. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-718 336 13/9 20/11

NAVAL AIR ENGINEERING CENTER PHILADELPHIA PA ENGINEERING DEPT (SI)

A STUDY IN TERMINAL BENDING OF UNIFORM AND ENCAPSULATED WIRE ROPE WITH LINEAR AND NON-LINEAR CONSTITUTIVE EQUATIONS.

(U)

JAN 71 114P BLACK, ROBERT;
REPT. NO. NAEC-ENG-7683
PROJ: A3405373/2008/1F32461402

UNCLASSIFIED REPORT

DESCRIPTORS: ( CABLES (MECHANICAL), BENDING), LOADING (MECHANICS), BENDING, DEFORMATION, CORDAGE, STRAIN (MECHANICS), ENCAPSULATION, ARRESTING GEAR

(U)

THE REPORT DEVELOPS EQUATIONS FOR THE CALCULATION
OF THE TERMINAL FORCES AND MOMENTS ABOUT A BUILT-IN
END OF A WIE ROPE WHEN THE UPSTREAM END IS SUBJECTED
TO A TENSILE LOAD APPLIED AT AN ANGLE MEASURED FROM
THE DIRECTION TAKEN BY THE LONGITUDINAL AXIS OF THE
ROPE AT THE POINT OF ATTACHMENT. SOLUTIONS FOR
THESE FORCES AND MOMENTS AND THE ROPE CURVATURE ARE
GIVEN ALONG THE LENGTH OF THE CABLE AND THE EFFECT OF
THESE QUANTITIES UPON THE STRANDS ARE DETERMINED.
THE ANALYSES ARE PRESENTED FOR WIRE ROPE LINEAR AND
NONLINEAR CONSTITUTIVE EQUATIONS. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-722 043 9/5
GENERAL MOTORS CORP KOKOMO IND DELCO ELECTRONICS DIV

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.

(U)

DESCRIPTIVE NOTE: FINAL REPT. 9 JAN 69-9 SEP 70,

JAN 71 171P BEVINGTON, JOHN R.; COOK,

JAMES P.; LITTLE, DAVID R.; INGLE, L. V.;

CONTRACT: F30602-69-C-0154

MONITOR: RADC, GIDEP TR-71-8, 515.00.00.00-F9-10

UNCLASSIFIED REPORT

DESCRIPTORS: (\*INTEGRATED\_CIRCUITS,

\*ENCAPSULATION), PLASTICS,

RELIABILITY(ELECTRONICS), ACCEPTABILITY (U)

INSUFFICIENT INFORMATION HAS BEEN AVAILABLE WITH RESPECT TO THE LONG-TERM STABILITY OF PLASTIC-ENCAPSULATED MICROCIRCUITS. OF SPECIAL INTEREST IS THE DEGREE OF SUSCEPTIBILITY OF THESE PLASTIC PACKAGES TO SUCH ENVIRONMENTAL STRESSES AS MOISTURE RESISTANCE (WITH AND WITHOUT BIAS) AND THERMAL SHOCK. THE OBJECTIVES OF THE STUDY ARE TO DETERMINE THE SUITABILITY OF REPRESENTATIVE, PRODUCTION, PLASTIC-ENCAPSULATED INTEGRATED CIRCUITS FOR MILITARY APPLICATIONS, AND TO DEVELOP METHODS AND TECHNIQUES FOR ASSESSING AND ASSURING THE RELIABILITY OF SUCH CIRCUITS. A SERIES OF SCREENS AND TESTS WERE PERFORMED ON SELECTED CIRCUITS, AND DETAILED FAILURE ANALYSES WERE HADE TO DETERMINE THE FAILURE MODES AND MECHANISMS CHARACTERISTIC OF THE VARIOUS TYPES OF PLASTIC ENCAPSULATION. THE REPORT INCLUDES DETAILED TEST RESULTS FROM LONG-TERM TESTS AND FROM SHORT-TERM HIGHLY ACCELERATED TESTS. COMPARISONS ARE MADE BETWEEN PACKAGE TYPES UNDER THE SAME STRESS CONDITIONS, BETWEEN SCREENED AND UNSCREENED GROUPS. AND BETWEEN STANDARD AND ACCELERATED TEST RESULTS. A STRESS TO DESTRUCTION TEST PROGRAM, INCLUDING EQUIVALENT HERMETIC TYPES FOR DIRECT COMPARISON WITH PLASTIC-ENCAPSULATED DEVICES UNDER SELECTED ACCELERATED TEST CONDITIONS, WAS PERFORMED. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-722 405 9/5 1/4
GENERAL DYNAMICS/CONVAIR SAN DIEGO CALIF

THERMAL ANALYSIS. ADVANCED AUTOPILOT FLATPAK MODULE DESIGN RECOMMENDATIONS.

(U)

DEC 67 38P HALL, J. E.;

REPT. NO. GDC-BTD67-144

CONTRACT: AF 04(695)-710

MONITOR: SAMSO TR-71-86

UNCLASSIFIED REPORT

DESCRIPTORS: (\*MODULES(ELECTRONICS), THERMAL
ANALYSIS), (\*AUTOMATIC PILOTS,
MODULES(ELECTRONICS)), (\*ENCAPSULATION,
MODULES(ELECTRONICS)), DESIGN, THERMAL
INSULATION, THERMAL CONDUCTIVITY, HEAT SINKS,
EXPANDED PLASTICS, ISOCYANATE PLASTICS, EPOXY
PLASTICS, COMPOSITE MATERIALS, COPPER
(U)
IDENTIFIERS: METAL PARTICLE COMPOSITES

A THERMAL MODEL OF A TYPICAL ELECTRONIC FLATPAK MODULE WAS CONSTRUCTED AND ANALYZED. POLYURETHANE FOAM AND ALUMINUM-FILLED EPOXY WERE ASSESSED FOR USE AS ENCAPSULATION MATERIALS. THE VALUE OF UTILIZING COPPER SHEETS AS HEAT CONDUCTIVE PATHS FROM HEAT GENERATORS TO THE FLATPAK FRAMES WAS ASSESSED. FROM A LARGE NUMBER OF DIGITAL COMPUTER CALCULATIONS. ACCUMULATED DATA WERE CORRELATED WITH SOME PRELIMINARY TEST DATA. WITH THIS INFORMATION. DESIGN RECOMMENDATIONS WERE MADE TO ASSIST THE FLATPAK DESIGNER. IN GENERAL, THE ECONOMICS OF MATERIAL AND FABRICATION COSTS MUST BE COMPARED, BY THE DESIGNER, WITH THERMAL CHARACTERISTICS OF THE ENCAPSULATION METHODS. TEMPERATURES ATTAINED BY CRITICAL HEAT GENERATING ELEMENTS ARE DEPENDENT UPON: (1) LOCATION RELATIVE TO THE FLATPAK FRAME. (2) LENGTH OF ELECTRICAL LEADS AND CONNECTIONS, AND (3) CONTACT RESISTANCES OF THE ELECTRICAL CONNECTIONS AND HEAT CONDUCTIVE SHEETS. RECOMMENDATIONS INCLUDE A TABULATION OF ALLOWABLE THERMAL RESISTANCE FOR EACH HEAT GENERATOR CONFIGURATION. (AUTHOR)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-722 448 11/3 4/2
NATIONAL CASH REGISTER CO DAYTON OHIO CAPSULAR RESEARCH
AND PRODUCT DEVELOPMENT DEPT

MICROENCAPSULATED CLOUD SEEDING
MATERIALS. (U)

DESCRIPTIVE NOTE: FINAL REPT. 15 AUG 69-14 JAN 71, FEB 71 158P ANDERSON, JERROLD L.; CONTRACT: F19628-70-C-D011 PROJ: AF-8620, ILIR-7-69 TASK: 862008, ILIR-7-69-01 MONITOR: AFCRL 71-0151

### UNCLASSIFIED REPORT

DESCRIPTORS: (\*ETHYL CELLULOSE, COATINGS),

(\*ARTIFICIAL PRECIPITATION, MATERIALS), (\*SODIUM
CHLORIDE, \*ENCAPSULATION), (\*UREA,
ENCAPSULATION), POLYMERS, FOG, PARTICLE SIZE,
PHOSPHATES, OPTICAL PROPERTIES, ADSORPTION,
PRODUCTION, SCATTERING, FEASIBILITY STUDIES,
POWDERS
(U)
IDENTIFIERS: \*CLOUD SEEDING,
MICROENCAPSULATION

A PROCESS WAS DEVELOPED FOR ENCAPSULATING HYGROSCOPIC, CLOUD-SEEDING AGENTS, SODIUM CHLORIDE AND UREA. THE ENCAPSULATION PROCESS INVOLVES DEPOSITING THE COATING POLYMER, ETHYLCFLLULOSE, ONTO FINELY DIVIDED POWDERS USING A PHASE SEPARATION-COACERVATION TECHNIQUE. THE PROCESS PRODUCES SMALL ENCAPSULATED AGGREGATES, THE SIZE AND DISTRIBUTION OF WHICH CAN BE VARIED. ENCAPSULATED MATERIALS PREPARED BY THE PROCESS ARE UNIQUE IN THAT THEY ARE VOID, ESSENTIALLY, OF POWDER FINES. LAPORATORY TESTS OF BOTH ENCAPSULATED SODIUM CHLORIDE AND UREA PROVED THE POWDERS TO BE RESISTANT TO CLUMPING AND CAKING ASSOCIATED WITH PREMATURE MOISTURE SORPTION OCCURRING DURING STORAGE AND HANDLING. THE ENCAPSULATION COATING POLYMER, ETHYLCELLULOSE, IS WATER INSOLUBLE, BUT IS PERMEABLE TO WATER VAPOR. WATE, AND SOLUTES. HENCE, WATER SORPTION AND PARTICLE GROWTH PROPERTIES RESULTING FROM EXPOSURE OF THE ENCAPSULATED PARTICLES TO HUMID ATMOSPHERES ARE EFFECTED BY DIFFUSION-MASS TRANSPORT PROCESSES. LABORATORY TESTING OF ENCAPSULATED SODIUM CHLORIDE AND UREA MATERIALS IN SIMULATED WARM FOG ATMOSPHERES REVEALED WATER SORPTION CHARACTERISTICS WHICH WERE COMPARABLE TO UNENCAPSULATED PARTICLES HAVING EQUIVALENT DIMENSION. (AUTHOR) (U)

UNCLASSIFIED

/ZZZHT

DDC REPORT BIBLIOGRAPHY SEARCH CONTPOL NO. /ZZZHT

AD-726 018 14/2 13/8 9/1
ARMY ELECTRONICS COMMAND FORT MONMOUTH N J

1.5-KW SOLID-STATE POWER CYCLER.

(0)

DESCRIPTIVE NOTE: RESEARCH AND DEVELOPMENT TECHNICAL REPT. 1

APR 71 18P MALINOWSKI, GREGORY J.;

REPT. NO. ECOM-3410

PROJ: DA-1-H-662705-A-056 TASK: 1-H-662705-A-05601

UNCLASSIFIED REPORT

DESCRIPTORS: (\*EMBEDDING SUBSTANCES, \*TEST EQUIPMENT(ELECTRONICS)), (\*TRANSISTORS, ENCAPSULATION), TIMING CIRCUITS, RELAXATION OSCILLATORS, SEMICONDUCTOR DEVICES, PULSE AMPLIFIERS, THERMAL PROPERTIES IDENTIFIERS: POWER CYCLERS

(U)

(U)

THE REPORT DESCRIBES THE DESIGN AND OPERATION OF A SOLID-STATE POWER CYCLER USED IN THE EVALUATION OF PLASTIC ENCAPSULATED SEMICONDUCTOR DEVICES. THE CYCLER CAN SWITCH LOADS UP TO 2.0 KW WITH A VARIABLE DUTY CYCLE. THIS REPORT ALSO SHOWS THE PERFORMANCE OF THE CYCLER AS DESIGNED AND RECOMMENDS FUTURE MODIFICATIONS FOR ADDED VERSATILITY.

(AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AU-727 680 6/8
ARMY NATICK LABS MASS FOOD LAB

DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY MIXES.

(U)

DESCRIPTIVE NOTE: TECHNICAL REPT.,

MAY 71 27P UMINA, ANTHONY ; KELLEY, NANCY

SEVERSON, THOMAS ; WESTCOTT, DONALD E.;

REPT. NO. FL-133

PROJ: PE-728012.12

MONITOR: USA-NLABS TR-71-54-FL

UNCLASSIFIED REPORT

DESCRIPTORS: (\*FOOD, STORAGE), CARBON DIOXIDE,
MOISTURE, TEMPERATURE, STABILITY, SODIUM
COMPOUNDS, CARBONATES, PHOSPHATES, ALUMINUM
COMPOUNDS, SEPARATION, ENCAPSULATION, PACKAGING,
MILITARY REQUIREMENTS
(U)
IDENTIFIERS: \*CAKE MIXES, CAKE MIX SHELF LIFE,
SODIUM BICARBONATES, SODIUM ALUMINUM PHOSPHATES,
\*FOOD STORAGE

IN ORDER TO PROLONG THE SHELF LIFE OF A PREPARED BAKERY MIX A LEAVENING SYSTEM WAS DESIRED WHICH WOULD PREVENT THE PREMATURE ESCAPE OF CARBON DIOXIDE DUE TO INTERACTION WITH MOISTURE IN THE PRODUCT DURING PROLONGED HIGH TEMPERATURE STORAGE. A VARIETY OF METHODS WAS TRIED WHICH WOULD PROVIDE A BARRIER BETWEEN THE SODIUM BICARBONAIE AND THE LEAVENING ACID, SODIUM ALUMINUM PHOSPHATE, AND AVAILABLE MOISTURE IN THE MIX. THESE INCLUDED ENCAPSULATING THE SODIUM BICARBONATE PARTICLES WITH HYDROPHOBIC MATERIALS SUCH AS HYDROGENATED VEGFTABLE OR ANIMAL OILS. THE SHORTENING PROTECTED SODIUM BICARBONATE METHOD WAS DEVELOPED INTO A TWO LAYERED BAKERY MIX. SEPARATING THE SODIUM BICARBONATE FROM THE MOISTURE CONTAINING INGREDIENTS OF THE MIX. PHYSICAL SEPARATION OF THE SODIUM BICARBONATE WAS ALSO INVESTIGATED BY PACKAGING THE SODIUM BICARBONATE IN A MOISTURE PROOF POUCH FROM WHICH IT COULD BE MIXED WITH THE REMAINING INGREDIENTS AT THE TIME OF BAKING. IT WAS FOUND THAT BOTH THE PHYSICALLY SEPARATED AND THE SHORTENING - PROTECTED SODIUM BICARBONATE IN A LAYERED MIX METHOD WERE SUCCESSFUL IN PREVENTING THE PREMATURE ESCAPE OF CARBON DIOXIDE. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-729 680 8/7 20/11
BATTELLE MEMORIAL INST COLUMBUS OHIO COLUMBUS LABS

THE EFFECT OF FLUIDS AND CYCLIC LOADING ON THE ELASTIC CONSTANTS OF ROCKS.

(U)

DESCRIPTIVE NOTE: SEMIANNUAL REPT. 18 DEC 70-18 JUN 71,

AUG 71 39P LA MORI, PHILLIP N.; CONTRACT: H0210007, ARPA ORDER-1579

UNCLASSIFIED REPORT

DESCRIPTORS: (\*SEDIMENTARY ROCK, STRUCTURAL PROPERTIES), LOADING (MECHANICS), CRACKS, POROSITY, ELASTICITY, COMPRESSIVE PROPERTIES, ACOUSTIC PROPERTIES, EXPERIMENTAL DATA IDENTIFIERS: ACOUSTIC VELOCITY

(U)

(U)

SIMULTANEOUS MEASUREMENTS OF ACOUSTIC VELOCITY AND LINEAR STRAIN HAVE BEEN MADE ON SAMPLES OF SALEM LIMESTONE AND BEREA SANDSTONE. CYCLIC LOADING CONDITIONS OF 0-1-0-5-0-8-0 KB WERE MADE ON THESE SAMPLES. THE RESULTS SHOW THAT THIN CRACKS HAVE A LARGE EFFECT ON ACOUSTICALLY MEASURED PROPERTIES AND LITTLE EFFECT ON LINEAR STRAIN. BOTH ROCK SAMPLES ARE QUITE POROUS AND EXHIBIT THE CRUSHING MODE OF FAILURE: AT 1.5 KB FOR THE LIMESTONE, 5 KB FOR THE SANDSTONE. THIS CRUSHING GREATLY DECREASES THE STATIC MODULUS BUT CHANGES THE ACOUSTIC MODULUS ONLY SLIGHTLY. A PECULIAR KNEE DEVELOPS IN THE VELOCITY CURVE NEAR THE PRESSURE OF THE CRUSH-UP AND APPEARS TO BE AN INDICATOR OF IT. THE RESULTS SUGGEST THAT VOLUME MEASUREMENTS OF ELASTIC CONSTANTS ARE TO BE PREFERRED TO ACOUSTIC MEASUREMENTS FOR EVALUATING EXCAVATION OF ROCK. (AUTHOR)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-729 691 13/8
SOUTHWEST RESEARCH INST SAN ANTONIO TEX

PREPARATION OF CAPSULES.

(U)

DESCRIPTIVE NOTE: FINAL REPT. 1 AUG 70-31 JUL 71, SEP 71 8P ADAMS, LEON M.; CONTRACT: NODO14-71-C-0027 PROJ: NR-356-509, SWRI-01-2928-01

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ENCAPSULATION, REVIEWS),
POLYVINYL ALCOHOL, PREPARATION, MATERIALS

(1/)

A GOVERNMENT-FURNISHED MATERIAL WAS SUCCESSFULLY ENCAPSULATED, AND A NUMBER OF SMALL VIALS OF THE RESULTING CAPSULES WERE SUPPLIED TO THE OFFICE OF NAVAL RESEARCH FOR TESTING. THE BEST CAPSULE SHELL FORMULATION EVALUATED WAS PREDOMINANTLY POLY(VINYL ALCOHOL). (AUTHOR)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO, /ZZZHT

AD-730 908 11/1

NATIONAL CASH REGISTER CO DAYTON OHIO CAPSULAR PRODUCTS
RESEARCH AND DEVELOPMENT

DEVELOPMENT OF MULTIPURPOSE CAPSULAR ADHESIVE SYSTEMS.

(U)

DESCRIPTIVE NOTE: FINAL REPT.,

MAY 71 60P PETERS, GAVIN H. ; SCHAAB, CARL K. ; HILBELINK, RONALD D. ; DAVIS, TERRY

R.;

CONTRACT: DAAA21-68-C-0581
MONITOR: PA TR-4215

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ADHESIVES, PLASTICS), EPOXY PLASTICS, POLYESTER PLASTICS, AGING(MATERIALS), ENCAPSULATION, STABILITY, UNDERWATER

(U)

A UNIQUE: POLYESTER-EPOXY ADHESIVE SYSTEM WAS DEVELOPED WHICH CURES VERY RAPIDLY UPON MIXING OF ITS TWO COMPONENTS AND ADHERES TO A MULTITUDE OF SUBSTRATES UNDER VARIOUS ENVIRONMENTAL CONDITIONS. EACH OF THE TWO LIQUID ADHESIVE COMPONENTS CAN BE ENCAPSULATED TO FORM 'PSEUDO SOLIDS'. MIXING TOGETHER OF THE TWO CAPSULAR COMPONENTS INTO THE PROPER RATIO FORMS A STABLE, 'ONE CAN, DRY POWDER ADHESIVE THAT IS EASILY ACTIVATED UPON RUPTURE OF THE CAPSULES. THIS RAPID CURING CAPSULAR ADHESIVE SYSTEM, WITH ITS IMPROVED STABILITY, HANDLING AND LOGISTICS CHARACTERISTICS DUE TO ENCAPSULATION: WAS FURTHER CHARACTERIZED DURING THE SECOND PHASE OF THE PROGRAM. CAPSULAR ADHESIVE STABILITY WAS FOUND TO BE NINE MONTHS UNDER LABORATORY CONDITIONS WITH THE EPOXY COMPONENT BEING THE LIMITING FACTOR. SEVERAL FORMULATION VARIATIONS WERE MADE THAT AFFECTED CURE TIME. BOND STRENGTH AND ADHESION PROPERTIES. ENCAPSULATION OF EACH OF THE TWO COMPONENTS WAS EASILY SCALED UP THROUGH THE PILOT-PLANT STAGE. SEVERAL MECHANICAL ADHESIVE APPLICATOR DESIGNS WERE DEVELOPED AND EVALUATED FOR THE EXTRUSION AND APPLICATION OF BOTH THE CAPSULAR ADHESIVES AND THE SAME FORMULATIONS IN THEIR LIQUID. UNENCAPSULATED FORMS (AUTHOR)

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-804 551 9/1 9/5

RADIO CORP OF AMERICA SOMERVILLE N J ELECTRONIC COMPONENTS
AND DEVICES

TRANSISTOR, VHF, SILICON, POWER, LINEAR, 30-MHZ, 100 WATTS PEP. (U)

DESCRIPTIVE NOTE: FINAL REPT. 1 JUN 65-30 JUN 66, DEC 66 123P ROSENZWEIG.R.; CHANG. 2. F.

CONTRACT: DA-38-043-AMC-01387(E)
PROJ: DA-1E6-22001-A-056
MONITOR: ECOM 01387-F

## UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, \*VERY HIGH FREQUENCY),
(\*POWER AMPLIFIERS, \*SILICON), ELECTRIC POWER
PRODUCTION, GAIN, MODULATION, DISTORTION,
CAPACITANCE, ELECTRICAL IMPEDANCE, RESISTORS,
STORAGE, LIFE EXPECTANCY, RADIOFREQUENCY
INTERFERENCE, ENCAPSULATION, SILICONE PLASTICS
(U)

THIS REPORT DESCRIBES THE WORK PERFORMED IN THE DEVELOPMENT AND FABRICATION OF A LINEAR AMPLIFIER TRANSISTOR WITH A GOAL OF 100 WATTS PEP AT 30 MEGAHERTZ WITH -30 DB INTERMODULATION DISTORTION. 15-08 POWER GAIN, AND EFFICIENCY GREATER THAN 35 PERCENT. THE TRANSISTOR STRUCTURE INCORPORATES DIFFUSED BALLAST RESISTANCE FOR SECOND\_BREAKDOWN PROTECTION. A TEMPERATURE-COMPENSATING DIODE HAS BEEN PLACED INSIDE THE TRANSISTOR PACKAGE TO PROVIDE CLASS AB BIAS-POINT CONTROL. THE PACKAGE 'S A UNIQUELY DESIGNED STUD PACKAGE HAVING SHORT, FLAT. LOW INDUCTANCE. ISOLATED TERMINALS. THERE ARE FOUR ISOLATED TERMINALS: THREE TERMINALS FOR THE TRANSISTOR AND ONE TERMINAL FOR THE DIODE. THE PELLET IS SEALED BY ENCAPSULATION IN A SILICON RESIN. PERFORMANCE DATA ON THE SUBMITTED FINAL SAMPLES REVEALS THAT 20 PERCENT OF THE TRANSISTORS WERE CAPABLE OF ATTAINING THE MAJOR GOAL OF 100 WATTS PEP WITH -30 DB INTERMODULATION DISTORTION. MEDIAN POWER GAIN ON SAMPLE TRANSISTORS WAS 14 DB AND COLLECTOR DIFFERENCES WERE NEAR 50 PERCENT. THE DEVICE WAS CAPABLE OF 150 WATTS DISSIPATION AT ROOM TEMPERATURE . (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-815 470 9/5 13/8 GENERAL DYNAMICS/POMONA CALIF

CORROSION PREVENTION/DETERIORATION CONTROL IN ELECTRONIC COMPONENTS AND ASSEMBLIES.

(U)

DESCRIPTIVE NOTE: FINAL SUMMARY ENGINEERING REPT., 66 152P SPARLING, R. H.;

REPT. NO. CR-6-347-958-001

CONTRACT: DA-01-021-AMC-12641(Z)

PROJ: DA-1400-A019

## UNCLASSIFIED REPORT

DESCRIPTORS: (\*ELECTRONIC EQUIPMENT, \*CORROSION INHIBITION), (\*RELIABILITY (ELECTRONICS), CORROSION INHIBITION), DEGRADATION, MATERIALS, PROCESSING, SELECTION, ENVIRONMENT, PROTECTIVE TREATMENTS, COATINGS, ENCAPSULATION, BONDING, SOLDERING, WELDING, PACKAGING

(U)

THE PURPOSE OF THIS DOCUMENT IS TO FOCUS THE ATTENTION OF DESIGNERS ON CORROSION AND THE CONSEQUENT DEGRADATION OF RELIABILITY OF ELECTRONIC ITEMS. THE REPORT POINTS OUT DANGEROUS COMBINATIONS OF MATERIALS AND PROCESSES, EMPHASIZES THE IMPORTANCE OF PROPER SELECTION OF MATERIALS, AND PROVIDES THE DESIGNER WITH MODERN TECHNIQUES FOR PREVENTION OF DETERIORATION. THE AIM OF THIS REPORT IS NOT TO DICTATE DESIGN, BUT TO HELP THE DESIGNER MEET ENVIRONMENTAL REQUIREMENTS.

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-821 915 9/5 20/12
WESTERN ELECTRIC CO INC NEW YORK

MICROWAVE DIODE RESEARCH.

(U)

DESCRIPTIVE NOTE: REPT. NO. 26 (FINAL), 10 JUN 65-9 JUN 67.

OCT 67 35P CICCOLELLA,D. F. IDE LOACH,B. C. , JR. IMARINACCIO,L. P. IMISAWA, T. ;SMITH,K. D. ;
CONTRACT: DA-28-043-AMC-01445(E)
PROJ: DA-1E6-22001-A-056
TASK: 1E6-22001-A-056-04

01445-F

. .

UNCLASSIFIED REPORT

MONITOR: ECOM

SUPPLEMENTARY NOTE: PREPARED IN COOPERATION WITH BELL TELEPHONE LABS., INC., WHIPPANY, N. J.

DESCRIPTORS: (\*AVALANCHE DIODES, \*MICROWAVE OSCILLATORS), MICROWAVE FREQUENCY, GERMANIUM, SILICON, ENCAPSULATION, CRYSTAL OSCILLATORS, MANUFACTURING METHODS (U)

IDENTIFIERS: \*IMPATT OSCILLATORS (U)

THE WORK DESCRIBED IN THIS REPORT IS PART OF A BROAD PROGRAM OF CONTINUING THEORETICAL AND EXPERIMENTAL STUDIES TO ACHIEVE IMPROVED MICROWAVE SEMICONDUCTOR DIODES AND COMBINATION MICROWAVE DEVICES. OF IMMEDIATE PARTICULAR INTEREST IS THE RESEARCH AND DEVELOPMENT EFFORT DIRECTED TOWARD CLARIFYING THE RELATIONSHIP BETWEEN STRUCTURE AND BEHAVIOR OF AVALANCHE TRANSIT-TIME DIODE OSCILLATORS AND IMPROVING THEIR MICROWAVE PERFORMANCE. CHAPTER 1 DESCRIBES EXPERIMENTAL WORK PERFORMED IN AN EFFORT TO OBTAIN MAXIMUM MICROWAVE CW OUTPUT FROM A SINGLE ENCAPSULATION, SPECIFICALLY BY USE OF SEVERAL SMALL SILICON WAFERS MOUNTED ON A COMMON PEDESTAL. CHAPTER 2 EXPLORES, ANALYTICALLY AND BY EXPERIMENTS, THE POSSIBILITIES OF OPERATING SEVERAL AVALANCHE WAFERS 12 PARALLEL FOR HIGHER POWER AND/OR HIGHER EFFICIENCY. CHAPTER 3 SUMMARIZES AND PLACES IN PERSPECTIVE THE RESULTS ACHIEVED IN TWO YEARS! WORK ON THE PRESENT CONTRACT. WHICH HAS COVERED THE EVOLUTION OF AN EXPERIMENTAL DEVICE INTO AN EFFICIENT, RUGGED MICROWAVE SOURCE. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-822 016 9/5
WESTERN ELECTRIC CO INC NEW YORK

MICROWAVE DIODE RESEARCH.

(U)

DESCRIPTIVE NOTE: INTERIM REPT. NO. 4, 10 SEP 66-9 MAR 67,

OCT 67 31P CICCOLELLA, D. F. ; GIBBONS,

G. ; RULISON, R. L. ;

CONTRACT: DA-28-043-AMC-01445(E)

PROJ: DA-1E6-22001-A-056 TASK: 1E6-22001-A-056-04 MONITOR: ECOM 01445-4

#### UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: PREPARED IN COOPERATION WITH BELL TELEPHONE LABS., INC., WHIPPANY, N. J.

DESCRIPTORS: (\*AVALANCHE DIODES, \*MICROWAVE OSCILLATORS), THERMAL STRESSES, SILICON, ENCAPSULATION, RADIOFREQUENCY POWER, GERMANIUM, SUPERHIGH FREQUENCY, EFFICIENCY, THERMAL PROPERTIES, PACKAGING (U) IDENTIFIERS: IMPATT (IMPACT AVALANCHE TRANSIT TIME)

WORK ON THE FABRICATION AND TESTS OF IMPROVED SILICON INPATT OSCILLATORS IS DESCRIBED IN CHAPTER I. EFFORT HAS BEEN CONCENTRATED ON THE P-N DIODE STRUCTURE BECAUSE OF ADVANTAGES IN PROCESS YIELD AND IN DIODE PERFORMANCE. A NEW AND MORE RUGGED ENCAPSULATION HAS BEEN USED FOR MOST OF THE DIODES FABRICATED IN THIS PERIOD; THIS FACILITATES CIRCUIT MOUNTING AND THERMAL DESIGN. IN THIS ENCAPSULATION A SINGLE SILICON DIODE HAS PROVIDED 1500-MW CW OUTPUT POWER. AND MANY UNITS IN THE 4-TO 6-GHZ RANGE HAVE GIVEN POWER OUTPUT GREATER THAN ONE WATT. FABRICATION AND TEST RESULTS OBTAINED WITH GERMANIUM P-N IMPATT DIODES, SUPPORTED IN PART BY THE PRESENT CONTRACT, ARE REPORTED IN CHAPTER 11. THIS WORK HAS RESULTED IN THE HIGHEST CW EFFICIENCY (12.1 PERCENT) SO FAR OBTAINED WITH IMPATT DEVICES, AND CW POWER OUTPUT IN EXCESS OF 500 MW AT & GHZ. THERMAL DISSIPATION PROBLEMS ARE MORE SEVERE WITH GERMANIUM THAN SILICON; THE AVERAGE BURNOUT TEMPERATURE APPEARS TO BE ABOUT 150 C. (AUTHOR) (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-823 785 15/2
STANFORD RESEARCH INST MENLO PARK CALIF

MICROENCAPSULATION.

(U)

DESCRIPTIVE NOTE: SPECIAL TECHNICAL REPT. NO. 17. APR 64-JUN 67.

JUN 67 94P BREEN, W. H. ; GIBSON, R. W. ; RADDING, S. B., ; SIRINE, G. F. ; BROWN, A. G. ;

CONTRACT: DA-18-035-AMC-122(A)

PROJ: SRI-PAU-4900 TASK: 18522301A08101

#### UNCLASSIFIED REPORT

DESCRIPTORS: (\*ENCAPSULATION, \*CHEMICAL WARFARE AGENTS), (\*DISSEMINATION, CHEMICAL WARFARE AGENTS), (\*CS AGENTS, ENCAPSULATION), POLYMERS, SOLUTIONS, POLYVINYL ALCOHOL, COATINGS, DRYING, SPRAYS, AIR, SOLVENTS, FREEZE DRYING (U)
IDENTIFIERS: MICROENCAPSULATION (U)

POTENTIAL CONTRIBUTIONS OF MICROENCAPSULATION TO DISSEMINATION SYSTEMS INCLUDE REDUCTION OF AGENT HANDLING HAZARDS, PRESIZING, STABILIZATION BY ISOLATION, PROTECTION FROM HOSTILE ENVIRONMENTS, AND SUSTAINED RELEASE, AS WELL AS POSSIBLITIES FOR NEW SYSTEMS BASED ON IMPACTION CAPSULES OR LARGE, EXPLOSIVE-COATED, SELF-DISSEMINATING CAPSULES. IN THIS PROGRAM ENCAPSULATION OF A WIDE RANGE OF ACTIVE AND INACTIVE MATERIALS WAS CARRIED OUT USING NCR-TYPE PROCESSES TO ASSESS REAL CAPABILITIES AND LIMITATIONS FOR APPLICATIONS TO BOTH EXISTING AND NEW DISSEMINATION SYSTEMS, GENERIC PROCEDURES WERE DEVELOPED FOR ADAPTATION OF MICROENCAPSULATION TO NEW MATERIALS, PRIMARILY USING GELATIN OR POLYVINYL ALCOHOL (PVA) AS WALL MATERIALS, AND A VARIETY OF SPECIAL SAMPLES WAS PREPARED FOR EVALUATION STUDIES AT STANFORD RESEARCH INSTITUTE AND AT EDGEWOOD ARSENAL. MAJOR EFFORTS WERE DEVOTED TO PRODUCTION AND STUDY OF SUSTAINED - PELEASE INHALABLE CAPSULES, 1-10 MICROONS IN DIAMETER. PARTICULARLY IN RESPECT TO POSSIBILITIES FOR PROLONGED-EFFECT CS. CS CAPSULES WITH BOTH GELATIN AND PVA WALLS WERE PREPARED IN THIS SIZE RANGE AND CS RELEASE INTO AQUEOUS MEDIA WAS SHOWN TO BE CONTROLLABLE IN RATE OVER A RANGE TO TWO ORDERS OF MAGNITUDE LESS THAN FOR NONCAPSULAR CS.

(U)

UNCLASSIFIED

ZZZHT

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-827 272 15/2 7/4
STANFORD RESEARCH INST MENLO PARK CALIF

RESEARCH STUDIES ON THE DISSEMINATION OF SOLID AND LIQUID AGENTS. (U)

DESCRIPTIVE NOTE: FINAL REPT. APR 64-DEC 67,
DEC 67 138P POPPOFF, I. G. ; THUMAN, W.

C.; CONTRACT: DA-18-035-AMC-122(A) PROJ: DA-18522301AD81, SRI-PAU-4900 TASK: 18522301AD8101

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL WARFARE AGENTS,
DISSEMINATION), SOLIDS, LIQUIDS, AEROSOLS,
EXPLOSIVE MATERIALS, ELECTROSTATICS, DETONATIONS,
SHOCK WAVES, IGNITION, PYROTECHNICS, PYROLYSIS,
OXIDATION, DEGRADATION, CONDENSATION, ULTRASONIC
RADIATION, PNEUMATIC SYSTEMS, ENCAPSULATION,
HYDROLYSIS, EQUATIONS OF STATE, ENTROPY,
ATOMIZATION, POWDERS
(U)
IDENTIFIERS: POINT-SOURCE DISSEMINATION

THE OBJECTIVE OF THE PROGRAM WAS TO PROVIDE BASIC INFORMATION NECESSARY FOR AN OVERALL IMPROVEMENT OF CHEMICAL AGENT DISSEMINATION TECHNIQUES. STUDIES WERE MADE OF EXPLOSIVE GENERATIONS OF AEROSOLS (MECHANICS OF EXPLOSIVE PROCESSES! DETONATION, SHOCK, AND REACTION PROCESSES; IGNITION PROCESSES; COMMINUTION PROCESSES); THERMAL AND PYROTECHNIC GENERATION OF AEROSULS (THERMAL AND PYROTECHNIC PROCESSES! PYROLYTIC AND OXIDATIVE DEGRADATION PROCESSES! CONDENSATION PROCESSES) : "LTRASONIC; PNEUHATIC, AND ATOMIZATION PROCESSES! ELECTROSTATIC PHENOMENA ASSOCIATED WITH AEROSOL PRODUCTION; THE APPLICATION OF MICROENCAPSULATION TO AEROSOL GENERATION AND ENHANCEMENT; AND NATURAL AEROSOL GENERATION. A CRITICAL SUMMARY OF THE PROGRAM AND RECOMMENDATIONS FOR FUTURE WORK IS FIRST PRESENTED. THIS IS FOLLOWED BY A DISCUSSION OF ACCOMPLISHMENTS AND RECOMMENDATIONS FOR FUTURE RESEARCH IN EACH OF THE STUDY AREAS LISTED ABOVE, WITH REFERENCE TO PROGRAM REPORTS (22 SPECIAL TECHNICAL REPORTS AND 13 QUARTERLY PROGRESS REPORTS) FOR DETAILS. (AUTHOR)

73

(U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-838 791 9/1 13/8
NAVAL AMMUNITION DEPOT CRANE IND

MICRO-NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPMENTS.

(U)

AUG 68 53P
REPT. NO. NAD-CR-MICRO NOTES-25
MONITOR: IDEP 515.00.00.00-X9-11

#### UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SPONSORED BY NAVAL AIR SYSTEMS COMMAND, WASHINGTON, D. C. AND NAVAL ELECTRONICS SYSTEM COMMAND, WASHINGTON, D. C.

DESCRIPTORS: (\*NAVAL EQUIPMENT,

\*MICROMINIATURIZATION(ELECTRONICS)),

(\*SEMICONDUCTOR DEVICES, \*ENCAPSULATION),

RELIABILITY(ELECTRONICS), EPOXY PLASTICS,

TRANSISTORS, SEMICONDUCTORS, MILITARY

REQUIREMENTS, INTEGRATED CIRCUITS, PLASTIC COATINGS,

REPORTS

(U)

CONTENTS: RELIABILITY ASSESSMENT OF EPOXY TRANSISTORS: PRESENT RELIABILITY STATUS OF PLASTIC - ENCAPSULATED SEMICONDUCTORS AND AN EVALUATION OF THEIR POTENTIAL FOR USE IN MILITARY SYSTEMS: SUMMARY OF SIGNETICS PRESENTATION INCLUDING PROPOSED GENERAL SPECIFICATION: PLASTIC SEMICONDUCTORS: WESTINGHOUSE GOLDILOX INTEGRATED CIRCUITS OFFER MILITARY RELIABILITY IN PLASTIC PACKAGES: PLASTICS FOR SEMICONDUCTOR PACKAGING: RELIABILITY OF PLASTIC INTEGRATED CIRCUITS; G-12 REPORT ON 'PLASTIC' INTEGRATED CIRCUITS; PLASTIC/ EPOXY SEMICONDUCTORS: USE OF PLASTIC ENCAPSULATED TRANSISTORS AT HAZELTINE; AN EVALUATION OF PLASTIC ENCASED SEMICONDUCTORS; SELECTION AND CONTROL OF PLASTICS FOR SEMICONDUCTOR PACKAGING; PLASTIC MICROCIRCUIT RELIABILITY: SUMMARY OF PRESENTATION ON PLASTIC ENCAPSULATED TRANSISTORS: SUMMARY OF PRESENTATION ON PLASTIC ENCAPSULATED TRANSISTORS; POSITION OF THE NAVAL APPLIED SCIENCE LABORATORY ON THE MILITARY USE OF PLASTIC ENCAPSULATED SEMICONDUCTOR DEVICES; AN R AND D PROGRAM TO DEVELOP POLYMERIC ENCAPSULANTS FOR SOLID STATE ELECTRONIC COMPONENTS. (U)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-846 071 9/1 13/8
NAVAL AMMUNITION DEPOT CRANE IND

MICRO NOTES. INFORMATION ON MICROELECTRONICS
FOR NAVY EQUIPMENTS. (U)

JAN 69 82P
REPT. NO. NAD-CR-MICRO NOTES-27
MONITOR: IDEP 515.00.00.00-X9-13

#### UNCLASSIFIED REPORT

DESCRIPTORS: (\*NAVAL EQUIPMENT,

\*MICROMINIATURIZA ION(ELECTRONICS)),

(\*SEMICONDUCTOR DEVICES, \*ENCAPSULATION),

RELIABILITY(ELECTRONICS), EPOXY PLASTICS,

TRANSISTORS, SEMICONDUCTORS, INTEGRATED CIRCUITS,

PLASTIC COATINGS, REPORTS

(U)

IDENTIFIERS: AN/AWS-27, METAL OXIDE

SEMICONDUCTORS, AVIONICS

(U)

THE REPORT IS AN EFFORT TO DISSEMINATE INFORMATION ON EVALUATION, APPLICATION, AVAILABILITY, RESEARCH AND DEVELOPMENT, AND STANDARDIZATION ACTIVITY PERTAINING TO STATE-OF-THE-ART MICROELECTRONIC CIRCUITS, DEVICES, AND MATERIALS, WITH A VIEW TOWARD AVOIDING DUPLICATION OF EFFORT AND MAKING MAXIMUM USE OF TECHNICAL RESOURCES. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD-849 285 11/4 20/13 MONSANTO RESEARCH CORP ST LOUIS MO

RHEOLOGY OF ROD-LIKE PARTICLES IN VISCOUS MEDIA. PART I. FORMATION OF COMPOSITES FROM SINGLE FIBERS.

(U)

FEB 69 46P TAKANO, MASAHARU; REPT. NO. NODO14-67-C-0218
CONTRACT: NODO14-66-C-0218, ARPA ORDER-873
PROJ: NR-356-484

#### UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: REPORT ON MONSANTO/WASHINGTON UNIV., ARPA ASSOCIATION PROJECT DEVELOPMENT OF HIGH PERFORMANCE COMPOSITES.

DESCRIPTORS: (\*COMPOSITE MATERIALS, MANUFACTURING METHODS), GRAPHITE, BORON, CARBON FIBERS, FIBERS, GLASS TEXTILES, RHEOLOGY, ANISOTROPY, SCATTERING, MATHEMATICAL MODELS, ENCAPSULATION, MECHANICAL PROPERTIES, DENSITY, EPOXY PLASTICS, SOLVENTS

(U)

THE TECHNIQUE DEVELOPED FOR PREPARING MOLDING
COMPOUNDS OF HIGH MODULUS FIBERS BY ENCAPSULATING
BUNDLES OF SHORT FIBERS WITH RESIN IS DIFFICULT TO
APPLY TO INDIVIDUALLY DISPERSED FIBERS.
PRELIMINARY MODEL STUDIES CARRIED OUT ON SHORT
GLASS FIBERS HAVE DEMONSTRATED THAT THE CRITICAL
CONCENTRATION FOR PROCESSING SINGLE FIBERS, RATHER
THAN FIBER BUNDLES, IS VERY LOW IN AQUEOUS SYSTEMS,
BUT CAN BE SIGNIFICANTLY INCREASED BY USE OF VISCOUS
MEDIA AND HIGH RATES OF SHEAR. (AUTHOR)

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZZZHT

AD=854 306 9/1 AUTONETICS ANAHEIM CALIF

INVESTIGATION OF PLASTIC EFFECTS ON SEMICONDUCTOR RELIABILITY.

(U)

DESCRIPTIVE NOTE: FINAL REPT., 22 DEC 67-31 DEC 68, MAY 69 1GIP VALLES, A. C. : ANDERSON, R.

J.;
REPT. NO. C8-387/501
CONTRACT: F30502-68-C-0125
PROJ: AF-5519
TASK: 551904

MONITUR: RADC, IDEP TR-69-82,742.00.00.00-F9-01

#### UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS,

RELIABILITY(ELECTRONICS)), (\*EM\*\*EDDJNG

SUBSTANCES, CHEMICAL CONTAMINATION), TRANSISTORS,

EPOXY PLASTICS, SILICONE PLASTICS, IMPURITIES,

IONS, FAILURE(ELECTRONICS), STRESSES,

ENCAPSULATION

(U)

THE OBJECTIVE OF THE PROGRAM WAS TO STUDY THE EFFECTS PRODUCED WHEN IONS PURPOSELY WERE INTRODUCED INTO PLASTICS AND USED ON TRANSISTORS. A MATERIALS SURVEY RESULTED IN THE SELECTION OF SEVERAL CANDIDATE HIGH PURITY EPOXY RESINS AND SEMICONDUCTOR GRADE SILICONE COATINGS. THESE PLASTICS WERE THEN SCREENED USING MECHANICAL: PHYSICAL, AND CHEMICAL TESTS. ONE EPOXY AND ONE SILICONE WERE SELECTED FOR FURTHER FUNCTIONAL TESTING AS SEMICONDUCTOR COATINGS. A METHOD WAS DEVELOPED FOR DOPING THE TWO SELECTED RESINS WITH IONS BY DISPERSING THEREIN METAL SALTS OF ORGANIC ACIDS OF ORGANO-METALLIC COMPOUNDS, DOPANTS WERE ORGANIC SALTS OF SODIUM, MAGNESIUM, ZINC, OR AN ORGANO-METALLIC COMPOUND CONTAINING CHLORIDE IONS. THE DOPED PLASTICS WERE THEN APPLIED AND CURED OVER TEST NPN TRANSISTORS. THE EFFECTS OF EACH ION ON THE TRANSISTOR PARAMETERS WERE ASCERTAINED AFTER SUILECTING THE DEVICES TO ELEVATED TEMPERATURE-REVERSE BIAS AND HIGH HUMIDITY REVERSE BIAS STRESSES. (AUTHOR) (U)

## CORPORATE AUTHOR - MONITORING AGENCY

\*AIR FORCE CAMBRIDGE RESEARCH LABS L G HANSCOM FIELD MASS

AFCRL-71-0151 MICROENCAPSULATED CLOUD SEEDING MATERIALS. AD-722 448

\*AIR FORCE OFFICE OF SCIENTIFIC RESEARCH ARLINGTON VA

AFOSR-1001 ANALOG COMPUTER RESEARCH INTO THE ENERGY-EXCLIANGE BETWEEN GASES AND SOLIDS. AD-605 159

\*AIR FORCE WEAPONS LAB KIRTLAND AFB N MEX

AFWL-TR-64-167 ENCAPSULATION OF VIRUSES. AD-620 933

\*ARMY ELECTRONICS COMMAND FORT MONMOUTH N J

ECOM-01387-F TRANSISTOR, VHF, SILICON, POWER, LINEAR, 30-MHZ, 100 WATTS PEP. AD-804 551

ECOM-01424-2 LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-631 491

ECOM-01424-3 LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-635 183

ECOM-01445-F MICROWAVE DIODE RESEARCH. AD-821 915

ECOM-01445-4 MICROWAVE DIODE RESEARCH. AD-822 016

ECOM-01524-4 RESISTORS FOR MICROPOWER CIRCUITS. AD-489 906

ECOM-2879 PRELIMINARY INVESTIGATION OF PLASTIC ENCAPSULATED TRANSISTORS. AD-660 349

ECOM-3410 1.5-KW SOLID-STATE POWER CYCLER. AD-726 018

\*ARMY ELECTRONICS LABS FORT MONMOUTH N

ER E 1101 ENCAPSULATING RESINS AND POTTING COMPOUNDS AD-096 112

\*ARMY NATICK LABS MASS FOOD LAB

FL-133 DEVELOPMENT OF A STARLE LEAVENING SYSTEM FOR BAKERY MIXES. (USA-NLABS-TR-71-54-FL) AD-727 680

\*ARMY NATICK LABS MASS

USA-NLABS-TR-71-54-FL DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY MIXES. AD-727 680

\* \* \*

\*AUTONETICS ANAHEIM CALIF

C8-387/501 INVESTIGATION OF PLASTIC EFFECTS ON SEMICONDUCTOR RELIABILITY. (RADC-TR-60-82) AD-854 306

\*BATTELLE MEMORIAL INST COLUMBUS OHIO COLUMBUS LABS

THE EFFECT OF FLUIDS AND CYCLIC

0-1 UNCLASSIFIED LOADING ON THE ELASTIC CONSTANTS OF ROCKS.
AD-729 680

\*BELL TELEPHONE LABS INC WHIPPANY N J

ENGINEERING SERVICES ON TRANSISTORS
AD-261 938

\*BUREAU OF NAVAL WEAPONS WASHINGTON D

NAVWEPS-7604

EFFECT OF PROCESS VARIABLES ON THE DIMENSYONS AND QUALITY OF EXTRUSION-COATED PROPELLANT GRAINS AD-255 962

\*CLEVITE TRANSISTOR PRODUCTS WALTHAM MASS

PRODUCTION ENGINEERING MEASURE FOR THE IMPROVEMENT OF GERMANIUM ALLOY POWER TRANSISTORS. AD-604 196

\*DEFENSE DOCUMENTATION CENTER ALEXANDRIA VA

DDC-YAS-70-39-1
PACKAGED CIRCUITS. VOLUME 1.
A/;-704 925

\*DEPUTT COMMANDER AEROSPACE SYSTEMS INGLEWOOD CALIF

DCAS-TDR62 5
CPYSTAL GROWTH AND
CRYSTALLOGRAPHY. A LITERATURE
SURVEY
AD-274 642

TDR62 5
CRYSTAL GROWTH AND
CRYSTALLOGRAPHY. A LITERATURE
SURVEY
(DCAS-TDR62 5)
AD-274 642

\*DOUGLAS AIRCRAFT CO 1.1C SANTA MONICA

CALIF MISSILE AND SPACE SYSTEMS DIV

SM-48410 STRESS ANALYSIS OF ENCAPSULATION MATERIALS FOR WELDED MODULES, AD-628 833

\*ELECTRONIC, SYSTEMS DIV L G HANSCOM FIELD MASS

ESD-TDR-64-630 LEAD ATTACHMENT AND ENCAPSULATION TECHNIQUES FOR THIN FILM MICROCIRCUITS, AD-611 752

\*GENERAL DYNAMICS/CONVAIR SAN DIEGO CALIF

GDC-BTD67-144

THERMAL ANALYSIS. ADVANCED
AUTOPILOT FLATPAK MODULE DESIGN
RECOMMENDATIONS.
(SAMSO-TR-71-86)
AD-722 405

\*GENERAL DYNAMICS/POMONA CALIF

CR-6-347-958-001
CORROSION
PREVENTION/DETERIORATION CONTROL IN
ELECTRONIC COMPONENTS AND
ASSEMBLIES.
AD-815 470

\*GENERAL ELECTRIC CO SYRACUSE N Y

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS AD-265 461

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS AD-265 857

\*GENERAL ELECTRIC CO UTICA N Y

\* \* \*

RESEARCH AND DEVELOPMENT OF
THERMOCOUPLE ENERGY CONVERTERS

0-2 UNCLASSIFIED AD-251 485

\*GENERAL MOTORS CORP KOKOMO IND DELCO ELECTRONICS DIV

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. (RADC-TR-71-8) . AD-722 043

\*GENERAL MOTORS CORP KOKOMO IND DELCO RADIO DIV

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. (RADC-TR-69-451)
AD-703 292

\*GGVERNMENT-INDUSTRY DATA EXCHANGE PROGRAM

GIDEP-515.00.00.00-F9-10 RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. AD-722 043

\*HARRY DIAMOND LABS WASHINGTON D C

TR-1308
LOW-LOSS STYRENE-TYPE FOAM-INPLACE ENCAPSULATING RESINS,
AD-628 537

\*INTERAGENCY DATA EXCHANGE PROGRAM

IDF9-501.32.19.45-56-01 The IMPROVEMENT OF ENCAPSULATING FOAMS AND QUALITY ASSURANCE OF POTTING PLASTIC. AD-646 915

IDEP-515.00.00.00-F9-01
FAILURE MECHANISMS IN PLASTIC
ENCAPSULATED MICROCARCUITS.
AD-689 224

\* \* \*

\* \* \*

IDEP-515.00.00.00-X9-10
MICRO-NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
AD-371 797

IDEP-515.00.00.00-X9-11
MICRO-HOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
AD-838 791

IDEP-515.00.00.00-X9-13
MICRO NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
AD-846 071

IDEP-742.00.00.00-F9-01 INVESTIGATION OF PLASTIC EFFECTS ON SEMICONDUCTOR RELIABILITY. AD-854 306

\*INTERAGENCY DATA EXCHANGE PROGRAM

IDEP-515.00.00.00-F9-07
• RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. AD-703 292

\* \* \*

\*ITT SEMICONDUCTOR PRODUCTS LABS PALO ALTO CALIF

FOUR-LAYER DIODE DEVELOPMENT PROGRAM. (RADC-TR-68-136) AD-669 850

\*JOHNS HOPKINS UNIV BALTIMORE MD

ANALOG COMPUTER RESEARCH INTO THE ENERGY-EXCHANGE BETWEEN GASES AND SOLIDS. (AFOSR-1001) AD-605 159

\*JOHNS HOPKINS UNIV SILVER SPRING MD APPLIED PHYSICS LAB

TG-817
THE IMPROVEMENT OF
ENCAPSULATING FOAMS AND QUALITY
ASSURANCE OF POTTING PLASTIC.
(IDEP-501.32.19.45-S6-01)
AD-646 915

0-3 UNCLASSIFIED \*LOCKHEED MISSILES AND SPACE CO SUNNYVALE CALIF

MRI267 01 VACUUM DE-GASSING OF ENCAPSULANTS, AD-412 282

SB 61 50
ENCAPSULATING, POTTING, AND
EMBEDDING MATERIALS FOR ELECTRONIC
COMPONENTS AND MODULES. AN
ANNOTATED BIBLIOGRAPHY
AD-265 866

SB62 433 80 62 28
INSPECTING AND TESTING OF
EMBEDDING MATERIALS AND COMPONENTS
OF ELECTRICAL MODULES BEFORE.
DURING AND AFTER ASSEMBLY: A
PARTIALLY ANNOTATED BIBLIOGRAPHY
AD-296 356

\*MCDONNELL AIRCRAFT CORP ST LOUIS MO

9354
ELECTRICAL POTTING COMPOUNDS SURFACE AND VOLUME RESISTIVITY AT
'ELEVATED TEMPERATURES FOR
PROTRACTED TIMES (PHASE 11:
ELECTRICAL TESTS)
AD-295 538

\*MITRE CORP BEDFORD MASS

W-6353 LEAD ATTACHMENT AND ENCAPSULATION TECHNIQUES FOR THIN FILM MICROCIRCUITS, (ESD-TDR-64-630) AD-611 752

\*MONSANTO RESEARCH CORP ST LOUIS MO

RHEOLOGY OF ROD-LIKE PARTICLES
IN VISCOUS MEDIA. PART I.
FORMATION OF COMPOSITES FROM SINGLE
FIBERS.
AD-849 285

\*MOTOROLA INC SCOTTSDALE ARIZ

4003
MINIATURE THIN FILM INDUCTORS
(MODIFICATION NO. 2).
AD-602 270

\*NATIONAL CASH REGISTER CO DAYTON OHIO CAPSULAR PRODUCTS RESEARCH AND DEVELOPMENT

DEVELOPMENT OF MULTIPURPOSE CAPSULAR ADHESIVE SYSTEMS. (PA-TR-4215) AD-730 908

\*NATIONAL CASH REGISTER CO - DAYTON OHIO CAPSULAR RESEARCH AND PRODUCT DEVELOPMENT DEPT

ENCAPSULATION OF VIRUSES. (AFWL-TR-64-167)
AD-620 933

MICROENCAPSULATED CLOUD SEEDING MATERIALS. (AFCRL-71-0151) AD-722 448

\*NATIONAL CASH REGISTER CO DAYTON OHIO

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL AD-265 894

1 STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL AD-265 895

A STUDY OF THE ENCAPSULATION OF HIGH ENERGY SUBSTANCES. AD-601 772

\*NAVAL AIR ENGINEERING CENTER
PHILADELPHIA PA ENGINEERING DEPT
(SI)

NAEC-ENG-7683
A STUDY IN TERMINAL BENDING OF UNIFORM AND ENCAPSULATED WIRE ROPE

0-4 UNCLASSIFIED WITH LINEAR AND NON-LINEAR CONSTITUTIVE EQUATIONS, AD-718 336

\*NAVAL AMMUNITION DEPOT CRANE IND

NAD-CR=MICRO-NOTES-24
MICRO-NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
.(IDEP-515.00.00.00-X9-10)
AD-671 797

NAD-CR-MICRO NOTES-25
MICRO-NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
(IDEP-515.00.00.00-X9-11)

\* \* \*

AD-838 791

NAD-CR-MICRO NOTES-27
MICRO NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
(IDEP-515.00.00.00-X9-13)
AD-846 071

NAD-CR-MICRO-NOTES-28
MICHO-NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
AD-690 445

NAD-CR-MICRO NOTES-30
MICRO-NOTES. INFORMATION ON
MICROELECTRONICS FOR NAVY
EQUIPMENTS.
AD-715 108

\*NAVAL BOILER AND TURBINE LAB PHILADELPHIA PA

EVALUATION OF HIGH TEMPERATURE INSTRUMENTATION FOR DYNAMIC ANALYSIS. ENCAPSULATED STRAIN GAGE INSTALLATION FOR USE IN STEAM ENVIRONMENT, AD-432 229

\*NAVAL ORDNANCE TEST STATION CHINA LAKE CALIF

TP 2597
EFFECT OF PROCESS VARIABLES ON THE DIMENSIONS AND QUALITY OF EXTRUSION-COATED PROPELLANT GRAINS (NAVWEPS-7604)
AD-255 962

\*NAVAL RESEARCH LAB WASHINGTON D C

NRL-MR-1481
ENCAPSULATION TECHNIQUES FOR
NRL IRRADIATION EFFECTS STUDIES.
AD-430 751

\*NAVY MARINE ENGINEERING LAB ANNAPOLIS MD :

MEL-421/65
EFFECT OF WATER ABSORPTION ON DIMENSIONAL STABILITY OF ELECTRIC MOTOR ENCAPSULATING MATERIALS.
AD-630 S66

\*PHILCO CORP LANSDALE PA

PEM FOR TRANSISTOR
MANUFACTURING PROCESS IMPROVEMENT.
AD-433 654

LOW COST INTEGRATED CIRCUIT TECHNIQUES. (ECOM-01424-2)
AD-631 491

LOW COST INTEGRATED CIRCUIT TECHNIQUES. (ECOM-01424-3) AD-635 183

PHILCO R-506
RESEARCH AND DEVELOPMENT LOW
COST INTEGRATED CIRCUIT TECHNIQUES.
AD-628 618

R 232 1
PEM FOR TRANSISTOR
MANUFACTURING PROCESS IMPROVEMENT
AD-286 907

\*PICATINNY ARSENAL DOVER N J

0-5 UNCLASSIFIED PIC-SPE

AMMUNITION ENGINEERING DIRECTORATE

AED-TM-1308
ENCAPSULATING PROPELLANTS BY
MEANS OF ULTRASONIC WELDING,
AD-427 412

\*PICATINNY ARSENAL DOVER N J

. PA-TR-4215
DEVELOPMENT OF MULTIPURPOSE
CAPSULAR ADHESIVE SYSTEMS.
AD-730 908

\*PLASTICS TECHNICAL EVALUATION CENTER DOVER N J

PLASTEC-29
ENCAPSULATION OF ELECTRONIC
PARTS IN PLASTICS: A REVIEW,
AD-648 420

\*RADIO CORP OF AMERICA SOMERVILLE N J

PRODUCTION ENGINEERING MEASURE ON 2N1708 SILICON PLANAR EPITAXIAL TRANSISTOR. VOLUME. I. AD-435.114

\*RADIO CORP OF AMERICA SOMERVILLE N J ELECTRONIC COMPONENTS AND DEVICES

TRANSISTOR, VHF, SILICON,
POWER, LINEAR, 30-MHZ, 100 WATTS
PEP.
(ECOM-01387-F)
AD-804 551

\*ROME AIR DEVELOPMENT CENTER GRIFFISS AFB N Y

RADC-TR-65-291
RELIABILITY ANALYSIS OF X-BAND
TUNNEL DIODES.
AD-625 956

RADC-TR-68-136
FOUR-LAYER DIODE DEVELOPMENT
PROGRAM.
AD-669 850

RADC-TR-69-82
INVESTIGATION OF PLASTIC
EFFECTS ON SEMICONDUCTOR
RELIABILITY.
AD-854 306

RADC-TR-69-111
FAILURE MECHANISMS IN PLASTIC ENCAPSULATED MICROCIRCUITS.
(IDEP-515.00.00.00-F9-01)
AD-689 224

RADC-TR-69-451
RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.
AD-703 292

RADC-TR-70-213
STRESS INDUCED INTERMITTENT
FAILURES IN ENCAPSULATED
MICROCIRCUITS.
AD-715 984

RADC-TR-71-8
RELIABILITY EVALUATION OF
PLASTIC INTEGRATED CIRCUITS.
AD-722 043

\*SOUTHWEST RESEARCH INST. SAN ANTONIO TEX

PREPARATION OF CAPSULES. AD-729 691

TDR62 53 ENCAPSULATION OF FOODS (6570 AMRL-TDR62 53) AD-284 005

\*SPACE AND MISSILE SYSTEMS ORGANIZATION LOS ANGELES AIR FORCE STATION CALIF

SAMSO-TR-71-86
THERMAL ANALYSIS. ADVANCED
AUTOPILOT FLATPAK MODULE DESIGN
RECOMMENDATIONS.
AD-722 405

\*SPEER CARBON CO NIAGARA FALLS N Y

0~6 UNCLASSIFIED

R-140 RESISTORS FOR HICROPOWER CIRCUITS. (ECOM-01524-4) AD-489 906

SCC-24 RESISTORS FOR MICROPOWER CIRCUITS. (ECOM-01524-4) AD-489 906

\*STANFORD RESEARCH INST MENLO PARK CALIF

ENCAPSULATED AEROSOLS AD-255 010

ENCAPSULATED AEROSOLS AD-260 926

ENCAPSULATED AEROSOLS AD-265 314

ENCAPSULATED AEROSOLS AD-283 325

MICROENCAPSULATION. AD-823 785

RESEARCH STUDIES ON THE DISSEMINATION OF SOLID AND LIQUID AGENTS. AD-827 272

\*SYLVANIA ELECTRIC PRODUCTS, INC WOBURN MASS SEMI-CONDUCTOR DIV

RELIABILITY ANALYSIS OF X-BAND TUNNEL DIODES. (RADC-TR-65-291) AD-625 956

\*SYLVANIA ELECTRONIC SYSTEMS-WEST MOUNTAIN VIEW CALIF ELECTRONIC DEFENSE LABS

EDL G220 NONCOMMUNICATIONS EXPENDABLE JAMMER INVESTIGATIONS. VOLUME 3. MECHANICAL DEVELOPMENT.

AD-443 097

VOL. 3 NONCOMMUNICATIONS EXPENDABLE JAMMER INVESTIGATIONS. VOLUME 3. MECHANICAL DEVELOPMENT, AD-443 097

\*SYNTHETIC MICA CO WEST CALDWELL N J

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-258' 395

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-265 499

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-266 161

\*TEXAS INSTRUMENTS INC DALLAS

03 64 43 PRODUCTION ENGINEER: NG MEASURES TO INCREASE TRANSISTOR RELIABILITY FOR THE 2N656. AD-602 939

\*TRW SEMICONDUCTORS INC LAWNDALE CALIF

PRODUCTION ENGINEERING MEASURE RELIABILITY THRU PROCESS IMPROVEMENT AD-294 110

\*TRW SPACE TECHNOLOGY LABS LOS ANGELES CALIF

STL/TR-59-0000-09931 LOW PRESSURE ELECTRICAL DISCHARGE STUDIES: AD-605 984

0-7 UNCLASSIFIED

WES-WES

\*WESTERN ELECTRIC CO INC NEW YORK

MICROWAVE DIODE RESEARCH. (ECOM-01445%F) AD-821 915

MICROWAVÉ DIODE RESEARCH. (ECOM-01445-4) AD-822 016

\*WESTERN ELECTRIC CO INC WINSTON-SALEM N C

INDUSTRIAL PRÉPAREDNESS STUDY. LACQUER FILM CAPACITORS AD-257 829

\*WESTINGHOUSE ELECTRIC CORP WASHINGTON D C

HIGH CURRENT AND HIGH VOLTAGE SILICON CONTROLLED RECTIFIERS AD-289 291

> 0-8 UNCLASSIFIED

#### SUBJECT INDEX

◆ADHESIVES306

PLASTICS

DEVELOPMENT OF MULTIPURPOSE

CAPSULAR ADHESIVE SYSTEMS. ◆

AD=730 908

•AEROSOLS

ENCAPSULATED AEROSOLS•

AD-255 010

ENCAPSULATED AEROSOLS•

AD-260 926

ENCAPSULATED AEROSOLS•

AD-265 714

METHODS OF AEROSOL ENCAPSULATION INCLUDED PREENCAPSULATION, COLLECTION, THEN REDISPERSION; ENCAPSULATION BY CONDUNSATION AND VARIOUS COAGULATION HETHODS•

AD-287 725

## \*AHIDES

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL•

•ARTIFICIAL PRECIPITATION ,

MATERIALS .

MICROENCAPSULATED CLOUD SEEDING

HATERIALS.•

LD-722 448

AUTOMATIC PILOTS
MODULES(ELECTRONICS)
 THERMAL ANALYSIS. ADVANCED
AUTOPILOT FLATPAK MODULE DESIGN
RECOMMENDATIONS, •
AD-722 405

•AVALANCHE DIODES
HICROWAVE OSCILLATORS
HICROWAVE DIODE RESEARCH.•
AD-821 915
HICROWAVE DIODE RESEARCH.•
AD-822 016

BACTERIOPHAGES
 ENCAPSULATION
 ENCAPSULATION OF VIRUSES.
 AD-620 922

.BIBLIUGRAPHIES

ENCAPSULATING, POTTING, AND
EMBEDDING MATERIALS FOR ELECTRONIC
COMPONENTS AND MODULES. AN
ANNOTATED BIBLIOGRAPHY.
AD-265 866
CRYSTAL GROWTH AND
CRYSTALLOGRAPHY. A LITERATURE
SURVEY.
AD-274 642

PACKAGED CIRCUITS

PACKAGED CIRCUITS. VOLUME 1.\*

AD-704 925

•BOILERS
INSTRUMENTATION
ENCAPSULATED STRAIN GAGE
INSTALLATION FOR USE IN STEAM
ENVIRONMENT•
AD-432 229

CABLES(HECHANICAL)
BENDING
 A STUDY IN TERMINAL BENDING OF
UNIFORM AND ENCAPSULATED WIRE ROPE
WITH LINEAR AND NON-LINEAR
CONSTITUTIVE EQUATIONS;
AD-718 326

•CAPACITORS
• INDUSTRIAL PREPAREDNESS STUDY•
LACQUER FILM CAPACITORS•
AD-257 829

• CHEHICAL WARFARE AGENTS ENCAPSULATED AEROSOLS • AC = 255 010

DISSEMINATION
RESEARCH STUDIES ON THE
DISSEMINATION OF SOLID AND LIQUID
AGENTS. •
AD-827 272

ENCAPSULATION
HICROENCAPSULATION. •
AD-829 789

•COATINGS

ENCAPSULATED AEROSOLS•

AD-255 010

D-1 UNCLASSIFIED EFFECT OF PROCESS VARIABLES ON THE DIMENSIONS AND QUALITY OF EXTRUSION-COATED PROPELLANT GRAINS. AD-255 962

METHODS OF AEROSOL ENCAPSULATION INCLUDED PREENCAPSULATION, COLLECTION, THEN REDISPERSION; ENCAPSULATION BY CONDENSATION AND VARIOUS COAGULATION. METHODS. AD-287 325

•COHPOSITE MATERIALS

MANUFACTURING METHODS

RHEOLOGY OF ROD-LIKE PARTICLES

IN VISCOUS MEDIA. PART I.

FORMATION OF COMPOSITES FROM SINGLE

FIBERS...

AD-849 285

• CONTAINERS

ENCAPSULATING HATERIALS FOR

PACKAGING FOOD FOR SPACE FLIGHTS.

• HATERIALS INCLUDE MOISTURE

BARRIERS AND FILM FORHERS.

AD-284 005

DESIGN
TECHNIQUES AND DESIGN PHILOSOPHY
FOR ENCAPSULATION OF TEST SPECIMENS
FOR STUDIES OF RADIATION DAMAGE OF
STEEL. (NUCLEAR REACTOR STRUCTURAL
MATERIAL).
AD-430 751

•CORROSION INHIBITION
ELECTRONIC EQUIPHENT
COPROSION
PREVENTION/DETERIORATION CONTROL IN
ELECTRONIC COMPONENTS AND
ASSEMBLIES.•
AD-815 470

•CORUNDUM CRYSTAL GROWTH AND CRYSTALLOGRAPHY• A LITERATURE SURVEY• AD-274 642

•CRYSTALS

CRYSTAL GROWTH AND

CRYSTALLOGRAPHY• A LITERATURE

SURVEY•

AD-274 642

 C5 AGENTS , ENCAPSULATION MICROENCAPSULATION . •
 AD-823 785

ODIELECTRICS

DEVELOPMENT OF ULTRA HIGH
TEMPERATURE DIELECTRIC MATERIALS
FOR EMBEDDING AND ENCAPSULATING
ELECTRONIC COMPONENTS
AD-265 499

 Prodes
 ENGINEERING SERVICES ON TRANSISTORS
 AD-261 938

•DIODES(SEMICONDUCTOR)

HANUFACTURING METHODS

FOUR-LAYER DIODE DEVELOPMENT

PROGRAM.•

AD-669 850

DISSEMINATION
 CHEHICAL WARFARE AGENTS
 MICROENCAPSULATION.
 AD-822 785

•DROPS

A STUDY OF THE ENCAPSULATION

APPLICABLE TO LIQUID ROCKET FUEL•

AD=265 894

• ELECTRIC CONNECTORS
INTEGRATED CIRCUITS
RESEARCH AND DEVELOPMENT LOW
COST INTEGRATED CIRCUIT TECHNIQUES.
AD-628 618

•ELECTRIC DISCHARGES
HIGH ALTITUDE
LOW-PRESSURE ELECTRICAL
DISCHARGE STUDIES WITH REFERENCE TO

D-2 UNCLASSIFIED

ELECTRICAL BREAKDONN OF GUIDED HISSILE COMPONENTS AT THEY ALTITUDES. AD-605 984

•ELECTRIC MOTORS ENCAPSULATION EFFECT OF WATER ABSORPTION ON DIMENSIONAL STABILITY OF ELECTRIC HOTOR ENCAPSULATING MATERIALS. AD-670 566

. ELECTRIC POWER PRODUCTION OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS. AD-265 461 OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS. AD-265 857

.ELECTRUNIC EQUIPMENT DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS. AD-265 499 POTTING COMPOUNDS FOR ELECTRONIC CIRCUITS; SURFACE AND VOLUME RESISTIVITY AT ELEVATED TEMPERATURE FOR PROTRACTED PERIODS OF TIME. AD-295 538

CORROSION INHIBITION CORROSION PREVENTION/DETERIORATION CONTROL IN ELECTRONIC COMPONENTS AND ASSEMBLIES. . AD-815 470

ENCAPSULATION ENCAPSULATION OF ELECTRONIC PARTS IN PLASTICS: A REVIEW, . AD=648 420

· ELECTRONIC SWITCHES DIODES(SEHICONDUCTOR) FOUR-LAYER DIODE DEVELOPMENT PROGRAM. AD-669 850

• EMBEDDING SUBSTANCES

ENCAPSULATING RESINS AND POTTING COMPOUNDS. AD-096 112 DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS. AD-258 395 DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC HATERIALS FOR EMBEDDING AND EMCAPSULATING ELECTRONIC COMPONENTS. AD-265 499 ENCAPSULATING, POTTING, AND EMBEDDING MATERIALS FOR LLECTRONIC COMPONENTS AND MODULES. AN ANNOTATED BIBLIOGRAPHY. AD-265 866 DEVELOPHENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS. AD-266 161 POTTING COMPOUNDS FOR ELECTRONIC CIRCUITS: SURFACE AND VOLUME RESISTIVITY AT ELEVATED TEMPERATURE FOR PROTRACTED PERIODS OF TIME. AU-295 538 BIBLIGGRAPHY ON INSPECTION AND BEFORE, DURING, AND AFTER

TESTING OF EMBEDDING A TERIALS AND COMPONENTS OF ELECTRONICS HODULES ASSEMBLY. AD-296 356

CHEMICAL CONTAMINATION INVESTIGATION OF PLASTIC EFFECTS ON SEMICONDUCTOR RELIABILITY.. AD-854 306

TEST EQUIPMENT (ELECTRONICS) 1.5-KW SOLID-STATE PONER CYCLER. . AD-726 018

TEST HETHODS THE IMPROVEMENT OF ENCAPSULATING FOAMS AND QUALITY ASSURANCE OF POTTING PLASTIC.. AD-646 915

D-3 UNCLASSIFIED • ENCAPSULATION RESEARCH AND DEVELOPHENT OF THERHOCOUPLE ENERGY CONVERTERS. AD-251 485 ENCAPSULATED AEROSOLS. AD-255 010 EFFECT OF PROCESS VARIABLES ON THE DIHENSIONS AND QUALITY OF EXTRUSION-COATED PROPELLANT GRAINS. AD-255 962 DEVELOPHENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPCHENTS. AD-258 395 ENCAPSULATED AEROSOLS\* AD-260 926 ENCAPSULATED AEROSOLS. AD-265 314

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS+ AD-265 499

ENCAPSULATING, POTTING, AND
EMBEDDING LATERIALS FOR ELECTRONIC
COMPONENTS AND MODULES. AN
ANNOTATED BIBLIOGRAPHY.
AD-265 866

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL AD-265 894

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL+ AD-265 895

DEVELOPHENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS. AD-266 161

HETHODS OF AEROSOL ENCAPSULATION INCLUDED PREENCAPSULATION. COLLECTION, THEN REDISPERSION; ENCAPSULATION BY CONDENSATION AND VARIOUS COAGULATION METHODS. AD-287 325

ENCAPSULATING MATERIALS FOR
PACKAGING FOOD FOR SPACE FLIGHTS.
MATERIALS INCLUDE MOISTURE
BARRIERS AND FILM FORMERS.
AD-284 005

POTTING COMPOUNDS FOR ELECTRONIC CIRCUITS; SURFACE AND VOLUME RESISTIVITY AT ELEVATED TEMPERATURE FOR PROTRACTED PERIODS OF TIME.

AD-295 538

BIBLIOGRAPHY ON INSPECTION AND TESTING OF EMBEDDING MATERIALS AND COMPONENTS OF ELECTRONICS MODULES BEFORE, DURING, AND AFTER ASSEMBLY.

AD-296 356

BACTERIOPHAGES
ENCAPSULATION OF VIRUSES
AD-620 933

CHEMICAL WARFARE AGENTS
MICROENCAPSULATION..
AD-823 785

EPOXY PLASTICS
. EFFECT OF WATER ABSORPTION ON DIMENSIONAL STABILITY OF ELECTRIC HOTOR ENCAPSULATING MATERIALS. • AD-630 566

EXPANDED PLASTICS
THE IMPROVEMENT OF ENCAPSULATING FOAMS AND QUALITY ASSURANCE OF POTTING PLASTIC...
AD-646 915

INTEGRATED CIRCUITS

RESEARCH AND DEVFLORMENT LOW

COST INTEGRATED CIRCUIT TECHNIQUES.

AD-628 618

LOW COST INTEGRATED CIRCUIT

TECHNIQUES.

AD-631 491

LOW COST INTEGRATED CIRCUIT

TECHNIQUES.

AD-635 183

RELIABILITY EVALUATION OF

PLASTIC INTEGRATED CIRCUITS.

AD-703 292

RELIABILITY EVALUATION OF

LIQUID ROCKET PROPELLANTS ENCAPSULATION OF LIQUID ROCKET

PLASTIC INTEGRATED CIRCUITS. .

AD-722 043

0-4 UNCLASSIFIED PROPELLANTS. AD-601 772

MANUFACTURING METHODS VACUUM DE-GASSING OF ENCAPSULANTS. AD-412 282

MATERIALS
- ENCAPSULATION MATERIALS FOR
WELDED ELECTHONIC MODULES: STRESS
ANALYSIS.
AD-628 837

MODULES (ELECTRONICS)
THERMAL ANALYSIS. ADVANCED
AUTOPILOT FLATPAK HODULE DESIGN
RECOMMENDATIONS.
AD-722 405

PACKAGED CIRCUITS

LEAD ATTACHMENT AND

ENCAPSULATION TECHNIQUES FOR THIN

FILM MICROCIRCUITS.

AD-611 752

PLASTICS
ENCAPSULATION OF ELECTRONIC
PARTS IN PLASTICS: A REVIEW, •
AD-648 420

REVIEWS
PREPARATION OF CAPSULES. • AD-729 691

SEMICONDUCTOR DEVICES

HICRO-NOTES. INFORMATION ON HICROELECTRONICS FOR NAVY
EQUIPMENTS...

AD-838 791

HICRO NOTES. INFORMATION ON HICROELECTRONICS FOR NAVY
EQUIPMENTS...

AD-846 071

SODIUM CHLORIDE
HICROENCAPSULATED CLOUD SEEDING
HATERIALS...
AD-722 448

STYRENE PLASTICS

LOW-LOSS STYRENE-TYPE FOAH-IN-PLACE ENCAPSULATING RESINS. AD-628 537

• ENERGY
TRANSPORT ROPERTIES

ANALOG COMPUTER RESEARCH INTO
THE ENERGY-FXCHANGE BETWEEN GASES
AND SOLIUS.
AD-605 159

•EPOXY PLASTICS
ENCAP-ULATION

EFFECT OF WATER ABSORPTION ON
DIHENSIONAL STABILITY OF ELECTRIC
HOTOR ENCAPSULATING HATERIALS.
AD-630 566

◆ETHYL CELLULOSE

A STUDY OF THE ENCAPSULATION

APPLICABLE TO LIQUID ROCKET FUEL◆

AD=265 895

COATINGS
HIGROENCAPSULATED CLOUD SEEDING
HATERIALS...
AD-722 448

◆EXPANDED PLASTICS
ENCAPSULATION
. LOW-LOSS STYRENE-TYPE FOAM-INPLACE ENCAPSULATING RESINS.
AD-628 537
THE IMPROVEMENT OF ENCAPSULATING
FOAMS AND QUALITY ASSURANCE OF
POTTING PLASTIC...
AD-646 915

EXTRUSION

EFFECT OF PROCESS VARIABLES ON
THE DIMENSIONS AND QUALITY OF
EXTRUSION-COATED PROPELLANT GRAIMS®
AD-255 962

+FILHS
A STUDY OF

A STUDY OF THE ENCAPSU ATION APPLICABLE TO LIQUID ROCK T FUEL.

AD-265 894

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL.

AD-265 895

D=5 UNCLASSIFIED •F00D

ENCAPSULATING MATERIALS FOR
PACKAGING FOOD FOR SPACE FLIGHTS.
HATERIALS INCLUDE MOISTURE
BARRIERS AND FILM FORMERS.
AD-284 005

STORAGE DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY HIXES...

EGARNET

CRYSTAL GROWTH AND CRYSTALLOGRAPHY. A LITERATURE SURVEY. AD-274 642

AGASES

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL. AD-265 695

•GENERATORS
OPTIMIZATION OF THERHOELECTRIC
ENERGY CONVERTERS•
AD-265 461

OHYDRAZINES-

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL. AD-265 894

•INSULATING HATERIALS

ENCAPSULATING, POTTING, AND
EHBEDDING HATERIALS FOR ELECTRONIC
COMPONENTS AND MODULES. AN
ANNOTATED BIBLIOGRAPHY.
AD-265 866

•INTEGRATED CIRCUITS ENCAPSULATION RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. AD-722 043

FAILURENTLECTRONICS)
STRESS INDUCED INTERMATTENT
FAILURES IN ENCAPSULATED
HICKOCIRCUITS...
AD-715 984

MANUFACTURING METHODS

RESEARCH AND DEVELOPMENT LOW

COST INTEGRATED CIRCUIT TECHNIQUES.

AD-628 618

LOW COST INTEGRATED CIRCUIT

TECHNIQUES.

AD-621 491

LOW COST INTEGRATED CIRCUIT

TECHNIQUES.

AD-625 182

NAVAL RESEARCH
HICRO-NOTES. INFORMATION ON
HICROELECTRONICS FOR NAVY
EQUIPMENTS...
AD-490 445

RELIABILITY (ELECTRONICS)

FAILURE MECHANISMS IN PLASTIC ENCAPSULATED MICROCIRGUITS. •

AD-689 224

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. •

AD-709 292

TESTS

MICRO-NOTES. INFORMATION ON

MICROELECTRONICS FOR NAVY

EQUIPMENTS:

AD-671 797

LIQUID ROCKET PROPELLANTS

 A STUDY OF THE ENCAPSULATION
 APPLICABLE TO LIQUID ROCKET FUEL

D-6 UNCLASSIFIED AD-265 894

ENCAPSULATION
ENCAPSULATION OF LIQUID ROCKET
PROPELLANTS.
AD-601 772

##ANUFACTURING HETHODS

PRODUCTION ENGINEERING HEASURE

TO INCREASE THE RELIABILITY

FOR THE JET ETCH TRANSISTOR TYPE

2NSOIA, HAXINUM OPERATURG

FAILURE RATE OF 0.01%/1000 HR AT A

90% CONFIDENCE LEVEL AT 25 C.

AD-234 907

PRODUCTION ENGINEERING HEASURE

RELIABILITY THRU PROCESS

IMPROVEHENT.

TRANSISTORS

PRODUCTION ENGINEERING HEASURE

FOR THE INFROVEMENT OF GERHANIUM

ALLOY POWER TRANSISTORS.

AD-604 196

●HETHYL HYDRAZINES

A STUDY OF THE ENCAPSULATION

APPLICABLE TO LIQUID ROCKET FUEL● •

AD=265 894

.HICA

AD-266 161

DEVEROPHENT OF ULTRA HIGH
TEMPERATURE DIELECTRIC HATERIALS
FOR EMBEDDING AND ENCAPSULATING
ELECTRONIC COMPONENTS

DEVELOPMENT OF ULTRA HIGH
TEMPERATURE DIELECTRIC HATERIALS
FOR EMBEDDING AND ENCAPSULATING
ELECTRONIC COMPONENTS

AD-265 499

QEVELOPMENT OF ULTRA HIGH
TEMPERATURE DIELECTRIC HATERIALS
FOR EMBEDDING AND ENCAPSULATING
ELECTRONIC COMPONENTS

•MICROMINIATURIZATION (ELECTRONICS)
ELECTRIC CONNECTORS
LEAD ATTACHMENT AND

ENCAPSULATION TECHNIQUES FOR THIN FILM HICROCIRCUITS.

AD-6 11 752

• HICROMINIATURIZATION (ELECTRONICS) NAVAL EQUIPMENT MICRO-NOTES. INFORMATION ON HICROELECTRONICS FOR NAVY EQUIPMENTS. . AD-671 797 MICRO-NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPHENTS. . AD-690 445 MICRO-NOTES. INFORMATION ON HICROCLECTRONICS FOR NAVY EQUIPHENTS. . AD-715 108 MICRO-NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPMENTS. . AD-838 791 HICRO NOTES. INFORMATION ON HICROÈLECTRONICS FOR NAVY EQUIPHENTS. . AD-846 071

•HICROWAVE OSCILLATORS

AVALANCHE DIODES

HICROWAVE DIODE RESEARCH.

AD=821 715

HICROWAVE DIODE RESEARCH.

AD=822 016

•HINIATURE ELECTRONIC EQUIPHENT (COILS HINIATURE THIN FILH INDUCTORS• AD-602 270

•MODULES (ELECTRONIC)
DEGASIFI CATION
VACUUM DE-GASSING OF
ENCAPSULANTS:
AD-412 282

OHODULES(ELECTRONICS)
THERHAL ANALYSIS
THERHAL ANALYSIS. ADVANCED
AUTOPILOT FLATPAK HODULE DESIGN
RECOMMENDATIONS.
AD-722 405

D-7 UNCLASSIFIED AUD-GUA

●MODULES(ELECTRONIC)

ENCAPSULATION

ENCAPSULATION HATERIALS FOR

WELDED ELECTRONIC HODULES: STRESS

ANALYSIS:

AD=426 8⊅3

**●NAVAL** EQUIPHENT MIC/OMINIATURIZATION(ELECTRONICS) HICRO-NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPHENTS. . AD-671 797 HICROSNOTES. INFORMATION ON MICROSLECTRONICS FOR HAVY EQUIPHENTS . . AD-690 445 HICRO-NOTES. INFORMATION ON HICROELECTRONICS FOR NAVY EQUIPMENTS. . AD-838 791 HICRO NOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPHENTS.. AD-846 071

entrocellulose

A \$7007 OF THE FREETILETIE

APPLICABLE TO LIQUID ROCKET FUEL.

PASSAGED CIRCUITS

BIBLIOGRAPHIES

PACKAGED CIRCUITS VOLUME 1.0

AD-704 925

HANUPACTURING HETHODS
LEAD ATTACHMENT AND
ENCAPSULATION TECHNIQUES FOR THIN
FILM MICROCIRCUITSAD-611 752

◆PACKAGING TEST EQUIPMENT/ELECTRONICS) ENCAPSULATION MATERIALS FOR WELDED ELECTRONIC MODULES: STRESS ANALYSIS• AD-628 833

•PLASTIC COATINGS

EFFECT OF PROCESS VARIABLES ON

THE DIMENSIONS AND QUALITY OF EXTRUSION-COATED PROPELLANT GRAINS. AC-25\$ 962.

 PLASTICS
 ENCAPSULATING 'REGINS AND POTTING COMPOUNDS -AD-096 112

COMPATIBILITY
ENCARSULATION OF LIQUID ROCKET
PROPELLANTS.
AD-601 772

POLYHERS
 A STUDY OF THE ENCAPSULATION
 APPLICABLE TO LIQUID ROCKET FUEL
 AD-265 895

●POWER

DEVELOPMENT OF A HIGH CURRENT.

HIGH VOLTAGE SILICON CONTROLLED

RECTIFIER.

AD-289 291

\*\*POWER AMPLIFIERS
SILICON
TRANSISTOR, VHF, SILICUL LUDGE
LINEAR, JOHHHZ, 100 WATTS PEP.\*
AD-804 551

•POWER SUPPLIES

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS•

AD-265 887

PROPELLANT GRAINS
 EFFECT OF PROCESS VARIABLES ON
 THE DIMENSIONS AND SUALITY OF
 EXTRUSION-COATED PROPELLANT GRAINS •
 AD-255 962

PROPELLANT TANKS
WELDING
ULTRASONIC WELDING APPLICATION
FOR HEAMETICALLY SEALING PROPELLANT
CONTAINERS.
AD=427 412

OQUALITY CONTROL TRANSISTORS

D-8 UNCLASSIFIED Reproduced from bost available copy.

PRODUCTION ENGINEERING HEASURES TO INCREASE TRANSISTOR RELIABILITY FOR THE 2N656. AD-602 929

•RADIO JAMHING LANDING SHPACT NONCOMMUNICATIONS EXPENDABLE JAMMER INVESTIGATIONS. VOLUME 2. MECHANICAL DEVELOPMENT, . AD-443 097

\*RECTIFIERS DEVELOPHENT OF A HIGH CURRENT. VOLTAGE SILICON CONTROLLED RECTIFIER. AD-289 291

\*RELIABILITY (ELECTRONICS) CORROSION INHIBITION CORROSION. PREVENTION/DETERIORATION CONTROL IN ELECTRONIC COMPONENTS AND ASSEMBLIES. . AD-815 470

•RESISTORS DESIGN RESISTORS FOR HICROPOWER CIRCUITS.. AD-489 906

ORUBY

CRYSTA, GRUNTH AND CRYSTALLOGRAPHY. A LÍTERATURE SURVEY. AD-274 642

.SEDINENTARY ROCK STRUCTURAL PROPERTIES THE EFFECT OF FLUIDS AND CYCLIC LOADING ON THE FLASTIC CONSTANTS OF ROCKS.. AD-729 680

.SENICONDUCTOR DEVICES ENCAPSULATION HICRO-MOTES. INFORMATION ON MICROELECTRONICS FOR NAVY EQUIPMENTS.. AD-838 791

HICRO NOTES. INFORMATION : HICROELECTRONICS FOR NAVY EQUIPHENTS. . AD-846 071

. SEMIPERHEABILITY A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUIT ROCKET LEL. AD-265 895 .

•SILICON POWER AMPLIFIERS TRANSISTOR, VHF, SILICON, POWER LINEAR, 30-HHZ, 100 WATTS EP. . AD-604 551

◆SODIUM CHLORIDE ENCAPSULATION HICROENCAPSULATED CLOUD SEEDING HATERIALS. AD-722 448

\*SPECIFICATIONS PROCESSING PEH FOR TRANSISTOR HANGFACTURING PROCESS IMPROVEHENTS AD-433 654

**OSPINELS** CRYSTAL GROWTH AND CRYSTALLOGRAPHY. A LISTCRATURE SURVEYS AD-274 642

.STEEL RADIATION DAMAGE TECHNIQUES AND DESIGN PHILOSOPHY FOR ENCAPSULATION OF TEST SPECIMENS FOR STUDIES OF RADIATION DAMAGE OF STEEL. INUCLEAR REACTOR STRUCTURAL MATERIALI. AD-430 751

STRASH GAGES STEAH ENCAPSULATED STRAIN GAGE INSTALLATION FOR USF IN STEAM ENVIRONMENT. AD-432 229

STYRENE PLASTICS

0-9 UNCLASSIFIED ENCAPSULATION.
LOW-LOSS STYRENE-TYPE FOAH-INPLACE ENCAPSULATING RESINS.
AD-628 \$37.

etest equiphent (electronics)
Enbedding substances
1.5-km solid=state power
Cycler...

•THERHAL CONDUCTIVITY

OPTIMITATION OF THERMOELECTRIC

ENERGY CONVERTERS•

AD=265 441

#THERHÖCOUPLES.

RÉSEARCH ANDIBEVELOPHENT OF

THERHOCOUPLE ENERGY CONVERTERS\*

AD=251 485

•THERHOELECTRICITY

OPTIMIZATION OF THERHOELECTRIC
ÈNERGY CONVERTERS•

AD-245 461

OPTIMIZATION OF THERHOELECTRIS;
ENERGY CONVERTERS•
;AU-265 857

\*\*\*OTRANSISTOR AMPLIFIERS ENGINEERING SERVICES ON TRANSISTORS\*\* AD-241 938

•TRANSISTORS ENGINEERING SERVICES ON TRANSISTORS. AD-261 926 PRODUCTION ENGINEERING HEASURE TO INCREASE THE RELIABILITY FOR THE UET ET 2NSOLA KAXIHUM ETCH TRANSISTOR TYPE 2NSDIA MAXIMUM OPERATING FAILURE RATE OF 0.019/1000 HR AT A 90% CONFIDENCE LEVEL AT 25 C. AD-286 907 PRODUCTION ENGINEERING MEASURE RELIABILITY THRU PROCESS IMPROVEMENT . AD-294 110

ENCAPSULATION

PRELIMINARY INVESTIGATION OF PLASTIC ENCAPSULATED TRANSISTORS...
AD-640 349
1.5-KW SOLID-STATE POWER
CYCLER...
AD-726 018

EPITAXIAL GROWTH.
PRODUCTION ENGINEERING HEASURE
ON 2N17OB SILICON PLANAR EPITAXIAL
TRANSISTOR. VOLUME 1...
AD~425 114.

GERHANIUH
PRODUCTION ENGINEERING HEASURE
FOR THE IMPROVEMENT OF GERMANIUH
ALLOY FOWER TRANSISTORS.
AD-684-196

HANUFACTURING HETHODS
PEM FOR TRANSISTOR HANUFACTURING
PROCESS IMPROVENENT.
AD-422.654

RELIABILITY (ELECTRONICS)

PRODUCTION ENGINFERING HEASURES

TO INCREASE TRANSISTOR RELIABILITY

FOR THE 2NAME;

AD-402 929

RELIABILITY (ELECTRONICS):

INV/STIGATION OF PLASTIC EFFECTS
ON SEMICONDUCTOR BELIABILITY.
AD-854 206

VERY HIGH FREQUENCY TRANSISTOR, VHF, SILICON, POWER, LINEAR, 20-MHZ, 100 WATTS PEP. • AD-804 551

TRANSPORT PROPERTIES
THERMOSYNAMICS
ANALOG COMPUTER RESEARCH INTO
THE ENERGY-EXCHANGE BETWEEN GASES
AND SOLIDS.
AD-605 159

TUNNEL DIODES RECIACILITY (ELECTRONICS) RELIABILITY ANALYSIS OF X-BAND TUNNEL DIODES.

D-10 UNCLASSIFIED AD-625 956

OULTRASONIC RADIATION
WELDING
ULTRASONIC WELDING APPLICATION
FOR HERHETICALLY SEALING PROPELLANT
CONTAINERS.
AD-427 412

OUREA

ENCAPSULATION

HICROENCAPSULATED CLOUD SEEDING.

HATERIALS...
AD-722 448

•VAPORS

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL. AD-265 895

•VERY HIGH FREQUENCY
TRANSISTORS
TRANSISTOR, VHF. SILICON. POWER,
LINEAR, 20-HHZ, 100 WATTS PEP.•
AD-804 551

•VIRUSES
-ENCAPSULATION
-ENCAPSULATION OF VIRUSES•
-AD-620 999

OWELDING

PROPELLANT TANKS

ULTRASONIC WELDING APPLICATION

FOR HERMETICALLY SEALING PROPELLANT

CONTAINERS.

AD-427 412

D-11 UNCLASSIFIED

## TITLE INDEX

ANALOG COMPUTER AD-605 159	EFFECT OF PROCESS AD-235 962
RESEARCH INTO THE EMERGY-EXCHANGE	VARIABLES ON THE DIMENSIONS AND
BETHEEN GASES AND SOLIDS (U)	WUALITY OF EXTRUSION-COATED
TRANSPORT PROPERTIES	PROPELLANT GRAINS(U)
	• COATINGS
CORROSION PREVENTION/DET AD-815 470	and the second s
ERIGRATION CONTROL IN ELECTRONIC	EFFECT OF WATER AD-630 566
COMPONENTS AND ASSEMBLIES. (U)	ABSORPTION ON DIMENSIONAL STABILITY
ELECTRONIC EQUIPMENT	OF ELECTRIC HOTOR ENCAPSULATING
	MATERIALS.(U)
CRYSTAL GROWTH AND AD-274 642	+EPOXY PLASTICS
CRYSTALLOGRAPHY. A LITERATURE	
SURVEY(U)	ELECTRICAL POTTING AD-295 578
•BIBLIGGRAPHIES	COMPOUNDS - SURFACE AND VOLUME
	RESISTIVITY AT ELEVATED
DEVELOPMENT OF A STABLE AD-727 480	TEMPERATURES FOR PROTRACTED TIMES
LEAVENING SYSTEM FOR BAKERY	(PHASE 11: ELECTRICAL TESTS) (U)
MIXES.(U)	• ELECTRONIC EQUIPMENT
•F00D	
	ENCAPSULATED AD-295 010
DEVELOPMENT OF AD-770 908	AEROSOLS(U)
HULTIPURPOSE CAPSULAR ADHESIVE	• AEROSOLS
SYSTEMS.(U)	
*ADHESTVLS	ENCAPSULATED AD-260 926
	AFROSOLSCUI
DEVELOPMENT OF ULTRA AD-258 395	• AEROSOLS
HIGH TEMPERATURE DIELECTRIC	40.04.04.04.04.04.04.04.04.04.04.04.04.0
MATERIALS FOR EMBEDDING AND	ENCAPSULATED AD-265 314
ENCAPSULATING ELECTRONIC	AEROSOLS(U)
COMPONENTS (U)	• AEROSOLS
PERSENTING SUBSTANCES	
	ENCAPSULATED AD-287 725
DEVELOPMENT OF ULTRA AD-265 499	AEROSOLS (U)
HIGH TEMPERATURE DIELECTRIC	• AEROSOLS
MATERIALS FOR EMBEDDING AND	
ENCAPSULATING ELECTRONIC	ENCAPSULATING, POTTING, AD-265 866
COMPONENTS (U)	AND EMBEDDING MATERIALS FOR
•DIELECTRICS	ELECTRONIC COMPONENTS AND MODULES.
	AN ANNOTATED BIBLIOGRAPHY(U)
DEVELOPMENT OF ULTRA AD-266 161	•BIBLIOGRAPHIES
HIGH TEMPERATURE DIELECTRIC	#MACALIT . # 110
MATERIALS FOR EMBEDDING AND	ENCAPSULATING AD-427 412
ENCAPSULATING ELECTRONIC	PROPELLANTS BY MEANS OF ULTRASONIC
COMFONENTS (U)	WELDING. (U)
*EMBEDDING SUBSTANCES	OULTRASUNIC RADIATION

T-1 UNCLASSIFIED

AD-729 680

THE EFFECT OF FLUIDS

.SEDIMENTARY ROCK

CONSTANTS OF ROCKS. (U)

AND CYCLIC LOADING ON THE ELASTIC

ENCAPSULATING RESINS

ENCAPSULATION OF

AND POTTING COMPOUNDS(U)
•EMBEDDING SUBSTANCES

AD-096 112

AD-448-420-

## ENC-HIC

	MICROWAVE DIODE AD-822 014
•CAPACITORS	
STUDY. LACQUER FILM CAPACITORS (U)	AVALANCHE DIODES
INDUSTRIAL PREPAREDNESS AD-257 829	MICROWAVE DIODE AD-821 919 RESEARCH.(U)
*EXPANDED PLASTICS	HICROWAVE DIODE AD-821 915
ASSURANCE OF POTTING PLASTIC. (U)	*ENCAPSULATION
ENCAPSULATING FOAMS AND QUALITY	HICROENCAPSULATION (U) AD-827 785
THE IMPROVEMENT OF AD-646 915	MIRRAULIPARAM ARIAM AND
THE THE DAUGHENT OF THE PARTY OF	*ETHYL CELLULOSE
• POWER	SEEDING MATERIALS. (U)
RECTIFIERS(U)	HICROENCAPSULATED CLOUD AD-722 448
VOLTAGE SILICON CONTROLLED	MICOGRAPAN ARCA CARA CARA CARA CARA CARA CARA CA
HIGH CURRENT AND HIGH AD-289 291	·ELECTRIC DISCHARGES
Mich augustus and made and and and	DISCHARGE STUDIES, (1)
• ELECTRONIC SWITCHES	LOW PRESSURE ELECTRICAL AD-605 984
DEVELOPHENT PROGRAM. (U)	
FOUR-LAYER DIODE AD-669 850	• ENCAPSULATION
	RESINS, (U)
•INTEGRATED CIRCUITS	FOAM-IN-PLACE ENCAPSULATING
MICHOCIRCUITS.(U)	LOW-LOSS STYRENE-TYPE AD-628 927
PLASTIC ENCAPSULATED	•
FAILURE MECHANISMS IN AD-689 224 .	·INTEGRATED CIRCUITS
•	CIRCUIT TECHNIQUES. (U)
STRAIN GAGES	LOW COST INTEGRATED AD-635 187
STEAM ENVIRONMENT, (U)	
STRAIN GAGE INSTALLATION FOR USE IN	·INTEGRATED CIFCUITS
DYNAMIC ANALYSIS. CHCAPSULATED	CIRCUIT TECHNIQUES. (U)
TEMPERATURE INSTRUMENTATION FOR	LOW COST INTEGRATED AD-671 491
EVALUATION OF HIGH AD-472 229	
· · · · · · · · · · · · · · · · · · ·	*PACKAGED CIRCUITS
*DIODES	FILM HICHOCIRCUITS, (U)
TRANSISTORS (U)	ENCAPSULATION TECHNIQUES FOR THIN
ENGINEERING SERVICES ON AD-241 938	LEAD ATTACHMENT AND AD-611 752
	च  - चण्डाम्च  स्वस्थाम्याण्यक्ताः
•STEEL	*EMBEDDING SUBSTANCES
EFFECTS STUDIES. (U)	POWER CYCLEP.(U)
TECHNIQUES FOR THE IRRADIATION	1.5-KW SOLID-STATE AD-726 018
ENCAPSULATION AD-430 751	- 10002151002
ALLEGATA	RELIABILITY.(U) •TRANSISTORS
•VIRUSES • (U)	PLASTIC EFFECTS ON SEMICOMOUCTOR
VIRUSES.(U)	INVESTIGATION OF AD-054 206
ENCAPSULATION OF AD-620 422	INVESTIGATION OF AN ARM TOL
• CONTAINERS	• CMBEDDING SUBSTANCES
FOODS(U)	BIBLIOGRAPHY (U)
ENCAPSULATION OF AD-284 005	A PARTIALLY ANNOTATED
FUCADAM INTON AS AR ARM DOT	SEFORE, DURING AND AFTER ASSEMBLY:
•ELECTRONIC EQUIPMENT	COMPONENTS OF ELECTRICAL MODULES
REVIEW, (U)	OF EMBEDDING MATERIALS AND
ELECTRONIC PARTS IN PLASTICS: A	INSPECTING AND TESTING AD-296 396
Floritopule Batto au managemen.	a construit a

T-2 UNCLASSIFIED RESEARCH.(U)
\*AVALANCHE DIODES

MICRO-NOTES. AD-671 797
INFORMATION ON MICROELECTRONICS FOR
NAVY EQUIPMENTS.(U)
•NAVAL EQUIPMENT

MICRO-NOTES. AD-690 445
INFORMATION ON MICROELECTRONICS FOR
NAVY EQUIPMENTS.(U)

\*NAVAL EQUIPMENT

MICRO-NOTES. AD-719 108
INFORMATION ON MICROELECTRONICS FOR
NAVY EQUIPMENTS.(U)
\*MICROMINIATURIZATION(ELECTRONICS)

MICRO-NOTES. AD-828 791
INFORMATION ON MICROELECTRONICS FOR
NAVY EQUIPMENTS. (U)
•NAVAL EQUIPMENT

HICRO NOTES. AD-846 071
INFORMATION ON MICROELECTRONICS FOR
NAVY EQUIPMENTS. (U)

NAVAL EQUIPMENT

MINIATURE THIN FILM AD-602 270 INDUCTORS (MODIFICATION NO. 2).(U)

MINIATURE ELECTRONIC EQUIPMENT

NONCOMMUNICATIONS AD-443 097
EXPENDABLE JAMMER INVESTIGATIONS.
VOLUME D. MECHANICAL
DEVELOPMENT.(U)
PRADIO JAMMING

OPTIMIZATION OF AD-269 461
THERMOELECTRIC ENERGY CONVERTERS(U)
\*ELECTRIC POWER PRODUCTION

OPTIMIZATION OF AD-269 897
THERMOELECTRIC ENERGY CONVERTERS(U)
\*ELECTRIC POWER PRODUCTION

PACKAGED CIRCUITS AD-704 929
VOLUME 1-(U)
PPACKAGED CIRCUITS

PEH FOR TRANSISTOR AD-286 907

٠.

MANUFACTURING PROCESS IMPROVEMENT(U)

TRANSISTORS)

PEM FOR TRANSISTOR AD-433 654
MANUFACTURING PROCESS
IMPROVEMENT.(U)
TRANSISTORS

PRELIMINARY AD-660 349
INVESTIGATION OF PLASTIC
ENCAPSULATED TRANSISTORS.(U)
\*TRANSISTORS

PREPARATION OF AD-729 691 CAPSULES.(U)
•ENCAPSULATION .

PRODUCTION ENGINEERING AD-602 939
MEASURES TO INCREASE TRANSISTOR
RELIABILITY FOR THE 2N656.(U)
•TRANSISTORS

PRODUCTION ENGINEERING AD-604 196
MEASURE FOR THE IMPROVEMENT OF
GERMANIUM ALLOY POWER
TRANSISTORS.(U)
•TRANSISTORS

PRODUCTION ENGINEERING AD-435 114

MEASURE ON 2N1708 SILICON PLANAR

EPITAXIAL TRANSISTOP. VOLUME 1.(U)

\*TRANSISTORS

PRODUCTION ENGINEERING AD-294 110
MEASURE RELIABILITY THRU PROCESS
IMPROVEMENT(U)

MANUFACTURING METHODS

RELIABILITY ANALYSIS OF AD-425 956 X-BAND TUNNEL DIODES.(U) TUNNEL DIODES

RELIABILITY EVALUATION AD-702 292
OF PLASTIC INTEGRATED CIRCUITS (U)
OINTEGRATED CIRCUITS

RELIABILITY EVALUATION AD-722 047
OF PLASTIC INTEGRATED CIRCUITS.(U)
\*INTEGRATED CIRCUITS

T-7 UNCLASSIFIED RESEARCH AND AD-628 618
DEVELOPMENT LOW COST INTEGRATED
CIRCUIT TECHNIQUES (U)
INTEGRATED CIRCUITS

RESEARCH AND AD-291 489
DEVELOPMENT OF THERMOCOUPLE ENERGY
CONVERTERS(U)
•ENCAPSULATION

RESEARCH STUDIES ON THE AD-827 272 DISSEMINATION OF SOLID AND LIQUID AGENTS (U) CHEMICAL WARFARE AGENTS

RESISTORS FOR AD-489 906
MICROPOWER CIRCUITS (U)
PRESISTORS

RHEOLOGY OF ROD-LIKE AD-849 289

PARTICLES IN VISCOUS MEDIA. PART

3. FORMATION OF COMPOSITES FROM

SINGLE FIBERS. (U)

• COMPOSITE MATERIALS

STRESS ANALYSIS OF AD-628 877
ENCAPSULATION MATERIALS FOR WELDED
MODULES.(U)
MODULES(ELECTRONIC)

STRESS INDUCED AD-715 784
INTERMITTENT FAILURES IN
ENCAPSULATED MICROCIRCUITS-IU)
\*INTEGRATED CIRCUITS

A STUDY IN TERMINAL AD-718 JJ6
BENDING OF UNIFORM AND ENCAPSULATED
WIRE ROPE WITH LINEAR AND NONLINEAR CONSTITUTIVE EQUATIONS, (U)
•CABLES(HECHANICAL)

A STUDY OF THE AD-265 874

ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL(U)

ANIDES

A STUDY OF THE AD-245 895 ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL(U) . •ENCAPSULATION

> T-4 UNCLASSIFIED

A STUDY OF THE AD-601 772 ENCAPSULATION OF HIGH ENERGY SUBSTANCES, (U) OLIQUID ROCKET PROPELLANTS

THERMAL ANALYSIS.

AD-722 405

ADVANCED AUTOPILOT FLATPAK HODULE

DESIGN RECOMMENDATIONS, (U)

MODULES(ELECTRONICS)

TRANSISTOR, VHF, AD-804 \$51
SILICON, POWER, LINEAR, 20-MHZ, 100
WATTS PEP-(U)
TRANSISTORS

VACUUM DE-GASSING OF AD-412 282 ENCAPSULANTS, (U) •ENCAPSULATION

#### PERSONAL AUTHOR INDEX

WADAMS, LEON M.

PREPARATION OF CAPSULES. AD-729 691

\*ANDERSON, JERROLD L.

ENCAPSULATION OF VIRUSES.
AD-620 933

MICROENCAPSULATED CLOUD SEEDING MATERIALS:
AD-722 448

FANCERSON. R. J.

INVESTIGATION OF PLASTIC EFFECTS ON SEMICONDUCTOR RELIABILITY. AD-854 306

\*ATALLA: M.M

ENGINEERING SERVICES ON TRANSISTORS AD-261 938

\*BARNES, S.H

PRODUCTION ENGINEERING MEASURE RELIABILITY THRU PROCESS IMPROVEMENT AD-294 110

+BARR+ F.A

DEVELOPMENT OF ULTRA HIGH
TEMPERATURE DIELECTRIC MATERIALS
FOR EMBEDDING AND ENCAPSULATING
ELECTRONIC COMPONENTS
AD-258 395

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-265 499

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPOSENTS AD-266 161 \*BEVINGTON, JOHN R.

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.
AD-703 292

PELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS. AD-722 043

\*BLACK ROBERT

A STUDY IN TERMINAL BENDING OF UNIFORM AND ENCAPSULATED WIRE ROPE WITH LINEAR AND NON-LINEAR CONSTITUTIVE EQUATIONS, AD-718 336

\*BREEN. W. H.

MICROENCAPSULATION. AD-823 785

BROWN, A. G.

MICROENCAPSULATION. AD-823 785

\*BUTZ, S. DAVID

ENCAPSULATION OF VIRUSES.
AD-620 933

\*CANEPA. R.

PRELIMINARY INVESTIGATION OF PLASTIC ENCAPSULATED TRANSISTORS. AD-660 349

+CHANG, Z. F.

TRANSISTOR, VHF, SILICON, POWER, LINEAR, 30-MHZ, 100 WATTS PEP. AD-804 551

\*CHERON. THEODOPE

CRYSTAL GROWTH AND CRYSTALLOGRAPHY.
A LITERATURE SURVEY
AD-274 642

P-1 UNCLASSIFIED

CHY-GRA

#CHIEN. F

PRODUCTION ENGINEERING MEASURE RELIABILITY THRU PROCESS IMPROVEMENT AD-294 110

\*CICCOLELLA, D. F.

MICROVAVE DIODE RESEARCH. AD-821 915

MICROWAVE DIODE RESEARCH.
AD-822 016

\*COOK, JAKES P.

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.
AD-722 043

\* \* \*

\*DAVIS. CHARLES

RELIABILITY ANALYSIS OF X-BAND TUNNEL DIODES. AD-625 956

\*DAVIS, TERRY R.

DEVELOPMENT OF MULTIPURPOSE CAPSULAR ADHESIVE SYSTEMS. AD-730 908

\*DEFELICE, A.

VACUUM DE-GASSING OF ENCAPSULANTS, AD-412 282

\*DE LOACH, B. C., JR

MICROWAVE DIODE RESEARCH.
AD-82: 915

DODSON, G.A

ENGINEERING SERVICES ON TRANSISTORS AD-261 938

\*ENGELHARDT F. J. O.

LOW-LOSS STYRENE-TYPE FOAM-IN-PLACE

ENCAPSULATING RESINS

\*EVANS+ F. C.

THE IMPRO/EMENT OF ENCAPSULATING FOAMS IND QUALITY ASSURANCE OF POTTING PLASTIC. AD-646/915

\*EVERETY PATRICK N.

LEAD AT ACHMENT AND ENCAPSULATION TECHNIQUES FOR THIN FILM MICFOCIRCUITS, AD-611 752

\*EVERSON, THOMAS

DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY MIXES. AD-727 680

\*FIRTH MILTON

NONCOMMUNICATIONS EXPENDABLE JAMMER INVESTIGATIONS. VOLUME 3. MECHANICAL DEVELOPMENT. AD-443 097

\*GIBBONS, G.

MICROWAVE DIODE RESEARCH.
AD-822 016

\*GIBSON. R. W.

MICROENCAPSULATION. AD-823 785

+6LEASON. F. R.

MINIATURE THIN FILM INDUCTORS
(MODIFICATION NO. 2).
AD-602 270

+GRANGER, 6. F.

PRODUCTION ENGINEERING MEASURE ON 2N1708 SILICON PLANAR EPITAXIAL TRANSISTOR. VOLUME I.

P-Z UNCLASSIFIED AD-435 114

\*HABERER. JOHN R.

STRESS INDUCED INTERMITTENT
FAILURES IN ENCAPSULATED
MICROCIRCUITS.
AD-715 984

\*HALL, J. E.

THERMAL ANALYSIS. ADVANCED
AUTOPILOT FLATPAK MODULE DESIGN
RECOMMENDATIONS.
AD-722 405

\*HAWTHORNE. J. R.

ENCAPSULATION TECHNIQUES FOR NRL IRRADIATION EFFECTS STUDIES. AC-430 751

\*HILBELINK, RONALD D.

DEVELOPMENT OF MULTIPURPOSE CAPSULAR ADHESIVE SYSTEMS. AD-730 908

\*HSIEH PAUL Y

A STUDY OF THE ENCAPSULATION APPLICABLE TO LIQUID ROCKET FUEL AD-265 894

A STUDY OF THE ENCAPSULATION
APPLICABLE TO LIQUID ROCKET FUEL
AD-265 895

\*INGLE: L. V.

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.
AD-722 043

\*KAPFER, VINCENT C.

FAILURE MECHANISMS IN PLASTIC ENCAPSULATED MICROCIRCUITS. AD-689 224

\*KELLEY, LUCILLE T.

PRODUCTION ENGINEERING MEASURE FOR THE IMPROVEMENT OF GERMANIUM ALLOY POWER TRANSISTORS.
AD-604 196

\*KELLEY, NANCY

DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY MIXES. AD-727 680

\*KLEIN\* PHILIPP H

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS AD-265 461

\*KREBS, W. H.

LOW PRESSURE ELECTRICAL DISCHARGE STUDIES, AD-605 984

\*LA MORI, PHILLIP N.

THE EFFECT OF FLUIDS AND CYCLIC LOADING ON THE ELASTIC CONSTANTS OF ROCKS.

AD-129 680

\*LINDEN, ERIK G

ENCAPSULATING RESINS AND POTTING COMPOUNDS AD-096 112

\*LITTLE DAVID R.

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.
AD-703 292

RELIABILITY EVALUATION OF PLASTIC INTEGRATED CIRCUITS.
AD-722 043

\*LLOYD, H.E

INDUSTRIAL PREPAREDNESS STUDY.
LACQUER FILM CAPACITORS

P-3 UNCLASSIFIED AD-257 829

\*LOCONTE: JEREMIAH AL

PRODUCTION ENGINEERING MEASURE FOR THE IMPROVEMENT OF GERMANIUM ALLOY FOWER TRANSISTORS.

AD-604 196

#LUECK ARTHUR

RELIABILITY ANALYSIS OF X-BAND TUNNEL DIODES. AD-625 956

\*LUFTe L.

OPTIMIZATION OF THERMOELECTRIC ENERGY CONVERTERS A0-265 857

\*MALINOWSKI + SREGORY J.

1.5-KW SOLID-STATE POWER CYCLER. AD-726 018

\*MARINACCIO, L. P.

MICROWAVE DIODE RESEARCH.
. AD-821 915

\*MCCARTHY, J.P

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-258 395

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-265 499

DEVELOPMENT OF ULTRA HIGH TEMPERATURE DIELECTRIC MATERIALS FOR EMBEDDING AND ENCAPSULATING ELECTRONIC COMPONENTS AD-266 161 +MCMAHON, WILLIAM E

ENCAPSULATION OF FOODS
AD-284 005

\*METCALF, H.F

EFFECT OF PROCESS VARIABLES ON THE DIMENSIONS AND QUALITY OF EXTRUSION—COATED PROPELLANT GRAINS AD-255 962

\*MISAWA, T.

MICROWAVE DIODE RESEARCH. AD-821 915

\*MOLZON. ARNOLD E.

ENCAPSULATION OF ELECTRONIC PARTS IN PLASTICS: A REVIEW, A. 648 420

\*NAKIM. E. B.

PRELIMINARY INVESTIGATION OF PLASTIC ENCAPSULATED TRANSISTURS. AD-660 349

\*OWENS. GEORGE E

ENCAPSULATING, POTTING, AND
EMBEDDING MATERIALS FOR ELECTRONIC
COMPONENTS AND MODULES. AN
ANNOTATED BIBLIOGRAPHY
AD-265 866

\*PARKS, CHARLES F.

RESISTORS FOR MICROPOWER CIRCUITS.
AD-489 906

\*PETERS. GAVIN H.

DEVELOPMENT OF MULTIPURPOSE CAPSULAR ADHESIVE SYSTEMS. AD-730 908

A STUDY OF THE ENCAPSULATION OF

P-4 UNCLASSIFIED HIGH ENERGY SUBSTANCES. AD-601 772

\*PIERCE: CHARLIE M

INSPECTING AND TESTING OF EMBEDDING MATERIALS AND COMPONENTS—OF ELECTRICAL MODULES BEFORE, DURING AND AFTER ASSEMBLY: A PARTIALLY ANNOTATED BIBLIOGRAPHY AD-296 356

\*POPPOFF. I. G.

RESEARCH STUDIES ON THE DISSEMINATION OF SOLID AND LIQUID AGENTS. 4D-827 272

\*PGSSEMATO, L. R.

PRODUCTION ENGINEERING MEASURE ON 2N1708 SILICON PLANAR EPITAXIAL TRANSISTOR. VOLUME I. AD-435 114

\*RADDING, S. B.

MICROENCAPSULATION, AD-823 785

\*REED, A. C.

LOW PRESSURE ELECTRICAL DISCHARGE STUDIES, AD-605 984

\*REICHHOLD, RALPH

NONCOMMUNICATIONS EXPENDABLE JAMMER INVESTIGATIONS. VOLUME 3. MECHANICAL DEVELOPMENT, AD-443 097

\*ROBBINS, ROBERT C

ENCAPSULATED AEROSOLS
AD-255 010

ENCAPSULATED AEROSOLS
AD-260 926

ENCAPSULATED AEROSOLS AD-265 314

ENCAPSULATED AEROSOLS
AD-283 325

\*ROGERS. MILTON

ANALOG COMPUTER RESEARCH INTO THE ENERGY-EXCHANGE BETWEEN GASES AND SOLIDS. AD-505 159

\*ROSCNZWEIG . R.

TRANSISTOR, VHF, SILICON, POWER, LINEAR, 30-MHZ, 100 WATTS PEP. AD-804 551

\*RULISON, R. L.

MICROWAVE DIOCE RESEARCH. AD-822 016

+SANDERS, J

PEM FOR TRANSISTOR MANUFACTURING PROCESS IMPROVEMENT AD-286 907

\*SANDERS, J. G.

PEM FOR TRANSISTOR MANUFACTURING PROCESS IMPROVEMENT.
AD-433 654

≠SCARLETT, ROBERT M.

FOUR-LAYER DIODE DEVELOPMENT PROGRAM. AD-669 850

\*SCHAAB, CARL K.

DEVELOPMENT OF MULTIPURPOSE CAPSULAR ADHESIVE SYSTEMS. AD-730 908

\*SCHUETZE + CLARKE E

P-5 UNCLASSIFIED ENCAPSULATION OF FOODS AD-284 005

\*SILBERMAN, LOUIS

ENCAPSULATING PROPELLANTS BY MEANS
OF ULTRASONIC WELDING,
AD-427 412

\*SIRINE. G. F.

MICROENCAPSULATION. AD-823 785

\*SMITH, K. D.

MICROWAVE DIODE RESEARCH. AD-821 915

\*SMITH. M. H.

STRESS ANALYSIS OF ENCAPSULATION MATERIALS FOR WELDED MODULES, AD-628 833

\*SPARLING, R. H.

CORROSION PREVENTION/DETERIORATION
CONTROL IN ELECTRONIC COMPONENTS
AND ASSEMBLIES.
AD-815 470

\*STEELC. L. E.

ENCAPSULATION TECHNIQUES FOR NRL IRRADIATION EFFECTS STUDIES. AD-430 751

\*SUTHERLAND RODNEY

EFFECT OF PROCESS VARIABLES ON THE DIMENSIONS AND QUALITY OF EXTRUSION—COATED PROPELLANT GRAINS AD-255 962

\*TAKANO, MASAHARU

RHEOLOGY OF ROD-LIKE PARTICLES IN VISCOUS MEDIA. PART I. FORMATION OF COMPOSITES FROM SINGLE FIBERS. AD-849 285

\* \* \*

+TAMBURRINO, ALFRED L.

FAILURE MECHANISMS IN PLASTIC ENCAPSULATED MICROCIRCUITS. AD-689 224

\*THUMAN, W. C.

RESEARCH STUDIES ON THE
DISSEMINATION OF SOLID AND LIQUID
AGENTS.
AD-827 272

\*TOBIN: JOHN F.

EFFECT OF WATER ABSORPTION ON DIMENSIONAL STABILITY OF ELECTRIC MOTOR ENCAPSULATING MATERIALS. AD-630 566

\*TOLOTTA: S.

EVALUATION OF HIGH TEMPERATURE INSTRUMENTATION FOR DYNAMIC ANALYSIS. ENCAPSULATED STRAIN GAGE INSTALLATION FOR USE IN STEAM ENVIRONMENT.

AD-432 229

\*UMINA. ANTHONY

DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY MIXES. AD-727 680

\*VALLES, A. C.

INVESTIGATION OF PLASTIC EFFECTS ON SEMICONDUCTOR RELIABILITY. AD-854 306

\*WAGNER. STURGER

LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-631 491

LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-635 183

P-6 UNCLASSIFIED . WAGNER. S.

RESEARCH AND DEVELOPMENT LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-628 618 .

\*WALKER. MAURO

LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-631 491

LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-635 183

\*WALKER . M.

RESEARCH AND DEVELOPMENT LOW COST INTEGRATED CIRCUIT TECHNIQUES. AD-628 618

\*WESTCOTT, DONALD E.

DEVELOPMENT OF A STABLE LEAVENING SYSTEM FOR BAKERY MIXES. AD-727 680

\*WINCKLER, G. A. F.

THE IMPROVEMENT OF ENCAPSULATING FOAMS AND GUALITY ASSURANCE OF POTTING PLASTIC. AD-646 915

\*ZGLENICKI, CHARLES

ENCAPSULATING PROPELLANTS BY MEANS OF ULTRASONIC WELDING, AD-427 412

P-7
UNCLASSIFIED

Security Classification			
	NTROL DATA - R &	D	
(Security classification of title, body of abatract and indexi	ng annotation must be ent	nred when the d	verall topart is classified)
DEFENSE DOCUMENTATION CENTER	24	. HEPORT SE	NCLASSIFICATION
Cameron Station Alexandria, Virginia 22314	7	b. GROUP	
3 REPORT TITLE		<del></del>	
ENCAPSULATION			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Bibliography (October 1955 - Se	ptember 1971	)	
5. AUTHOR(5) (First name, middle initial, lest name)			
S. REPORT DATE	70. TOTAL NO OF	PAGES	76, NO. OF REFS
May 1972	114		77
SM. CONTRACT OR GRANT NO.	98. ORIGINATOR'S F	IFFORT NUME	
b. PROJECT NO	DDC-TAS	-72-19-	I .
•	this report)	•	her numbers that may be analyzed
	AD- 740	990	
10. DISTRICUTION STATEMENT			
			·
Approved for public release; d	listribution	unlimit	ed
11. SUPPLEMENTARY NOTES	12. SPONSORING MII	LITARY ACTIV	/1T Y
			į.
13. ABSTRACT			
	* * * * * * * * * * * * * * * * * * *	<del></del>	
Encapsulation used as a pro	tective cove	ring fo	r electronic
Elicupsulation asca as a pro	COVE	1 119 10	i electronic

Encapsulation used as a protective covering for electronic circuits, insulation from moisture and heat, and lacquer film and thin film coatings of capacitors, is the subject of this bibliography. References dealing with failures, cracks, and deterioration effects are amply represented.

Corporate Author-Monitoring Agency, Subject, Title, and Personal Author Indexes are included.

DD . FORM . 1473

UNCLASSIFIED
Security Classification

Sec	uri	ty	Cla	5	sil	ice	ti	20

KEY WORDS			LINK A		LINK B		LINK C	
				WT	ROLE	WT	HOLE	WI
<b>+D161</b> 222222	_		ļ ·					ļ ·
*Bibliographie:	S		Ī					-
*Encapsulation	. +							
Embedding Subs Transistors	stances							l
Manufacturing	Methods		1					,
Films						i		İ
Aerosols			İ	}		1	1	İ
Lacquer Films			1		ļ ·	ļ		
Coatings Electronic Equ Integrated Ci								
Electronic Equ	uipment							l
Integrated C11	rcuits				'			٠.
Mica Microminiatur	ization/E	lectronics						1
Naval Equipme	1	16001011105)		1	1	1		
Packaged Circ	uits							
Packaging			}		1			1
Dielectrics			1	1				
			1		1			,
•						1		
				1	l	İ		١,
					l			
					1			
		*Garden		†	]	1		
					1	<b>1</b>		1
			1		Į.			
			1	1		1		
				[			-	-
			1	]			1	
			i			1		ļ ·
						1		
							1	
					}			
							1	'
			1					
								*